




Life Science Catalog

Products, user tips, and practical knowledge for life science applications.

BRAND. For lab. For life.®



Simple, easy, and efficient

Your life science applications with products from BRAND

At BRAND you will find the right consumables and liquid handling instruments for PCR, microbiology, cell culture and many other life science applications.

Each of our products emphasizes simple and easy lab work and an efficient workflow for your experiments. In this catalog, for example, find out how you can minimize evaporation losses during PCR (page 105) or achieve efficient cell growth using our cell culture inserts (page 74).

Efficient work also involves training and information. For every product, you will find tips and advice acquired from practical experience. Additional application notes and technical information are available in our knowledge database at www.brand.de.

BRAND, For lab, For life.®

Quality "Made in Germany" from BRAND



Cleanroom quality

BRAND disposables for the field of life sciences are manufactured under controlled conditions in Germany, in one of the world's largest cleanrooms for laboratory disposables (ISO 14644-1 Class 5, 7 and 8).

Continuous cleanroom monitoring, accompanied by precise regulation of the ambient conditions, results in high temperature stability throughout the entire production area. In combination with batch-related monitoring of the raw materials and end products, this stability guarantees the consistently high quality of BRAND life science products.

Quality of raw materials + High-quality granulates

+ Extensive testing of incoming goods

Production quality standards/controls

- + Cleanroom classes in accordance with ISO standards
- + Continuous cleanroom monitoring
- + High-quality injection molding tools
- + Quality controls during production
- + Exclusion of additives, such as mold release agents, in the production process

End product inspection

Depending on the product,

- + Leak test
- + Compatibility test

Simple, easy, and efficient work - some examples:



Unlimited flexibility with BRAND Insert 2in1 cell culture inserts

Page 78



Greater sensitivity during qPCR reactions with BRAND 384-well PCR plates

Page 109



Proliferation of CHO cells on BRAND*plates*® cellGrade™ surface

Page 64



lid closure

Page 132



Quality of raw materials

Sensitive applications, such as enzyme tests, PCR or the purification of nucleic acids and proteins, require the use of plastic disposables of the highest quality. For the production of pipette tips and PCR products BRAND uses specially selected PP types that are free of the additives di(2-hydroxyethyl) methyldodecylammonium (DiHEMDA) and 9-octadecenamide (oleamide). These two additives, which are often found in PP granulates, can interfere with biological tests and lead to false results. When source materials are selected for life science products, BRAND ensures any substances that could leach out of the raw material and influence the biological tests are reduced to the minimum necessary for processing. Mold release agents, such as stearate and erucic acid amide, are not used in the production process.

BIO-CERT®

BIO-CERT® products from BRAND meet the highest quality standards and offer quality levels dedicated to the application. In addition to the general Certified Quality Label, special quality levels for PCR, cell culture and liquid handling are available. This means you can quickly and easily find the optimal BIO-CERT® products for your application.

Find the right BIO-CERT® quality level for your application

| | CERTIFIED BIO-CERT® | BIO-CERT® | PCR BIO-CERT® | BIO-CERT® |
|---|------------------------|-----------|------------------|-----------|
| Cleanroom class 8 according to ISO 14644-1 | ✓ | ✓ | ✓ | ✓ |
| Free of DNA* | ✓ | ✓ | ✓ | ✓ |
| Free of RNase | ✓ | ✓ | ✓ | ✓ |
| Free of DNase | ✓ | ✓ | ✓ | ✓ |
| Free of pyrogens, according to LAL test ** | ✓ | ✓ | ✓ | ✓ |
| Sterile according to ISO 11137 | | ✓ | | ✓ |
| Free of cytotoxic substances acc. ISO 10993-5 | | ✓ | | |
| Free of PCR inhibitors | | | ✓ | |
| Free of ATP | | | | ✓ |

 $^{^{\}star}\,\text{human and bacterial DNA,}\,\,^{\star\star}\,\text{according to Limulus Amebocyte Lysate (LAL) test, detection limit 0.01\,EU/ml}$

Contents

__ Chapter I _____

© CELL CULTURE & MICROBIOLOGY

| | 1 | Cell culture | 10 - 85 |
|--------------|-----|-----------------------------------|---------|
| | 1.1 | Counting chambers | 11 |
| | 1.2 | Centrifuge tubes with screw cap | 17 |
| | 1.3 | Media bottle | 20 |
| | 1.4 | Cryogenic tubes | 22 |
| | 2 | Microbioloy | 27 - 38 |
| | 2.1 | seripettor [®] | 28 |
| | 2.2 | Culture and sample tubes | 30 |
| | 2.3 | Erlenmeyer flasks | 32 |
| | 2.4 | Centrifuge tubes | 34 |
| | 2.5 | Petri dishes | 36 |
| | 2.6 | Inoculation loops | 36 |
| \mathbb{Q} | 3 | Sample analysis | 39 - 46 |
| | 3.1 | Cuvettes | 40 |
| | 3.2 | Microscope slides Cover glasses | 44 |
| | 3.3 | Slide boxes | 45 |
| | 3.4 | Staining troughs | 46 |
| 0000 | 4 | Assay plates | 47 - 85 |
| 0000 | 4.1 | Non-treated plates | 48 |
| | 4.2 | Microplates for immunoassays | 54 |
| | 4.3 | Microplates for cell culture | 60 |
| | 4.4 | Cell culture inserts | 72 |

Chapter II _____

PCR & qPCR

| 5 | Sample preparation | 88 - 92 |
|------|--|-----------|
| 5.1. | PCR-suitable microtubes | 89 |
| 6 | PCR tubes for small and medium sample throughput | 93 - 100 |
| 6.1 | Single PCR tubes | 94 |
| 6.2. | PCR strips | 97 |
| 7 | PCR plates for medium and high sample throughput | 101 - 111 |
| 7.1 | 24-well PCR plates 48-well PCR plates | 102 |
| 7.2 | 96-well PCR plates | 104 |
| 7.3 | 384-well PCR plates | 109 |
| 8 | Sealing options | 112 - 119 |
| 8.1 | PCR cap strips | 113 |
| 8.2 | Sealing films | 116 |

__ Chapter III _____

SAMPLE STORAGE

| 9 | Sample storage down to -20 °C | 124 - 130 |
|------|---|-----------|
| 9.1 | Microtubes with snap lid | 125 |
| 9.2 | Microplates, PP Deep-well plates, PS | 128 |
| 10 | Sample storage down to -80 °C | 131 - 142 |
| 10.1 | Microtubes with lid closure | 132 |
| 10.2 | Microtubes with screw cap and plug seal | 134 |
| 10.3 | Deep-well plates, PP | 137 |
| 10.4 | Tube racks | 141 |
| 11 | Sample storage down to -196 °C | 143 - 151 |
| 11.1 | Microtubes with screw cap and silicone seal | 144 |
| 11.2 | Cryogenic tubes | 150 |





CELL CULTURE & MICROBIOLOGY

Identifying unknown pathogens and understanding cell signaling pathways (e.g. tumor biology or neurodegenerative diseases) are ongoing sources of scientific challenges for researchers. More and more, interdisciplinary research is being used to search for previously undiscovered active ingredients and innovative potential therapies through combining cellular and microbiological methods.

The only way to achieve the clear results essential to this research is by using the highest-quality consumable materials possible. To offer the best possible quality and purity for challenging analyses, BRAND continues to refine its Life Science products for cell culture and microbiology while optimizing manufacturing processes.



Chapter I

Cell culture & microbiology work areas

Cell banking and cryo storage

Cell cultivation | microbiology

Assaying



1.1 Counting chambers page 11



1.2 Centrifuge tubes with screw cap page 17



2.1 seripettor® page 28



2.2 Culture and sample tubes page 30



3.1 Cuvettes page 40



3.2 Microscope slides and cover glasses page 44



1.3 Media bottle page 20



1.4 Cryogenic tubes page 22



2.3 Erlenmeyer flasks page 32



2.4 Centrifuge tubes page 34



3.3 Slide boxes page 45



3.4 Staining troughs page 46



2.5 Petri dishes page 36



2.6 Inoculation loop page 36



4. Assay plates page 47

Liquid Handling 10 μl - 50 ml

Liquid Handling 1 μl - 25 ml

Liquid Handling 1 μl - 50 ml



1. Cell culture

Analyzing cell cultures (from cell lines or primary cells) can provide information on the effects of active ingredients, help interpret physiological conditions, and help explain pathophysiological changes.

Monitoring cell numbers using a hemocytometer (counting chamber) is an essential preparatory step for any cell culture. Only by determining these initial values researchers can calculate generation times or check cell densities before seeding them in culture vessels or put them for cryopreservation.

To support a wide range of experimental conditions, assay plates and culture vessels need to meet a variety of cellular requirements. Because of this, BRAND offers a broad range of certified cell culture products for many different applications in the areas of pharmacology, toxicology and tissue engineering including cell counting, cryopreservation, and cell cultivation and analysis in multiwell and microtiter plates.




1.1 Counting chambers



- ✓ BLAUBRAND® quality
- ✓ Outstanding measurement precision
- ✓ 100% certified quality

Determining cell counts is a key foundation for monitoring cellular proliferation. From patient samples to cell cultures, precision measuring equipment like BLAUBRAND® counting chambers ensure precise cell counts.



Applications

- + Counting blood cell types
- + Cell counts in cerebrospinal fluid
- + Quantifying bacteria and fungal spores
- + Counting plant pollen
- + Determining cell counts of cultivated cell lines and primary cells
- + Quantifying immobilized sperm


Features

- + Specialized optical glass
- + Certified BLAUBRAND® quality
- + In accordance with DIN 12847
- + Available with and without spring clips
- + Includes 2 hemocytometer cover glasses
- + 2 counting grids per chamber for counts

User information

Object counting with BLAUBRAND® counting chambers

- The aperture on the microscope condenser must be nearly closed.
- For counts in the 4 large squares at the corners, the use of a 10x objective (100x zoom) is recommended.
- A 40x objective is a better choice for counts in the central large square (such as for erythrocytes, algae cells and yeast).
- Double counts should be completed for all cell counts, especially if a sample includes a small number of cells.
- Allow the cells sufficient time to settle before starting a cell count.
- The more fields that are counted, the more accurate the count will be.
- The difference between the total counts for both counting grids may not exceed ten cells. The average for the counts is then used in the calculation formula.



The arrow indicates the process for counting, for instance from top to bottom. The light blue line in all three of the group squares shown above represents the boundary line, while the dark blue lines are guide lines.

Cells touching the boundary lines of the counting square on two adjacent sides are also included in the count. The drawing shows this for the top and right boundary lines. Cells to be included in the count are represented as solid black circles. Cells that touch the bottom and left boundary lines, in contrast, are not included in the count. These cells are represented as white circles with black outline.

Equation for particle determination (for general use)

Particles per μ l volume = Counted particles

Counted surface $(mm^2) \cdot Chamber depth (mm) \cdot Dilution$

Example: Erythrocytes

Chamber: Improved Neubauer

1. Counted particles: 528 erythrocytes

2. Counted surface: 5 group squares, equivalent to 0.2 mm²

3. Chamber depth: 0.1 mm

4. Dilution: 1:200

Calculation

 $528\cdot 200$

0.2 · 0.1 · 1

= $5.28 \cdot 10^6$ Ery/ μ l blood

Models

Counting chamber with spring clips



Counting chamber without spring clips








BRAND counting chamber and hemocytometer cover glasses are CE-marked according to IVD-Directive 98/79 EC.





Technical information & Ordering data











Ruling

Large squares "L"

Large central square

Chamber depth Special feature

For quantification of

Neubauer improved

area of 1 mm² each with 16 group squares of 0.0625 mm² each

area of 1 mm² each with 25 group squares of 0.04 mm² each area mini square: 0.0025 mm²

0.1 mm

all group squares have triple boundary lines on each side

Leucocytes "L" counter square other cell types

with spring

clips

Erythrocytes "E" large central Thrombocytes veast bacteria

without spring clips

717805 717820

Neubauer improved bright-line

area of 1 mm² each with 16 group squares of 0.0625 mm² each

area of 1 mm² each with 25 group squares of 0.04 mm² each area mini square: 0.0025 mm²

0.1 mm

all group squares have triple boundary lines on each side; rhodium-coated chamber bottom for reversed microscopy (dark

Leucocytes "L" counter square other cell types

Erythrocytes "E" large central Thrombocytes square veast bacteria

without spring clips

717810

Neubauer

area of 1 mm² each with 16 group squares of 0.0625 mm² each

area of 1 mm² each with 25 group squares of 0.04 mm² each area mini square: 0.0025 mm²

0.1 mm

Leucocytes "L" counter square other cell types

Erythrocytes "E" large central Thrombocytes square yeast bacteria

without spring clips 718605

with spring clips 718620

Cat. No.



LxW

Thickness [mm] Flatness tolerance [µm]

Pack of

Cat. No.





Hemocytometer cover glasses for Neubauer improved and **Neubauer counting chambers**

20 x 26 mm

0.4

± 3

100 pieces (10 boxes at 10 cover glasses)


723015


BLAUBRAND® counting chambers are delivered with two matching hemocytometer cover glasses.


Technical specifications are listed on the following two pages.




(continued counting chambers)












Large central square







Ruling

Large squares

Large central square

Chamber depth

Special feature

For quantification of

Thoma

not present

area: 1 mm²

with 16 group squares of 0.04 mm²

area mini square: $0.0025 \; mm^2$

0.1 mm

Erythrocytes Thrombocytes other cell types

without spring clips

718005 718620

with spring

clips

Bürker

area of 1 mm² each with double line divided into 16 group squares of 0.04 mm² each

area: 1 mm²

with 16 group squares of 0.04 mm²

area mini square: 0.0025 mm²

0.1 mm

double lines create mini squares of 0.0025 mm² each in all large squares

Erythrocytes Thrombocytes other cell types

without spring clips

718905

clips 718920

with spring

Bürker-Türk

area of 1 mm² each with double line divided into 16 group squares of 0.04 mm² each

area: 1 mm²

with 16 group squares of 0.04 mm²

area mini square: 0.0025 mm²

0.1 mm

combination of the Bürker and Thoma systems

Erythrocytes Thrombocytes other cell types

without spring clips

719505

with spring clips

719520

Cat. No.

LxW

Thickness [mm] Flatness tolerance [µm]

Pack of

Cat. No.





Hemocytometer cover glasses for Thoma, Bürker and Bürker-Türk counting chambers

20 x 26 mm


0.4

± 3

100 pieces (10 boxes at 10 cover glasses)


723015


Pure white (clear) borosilicate glass, hydrolytic class 1, DIN ISO 8255. Refractive index $n_e = 1.52 \pm 0.01$; Abbe number $v_e = 56.5 \pm 0.5$. Hemocytometer cover glasses differ from ordinary cover glasses by their plain ground and polished surface.







(continued counting chambers)








Large central square





Ruling

Large squares

Large central square Chamber depth

Special feature

For quantification of

Fuchs-Rosenthal

area of 1 mm² each with 16 group squares of 0.04 mm² each

no further division

0.2 mm

counting grid size 4 mm x 4 mm total area 16 mm²

cells in the cerebrospinal fluid

Malassez

area of 1 mm² each with 16 group squares of 0.04 mm² each

no further division

0.2 mm

rectangular ruling 2.5 mm x 2 mm

cells in the cerebrospinal fluid nematodes

Nageotte

area of 1 mm² each with 16 group squares of 0.04 mm² each

no further division

0.5 mm

large chamber volume facilitates robust quantification of leucocyte concentrations, even below 10 / µl

cells in the cerebrospinal fluid remaining leucocyte quantities in apheresis concentrates nematodes

Cat. No.

without spring clips

719805

719820

clips

with spring

without spring clips

719005

without spring clips

721305



C€ IVD

Hemocytometer cover glasses for Fuchs-Rosenthal, Malassez and Nageotte counting chambers

LxW

Thickness [mm] Flatness tolerance [µm]

Pack of

Cat. No.

24 x 24 mm

0.4

± 3

100 pieces (10 boxes at 10 cover glasses)

723014

20 x 26 mm

0.4 ± 3

100 pieces

(10 boxes at 10 cover glasses)

723015

22 x 30 mm

0.4

± 3

100 pieces (10 boxes at 10 cover glasses)

723016



Cleaning

We recommend using the disinfectant Mucocit® T to clean counting chambers. Please observe proper validated cleaning procedures for your specific counting chamber.

Mucocit®-T

Instrument disinfecting detergent

Particularly suited for sensitive instruments. Free of phosphates, aldehydes, phenols and chlorine derivates. Fresh scent. CE-marked according to MPG (German Medical Products Law).

| Description | Pack of | Cat. No. |
|----------------|------------|----------|
| 2 liter bottle | 5 | 44822 |
| 5 liter can | 1 | 44825 |



Microbiological efficiency/ concentration for use:

Disinfection of instruments: Bacteria (incl. Tuberculosis and mycobacteria) and fungi with high organic burden according to DGHM/VAH directives:

1% (10 ml/l)/1 hour 2% (20 ml/l)/30 minutes 3% (30 ml/l)/15 minutes

Limited virucidal efficacy* (incl. HIV. HBV. HCV) 1% (10 ml/l)/5 minutes

Inactivation of rotaviruses: 2% (20 ml/l)/5 minutes

* As recommended by the RKI, Federal Health Bulletin 01/2004

Accessories for automated cell counters

Sample cup for Technicon-Analyzer

PS, transparent. Packed in bags of 1000.

| Capacity [ml] | Upper Ø [mm] | Lower Ø [mm] | Height [mm] | Cat. No. |
|------------------|-----------------|-----------------|----------------|----------|
| 1.5 | 15 | 12.2 | 22.7 | 115015 |
| 2 | 14.8 | 12.8 | 24.9 | 115016 |
| 4 | 17 | 13.3 | 38 | 115017 |

Sample cup for COULTER COUNTER®

PS, transparent. PE lid. Pack quantity: 1000 = 4 bags of 250.



| Capacity | Ø | Height | Cat. No. |
|----------|------|--------|----------|
| [ml] | [mm] | [mm] | |
| 20 | 32 | 56 | 722055 |

Push-on caps

PE. Suitable for Technicon 1.5 ml and 2 ml sample tubes. Pack of 1000.








1.2 Centrifuge tubes with screw cap



- ✓ Biologically inert polypropylene for optimal cell and protein recovery
- ✓ Screw cap with plug seal offers protection against leaks
- ✓ Highly transparent PP for optimal sample visibility

Conical centrifuge tubes with screw closures are standard equipment in any cell culture laboratory. Defined dimensions ensure a good fit on commonly available centrifuge tubes. We use the purest, highest-quality materials available during manufacturing, ensuring outstanding sample integrity.

Duo to their excellent mechanical and chemical resistance, centrifuge tubes from BRAND are also a good choice for short-term sample and solution storage.



Applications

- + Adding culture medium
- + Holding cell suspension during passaging
- + Aliquoting and short-term storage of cell culture serum
- + Preparing SDS PAGE collection and separating gel solutions
- + Preparing solutions for protein biochemistry
- + For research use only!

Features

- + PP for good chemical resistance (PE cap)
- + Clear graduation
- + Sterile version available (sterility assurance level SAL 10⁻⁶)
- + Centrifuge up to 3000 x g



User information

Centrifuging information

The centrifuge tubes can withstand up to 3000 x g which meets the requirements of commonly used centrifugation protocols in cell culture.

| General fractionation of whole blood into blood plasma and cellular fractions. | 1500 - 3000 x g |
|--|-----------------|
| Sedimentation of cells in liquor | 1000 x g |
| General centrifuging during passaging of eukaryotic cells | ≤ 600 x g |

Frequently, the duration of centrifugation has a greater impact on cell viability than the relative centrifugal force (RCF).

Caution!

The relative centrifugal force (RCF) depends on the radius of the rotor and the speed (RPM) of the centrifuge.

General conversion formula

$$g = RCF = ((U/min)/1000)^2 \cdot r \cdot 1.118$$

g-value:

Gravitational acceleration

RCF:

Relative centrifugal force (corresponds to the g-value)

Rotation radius

U/min:

Rotor rotations per minute

(speed)

Adding a laboratory film as an additional external seal on the cap reduces the danger of contamination, for example if medium aliquots are to be heated in a water bath or serum is to be heat-inactivated.

Accessories

Test tube rack


PTFE. Excellent chemical resistance. Operating temperature -200 °C to 250 °C. Pack of 1.



| for Ø up to [mm] | Positions | L x W x H [mm] | Cat. No. |
|------------------|-----------|-------------------|----------|
| 13 | 21 | 180 x 60 x 60 | 115510 |
| 19 | 10 | 180 x 60 x 70 | 115515 |
| 30 | 4 | 180 x 60 x 80 | 115520 |




Technical information & Ordering data




Capacity 15 ml


| conical |
|--------------------------------|
| 13 |
| 120 |
| 17 |
| screw cap PE with plug seal |
| 750 pieces (5 x 150) |
| 114817 |



| conical | |
|--------------------------------|--|
| 50 | |
| 114 | |
| 30 | |
| screw cap PE with plug seal | |
| 300 pieces (6 x 50) | |
| 114820 | |



| 50 ml | | |
|--------------------------|----------|--|
| self-standi | ng | |
| 50 | | |
| 116 | | |
| 30 | | |
| screw cap with plug s | | |
| 250 pieces | (5 x 50) | |
| 114822 | | |



| Description | |
|-------------|--|
| Subdivision | |

Description

Height [mm] Outer-Ø [mm]

Cap


Pack of Cat. No.

Subdivision up to [ml]

Subdivision up to [ml]
Height [mm]
Outer-Ø [mm]

Cap
Pack of
Cat. No.


| | _ | | |
|------------------------|----------|----|--|
| conical | | | |
| 13 | | | |
| 120 | | | |
| 17 | | | |
| sterile | | | |
| screw cap with plug | | | |
| 750 pieces | (5 x 150 |)) | |
| 114818 | | | |



| conical |
|--------------------------------|
| 50 |
| 114 |
| 30 |
| sterile |
| screw cap PE with plug seal |
| 300 pieces (6 x 50) |
| 114821 |



| self-standing |
|--------------------------------|
| 50 |
| 116 |
| 30 |
| sterile |
| screw cap PE with plug seal |
| 250 pieces (5 x 50) |
| 114823 |



1.3 Media bottle



- ✓ Bottle and cap made of biologically inert material
- ✓ Larger bottle neck and bottle can be tilted by 45° for easy removal of medium
- ✓ Compatible with bottle top filters

Commonly used media bottles have narrow necks at a height that frequently require researchers to stand in uncomfortable postures over a clean bench when removing media using serological pipettes.

The new cell culture bottle from BRAND has a short profile, a wide bottle neck and can be tilted by 45°, allowing for a relaxed posture during pipetting. Thanks to its heavy weight, the cell culture bottle is always stable – either in a water bath or while using vacuum bottle top filters.



Applications

- + Preparing and storing media and buffers for cell culture
- + Adding media and buffers during sterile filtration
- + Providing medium on a clean bench

- + Bottle made of Boro 3.3
- + Wide bottle neck (GL 56)
- + Suitable for autoclaving
- + Vacuum-tight
- + Clearly legible volume scale



User information

Sterile filtration of cell culture media

- Cell culture medium with added serum should not be autoclaved, since this will reduce or eliminate the biological activity of the contents.
- For sterilizing so-called complete medium, we recommend sterile filtration through a filter with a 0.2 μm pore size.

Cleaning and storage

- The biologically inert PTFE adapter can be autoclaved at 121 °C and depyrogenated at 300 °C.
- The flat sides of the media bottle allow for space-saving storage in shelves and refrigerators.

Technical information & Ordering data



Vacuum-tight media bottle for sterile filtration

| Description |
|-------------|
| Thread |
| Material |
| Pack of |
| Cat. No. |

| bottle with screw cap |
|--------------------------|
| GL 56 |
| Boro 3.3 / PP |
| 1 piece |
| 122710 |

| screw cap |
|-----------|
| GL 56 |
| PP |
| 10 pieces |
| 122750 |

| thread adapter |
|----------------|
| GL 56 / GL 45 |
| PTFE |
| 1 piece |
| 122755 |



Thread Material Pore size [µm] Pack of Cat. No.

Sterile vacuum filter unit

| GL 45 |
|------------------|
| PS, PES membrane |
| 0.2 |
| 12 pieces |
| 122760 |
| |

| GL 45 |
|------------------|
| PS, PES membrane |
| 0.45 |
| 12 pieces |
| 122765 |



Accessories

Silicone tubing

Fits reducer fitting on the bottle top filter.



| Inner-Ø [mm] | Outer-Ø [mm] | Wall thickness [mm] | Cat. No. |
|--------------|--------------|---------------------|----------|
| _ | _ | | |
| 5 | 8 | 1.5 | 143358 |
| 6 | 9 | 1.5 | 143359 |
| 6 | 10 | 2 | 143360 |
| 7 | 10 | 1.5 | 143361 |
| 8 | 12 | 2 | 143362 |

1.4 Cryogenic tubes



- ✓ Safe long-term storage
- ✔ Perfectly sealed containers
- ✓ Highly stable

Cryopreservation is an essential process for halting almost all chemical reactions during long-term storage and for preventing sample degradation. The most commonly used approach is to store samples in the gas phase of a liquid nitrogen tank, or in freezers.

BRAND offers highly stable cryogenic tubes as an ideal choice for safe, long-term storage of biological materials. The right plastic and a precise thread design help perfectly seal these containers, reducing the danger of sample contamination.



Applications

- + Storage of micro-organisms
- + Storage of primary cells
- + Storage of cell lines
- + Storage of blood and serums
- + One-handed, aseptic work
- + Sample transport


- + Extremely stable
- + Available either with a silicone seal or sealing lip
- + Temperature stability to -196 °C
- + Autoclavable at 121 $^{\circ}\text{C}$ (2 bar), according DIN EN 285
- Suitable for centrifuging with up to 14,000 x g (tubes without ring stands)
- + Easy to open by hand with just a 11/4 turn



User information

Handling and safety information

- Cryogenic tubes should not be filled completely, as volumes may expand during freezing. The recommended fill volume is indicated at the upper end of the graduation.
- Cryogenic tubes with silicone sealing rings should not be opened while frozen, as this may damage the silicone seal.
- For safety reasons, BRAND recommends that cryogenic tubes be stored in the gas phase in liquid nitrogen. This reduces the danger of nitrogen penetration in case of improper use.



- Ensuring cell authenticity. Cells to be cryopreserved should be free of contamination and have good viability.
- Prepare cryomedium specific for the cell type, then place the cryomedium and pre-marked cryogenic tubes on ice.
- Harvest the cells, centrifuge to remove the growth media, then suspend the cell pellets in a cool cryomedium.
- Transfer the cell suspension into the cryogenic tubes and start the cooling process.



Advantages of external thread with sealing lip and silicone seal

- Simplifies single-handed operation in comparison to cryogenic tubes with internal thread.
- Reduces the danger of contamination.



Advantages of internal thread

- Space-saving compared to cryogenic tubes with external thread.
- Colored cap inserts snap in farther. Tubes can be removed from the box using the rod (Fig.).
- Uniform exterior diameter improves fit with centrifuge rotors.

Accessories

Cryogenic tube rack

Non-slip due to rubber feet. Locking cryogenic tubes with a foot rim simplifies single-handed opening. For 50 self-standing cryotubes.

Pack of 4.






Storage boxes

With openings on the lid and base to prevent condensation or ice build-up.

Fits into common stainless steel containers. Operating range -196 °C to +121 °C.



| for cryogenic tubes [ml] | Positions | L x W x H [mm] | Pack of | Cat. No. |
|--------------------------|-----------|-------------------|---------|----------|
| | | | | |
| 1.2 and 2 | 81 | 133 x 133 x 52 | 4 | 114862 |
| 3, 4 and 5* | 81 | 133 x 133 x 95 | 5 | 114864 |
| 1.2 and 2** | 100 | 133 x 133 x 52 | 4 | 114866 |

^{*} external thread, ** internal thread



Ice bucket

Durable. rigid polyurethane foam with excellent insulation properties. Operating temperature -196 °C to +95 °C. Pack of 1.

| Capacity [l] | Cat. No. |
|--------------|----------|
| 4.5 | 156100 |

Tubes can be removed from the box using the rod





Cryogenic tubes with external thread

Graduation up to [ml]

Description

Height [mm]

Screw cap

Pack of

Cat. No.



| self-standing |
|---------------|
| |

1.0

41

with silicone seal

1000 pieces (10 bags of 100)

114830



round-bottom

1.8

47

with silicone seal

1000 pieces (10 bags of 100)

114831




self-standing

1.8

with silicone seal

1000 pieces (10 bags of 100)

114832



Description

Graduation up to [ml]

Height [mm]

Screw cap

Pack of

Cat. No.

self-standing


3.0

71

with silicone seal

1000 pieces (10 bags of 100)

114833



self-standing


3.6

76

with silicone seal

1000 pieces (10 bags of 100)

114834



self-standing

4.5

with silicone seal

1000 pieces (10 bags of 100)

114835





Cryogenic tubes with internal thread

Graduation up to [ml]

Description

Height [mm] Screw cap

Pack of

Cat. No.



| 1.2 ml | | (I) ACT |
|-------------------------|----------|---------|
| self-stan | ding | |
| 1.0 | | |
| 41 | | |
| with silic | one seal | |
| 1000 pie (10 bags of | | |
| 114840 | | |




| self-standing |
|---------------------------------|
| 1.8 |
| 48 |
| with silicone seal |
| 1000 pieces (10 bags of 100) |
| 114841 |




| round-bottom |
|---------------------------------|
| 1.8 |
| 47 |
| with silicone seal |
| 1000 pieces (10 bags of 100) |
| 114842 |




| Description |
|-----------------------|
| Graduation up to [ml] |
| Height [mm] |
| Screw cap |
| Pack of |
| Cat. No. |



| round-bottom |
|---------------------------------|
| 3.6 |
| 71 |
| with silicone seal |
| 1000 pieces (10 bags of 100) |
| 114843 |
| |



| 4.0 ml | | 1 1 |
|------------------------|-----------|-----|
| self-sta | nding | |
| 3.6 | | |
| 76 | | |
| with sili | cone seal | |
| 1000 pie (10 bags o | | |
| 114844 | | |
| | | • |



| round-bottom |
|---------------------------------|
| 4.6 |
| 90 |
| with silicone seal |
| 1000 pieces (10 bags of 100) |
| 114845 |

Cap inserts for color coding

PP. Fit for all sizes. Pack of 500.



| Color | Cat. No. |
|--------|----------|
| white | 114850 |
| blue | 114851 |
| red | 114852 |
| green | 114853 |
| yellow | 114854 |







2. Microbiology

Classic microbiological methods such as bioburden testing or creating an enrichment, mixed or pure culture are used in hygiene monitoring, product safety testing and molecular biology.

The BRAND product portfolio offers disposable plastic products and reusable glass products for liquid cultures and other cultures used in pathogen detection or during cloning and plasmid propagation.

2.1 seripettor® bottle-top dispenser



- ✓ Simple and effortless operation
- ✓ Replaceable dispensing cartridge and wearing parts
- ✓ Ideal for serial dispensing

Dispensing small volumes into culture tubes

The seripettor® bottle-top dispenser from BRAND precisely, quickly, and easily dispenses culture media into small-volume vessels with narrow necks, making difficult pipetting unnecessary. The optional flexible discharge tube with safety grip allows for a good reach and for easily placing cannulas using the culture vessel.



Applications

- + Sterile dispensing of buffers and media
- + Luer-lock air filtration system helps maintain sterility
- + Serial dispensing into culture tubes

- + Easy cleaning and maintenance
- + Automatic filling, manual discharge
- + Simple operation
- + Safely handle hot aqueous solutions (up to 60 °C)
- + Can be mounted directly on bottles with a GL 45 thread
- + Sterile dispensing cartridges available



User information

Serial dispensing

The seripettor with GL45 thread adapter fits on most standard laboratory bottles. The flexible discharge tube with grip allows for safe and easy filling of culture tubes.

The seripettor significantly improves efficiency during serial dispensing versus working with pipettes.

Dispensing sterile liquids

1. Mount the valve block with filling tube onto the bottle and cover the valve block with cap. Attach the autoclavable sterile membrane filter (0.2 $\mu m)$ to the air vent opening and autoclave at 121 °C for 15 minutes.

2. On a clean-bench or sterile hood remove the cap from the valve block, screw in a new sterile dispensing cartridge and mount the pump assembly. You're ready to dispense!

Accessories


Dispensing cartridges

Non-sterile and sterile. Piston (PE), cylinder (PP). Not autoclavable.



| Description | Pack of | Cat. No. |
|---------------------------------------|---------|----------|
| 2 ml | 3 | 704500 |
| 10 ml | 3 | 704502 |
| 25 ml | 3 | 704504 |
| 2 ml, sterile (individually wrapped) | 7 | 704507 |
| 10 ml, sterile (individually wrapped) | 7 | 704506 |
| 25 ml, sterile (individually wrapped) | 5 | 704508 |

Additional accessories like pump assembly, discharge tubes and valve sets you will find at shop.brand.de





| Nominal volume | Cat. No. |
|----------------|----------|
| 2 + 10 ml | 704522 |
| 25 ml | 704523 |

Cap for closing valve block

PP, autoclavable (121°C). Pack of 1.

| Description | Cat. No. |
|-------------|----------|
| 2 + 10 ml | 704552 |
| 25 ml | 704554 |



Technical information & Ordering data



Description Subdivision [ml] A* ≤ ± [%] [μl] CV* ≤ [%] [μl] Cat. No.

seripettor®

Items supplied:

seripettor®, discharge tube, filling tube, spare dispensing cartridge and bottle adapters, PP (GL 45/32, GL 45/38, and GL 45/S40).

| 0.2 - 2 ml | | |
|------------|----|--|
| 0.04 | | |
| 1.2 | 24 | |
| 0.2 | 4 | |
| 4720120 | | |

| 1 - 10 ml | | |
|-----------|-----|--|
| 0.2 | | |
| 1.2 | 120 | |
| 0.2 | 20 | |
| 4720140 | | |

| 2.5 - 25 ml | | |
|-------------|-----|--|
| 0.5 | | |
| 1.2 | 300 | |
| 0.2 | 50 | |
| 4720150 | | |

^{*} The values of accuracy and coefficient of variation are final test values referring to the delivered volume. instrument and distilled water at equilibrium with ambient temperature (20 °C/68 °F) and smooth and steady operation. A = Accuracy. CV = Coefficient of variation

2.2 Culture and sample tubes



- ✓ Excellent sample visibility
- ✓ Tight sealing screw caps or grip stoppers
- ✓ Made of glass or plastic (PS)

Culture tubes for creating liquid and agar cultures are used in the fields of food technology, environmental analysis, infection biology or in basic research.


Culture tubes from BRAND stand out for their good resistance to centrifugal forces.

Use the seripettor® to quickly and easily transfer your culture media (or agar) into culture tubes.



Applications

- + Aerobic liquid cultures
- + Anaerobic liquid cultures
- + Stab cultures
- + Agar slant cultures



- + Made of soda lime glass or PS
- + With and without thread
- + PP screw caps with TPE elastomer seal
- + Glass tubes can be autoclaved (121 °C) according to DIN EN 285




Technical information & Ordering data



Culture tubes, glass with screw cap, PP

| Capacity | 6.5 ml | 10 ml | 20 ml | 30 ml |
|------------------------|------------|------------|------------|------------|
| Outer-Ø [mm] | 12 | 16 | 16 | 18 |
| Height [mm] | 100 | 100 | 160 | 180 |
| Wall thickness [mm] | 1 | 1 | 1 | 1 |
| RCF max. | 3000 | 3000 | 1800 | 1100 |
| Pack of | 100 pieces | 100 pieces | 100 pieces | 100 pieces |
| Cat. No. | 113931 | 113935 | 113941 | 113943 |



Culture tubes, glass rimless

| Capacity | 3 ml | 5.5 ml | 7.5 ml | 13 ml | 18 ml | 22 ml | 30 ml |
|------------------------|------------|------------|------------|-----------|------------|------------|------------|
| Outer-Ø [mm] | 10 | 12 | 12 | 16 | 16 | 16 | 18 |
| Height [mm] | 75 | 75 | 100 | 100 | 125 | 160 | 180 |
| Wall thickness [mm] | 0.6 | 0.6 | 0.6 | 0.7 | 0.7 | 0.7 | 0.7 |
| RCF max. | 3000 | 3000 | 3000 | 2600 | 1800 | 1500 | 900 |
| Pack of | 250 pieces | 250 pieces | 144 pieces | 78 pieces | 105 pieces | 100 pieces | 121 pieces |
| Cat. No. | 114105 | 114106 | 114110 | 114115 | 114120 | 114125 | 114130 |



Sample tubes, PS (disposable)

| Capacity | 12 ml | 5 ml |
|------------------------|--------------|---------------|
| Outer-Ø [mm] | 16 | 12 |
| Height [mm] | 100 | 75 |
| Wall thickness [mm] | approx. 1.1 | approx. 0.9 |
| RCF max. | 2000 | 2000 |
| Pack of | 2000 pieces | 4000 pieces |
| Cat. No. | 114715 | 114760 |
| Grip stopper | PE-LD | PE-LD |
| Pack of | 10000 pieces | 20 000 pieces |
| Cat. No. | 114720 | 114730 |



Racks for culture tubes and test tubes

Size 265 x 126 mm. Will not float in waterbath.

Operating temperature -20 °C to +90 °C, autoclavable.



| | | 7 | 2 |
|----|---|---|---|
| * | | | ₹ |
| | - | | |
| 10 | - | 4 | |
| | | | |

| For tubes up to Ø | 13 mm | 16 mm | 18 mm | 20 mm |
|-------------------|----------|----------|----------|----------|
| Height [mm] | 75 | 75 | 75 | 75 |
| Positions | 6 x 14 | 5 x 11 | 5 x 11 | 4 x 10 |
| Pack of | 5 pieces | 5 pieces | 5 pieces | 5 pieces |
| Cat. No. white | 4340000 | 4340060 | 4340010 | 4340020 |
| Cat. No. blue | 4340001 | 4340061 | 4340011 | 4340021 |
| Cat. No. red | 4340002 | 4340062 | 4340012 | 4340022 |

2.3 Erlenmeyer flasks



- ✓ Good mechanical resistance
- ✓ Easy to clean
- ✔ Diverse applications

Using Erlenmeyer flasks as vessels for larger liquid cultures offers the advantage of good gas exchange between the culture medium and gas phase.

BRAND Erlenmeyer flasks are made of borosilicate 3.3 glass. This makes them especially resistant to breakage, even after multiple cleaning cycles. The good mechanical resistance of BRAND Erlenmeyer flasks reduces the danger of breakage in automatic shakers.



Applications

- + Aerobic liquid cultures
- + Pure cultures
- + Enrichment cultures
- + Static cultures

- + Borosilicate 3.3 glass
- + With beaded rim
- + Clearly legible divisions
- + Easy to clean



User information

Determining microbial growth in a suspension culture

Turbidity measurement has become an established, routine method for determining biomasses in a suspension culture. Turbidity correlates directly with cell count, and follows the Beer-Lambert law.

Important note:

Optical density (OD) measurement is performed at 600 nm because no pigment is present that adsorbs this wavelength.

At an $OD_{600} \le 0.8$, the dry cell mass/ml corresponds well to the Beer-Lambert law. This means that light scatter is proportional to the number of particles released (cells).

If photometric measurements indicate an $OD_{600} \ge 0.8$, then the sample must be diluted and measured again.

Accessories

Standard cuvettes macro and semi-micro

PS and PMMA. Grouped by mold cavity number, 10 mm light path. Pack of 1000 (10 boxes of 100 cuvettes per box.)





Cuvette rack

PP, gray. Numbered positions. Autoclavable (121 °C). Suitable for standard 10 mm path-length cuvettes. Pack of 1.



| Description | Length [mm] | Width [mm] | Height [mm] | Cat. No. |
|-----------------|----------------|---------------|----------------|----------|
| for 16 cuvettes | 210 | 70 | 38 | 759500 |

Additional cuvettes are available in the Sample analysis section, starting on p. 40

Technical information & Ordering data



Erlenmeyer flasks narrow neck

| Capacity | 50 ml | 300 ml | 500 ml | 1000 ml | 2000 ml |
|--------------------|-----------|-----------|-----------|-----------|-----------|
| Neck outer-Ø [mm] | 22 | 34 | 34 | 42 | 50 |
| Flask outer-Ø [mm] | 51 | 87 | 105 | 131 | 166 |
| Height [mm] | 90 | 156 | 180 | 220 | 280 |
| Pack of | 10 pieces |
| Cat. No. | 92717 | 92739 | 92744 | 92754 | 92763 |



Erlenmeyer flasks wide neck

| Capacity | 50 ml | 300 ml | 500 ml | 1000 ml | 2000 ml |
|--------------------|-----------|-----------|-----------|-----------|-----------|
| Neck outer-Ø [mm] | 34 | 50 | 50 | 50 | 72 |
| Flask outer-Ø [mm] | 51 | 87 | 105 | 131 | 153 |
| Height [mm] | 85 | 156 | 175 | 220 | 276 |
| Pack of | 10 pieces |
| Cat. No. | 92817 | 92839 | 92844 | 92854 | 92863 |

2.4 Centrifuge tubes



- ✓ Extra thick and even vessel walls
- ✓ Good chemical resistance
- ✓ Stoppers available separately

Centrifugation is essential for extracting proteins and nucleic acids from microbial liquid cultures.

Centrifuge tubes from BRAND can be used to efficiently sediment culture volumes of up to 160 ml, reducing centrifuging times. Matching stoppers perfectly seal the tubes, reducing the danger of contamination to rotors and centrifuges. After decanting supernatant, the pellet can easily be placed in interim storage at -20 °C for processing at a later time.



Applications

- + Centrifugation of bacterial cultures
- + Alkaline lysis of micro-organisms
- + Plasmid extraction from transformed bacteria

- + High chemical resistance
- + Stoppers available separately
- + Rated up to 4500 RZBCF
- + Suitable for autoclaving (121 °C, 15 min)
- + For single use only



Technical information & Ordering data

Centrifuge tubes without PE-stopper



| Capacity | 10 ml | 30 ml | 26 ml | 48 ml |
|--------------|------------------------------|----------------------------|----------------------------|----------------------------|
| Outer-Ø [mm] | 16 | 20 | 24 | 30 |
| Height [mm] | 100 | 100 | 90 | 100 |
| Pack of | 3750 pieces (250 per bag) | 500 pieces (50 per bag) | 500 pieces (50 per bag) | 400 pieces (25 per bag) |
| Cat. No. | 115342 | 115348 | 115346 | 115350 |
| | | | | |
| Capacity | 75 ml | 110 ml | 160 ml | |
| Outer-Ø [mm] | 35 | 40 | 45 | |
| Height [mm] | 100 | 120 | 120 | |
| Pack of | 300 pieces (20 per bag) | 300 pieces (20 per bag) | 100 pieces (10 per bag) | |
| Cat. No. | 115352 | 115354 | 115356 | |

PE-stopper



| For centrifuge tubes | 10 ml | 30 ml | 26 ml | 48 ml |
|-------------------------------|-------------|------------|------------|------------|
| Height tube with stopper [mm] | 110 | 110 | 100 | 110 |
| Pack of | 1000 pieces | 500 pieces | 500 pieces | 500 pieces |
| Cat. No. | 115360 | 115366 | 115368 | 115370 |

| For centrifuge tubes | 75 ml | 110 ml | 160 ml |
|-------------------------------|------------|------------|------------|
| Height tube with stopper [mm] | 110 | 130 | 130 |
| Pack of | 500 pieces | 100 pieces | 100 pieces |
| Cat. No. | 1153 72 | 1153 74 | 1153 76 |

Racks for centrifuge tubes



Size 265 x 126 mm. Will not float in waterbath.


Operating temperature -20 °C to +90 °C, autoclavable.





| For tubes up to Ø | 16 mm | 20 mm | 25 mm | 30 mm |
|-------------------|----------|----------|----------|----------|
| Height [mm] | 75 | 75 | 88 | 88 |
| Positions | 5 x 11 | 4 x 10 | 4 x 8 | 3 x 7 |
| Pack of | 5 pieces | 5 pieces | 5 pieces | 5 pieces |
| Cat. No. white | 4340010 | 4340020 | 4340030 | 4340040 |
| Cat. No. blue | 4340011 | 4340021 | 4340031 | 4340041 |
| Cat. No. red | 4340012 | 4340022 | 4340032 | 4340042 |

In general, we recommend filling at least 80% of the total volume of the centrifuge tube to prevent tube failure during centrifugation.



2.5 Petri dishes

- ✓ Temperature stability to 80 °C
- ✓ Stackable
- Crystal clear PS

Petri dishes for creating agar cultures are standard in every microbiology and molecular biology laboratory. Since the agar is poured or dosed while it is still hot, plastic petri dishes have to be able to withstand the high temperatures involved.

Petri dishes for one-time use by BRAND stand out for their excellent temperature stability, ensuring that even hot agar substances do not deform the plastic dishes.

Use the seripettor® to quickly and easily transfer your agar into the petri dish.

Applications

Manufacturing of agar plates for

- Pure cultures
- Smears for separation
- + Smears for clonal colony formation after transformation (master plate)
- + Quantifying microorganisms

Features

- + Temperature stability to 80°C
- Fully-automated manufacturing and packaging
- Made of highly transparent polystyrene for consistency
- Stackable and dimensionally stable
- With and without vents

2.6 Inoculation loops



- ✓ Sterile (SAL 10⁻⁶)
- ✓ High flexibility for agar-saving smears
- Usable at both ends

Disposable inoculation loops by BRAND reduce the danger of contamination and make cleaning and sterilization processes unnec-

In particular when handling pathogenic agents, disposable BRAND inoculation loops are an excellent choice for keeping infection risk

Applications

- + For inoculating cell cultures
- For inoculating stab cultures
- For inoculating liquid cultures

- + Made of highly flexible polystyrene
- With loop only or with loop and needle
- Sterile in accordanc with USP 29 (SAL 10⁻⁶)
- For single use only



Technical information & Ordering data



Petri dishes, soda-lime glass

| Lid Ø | 40 mm | 60 mm | 80 mm | 100 mm | 100 mm | 150 mm |
|------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Base height [mm] | 12 | 15 | 15 | 15 | 20 | 25 |
| Pack of | 10 pieces |
| Cat. No. | 455701 | 455717 | 455732 | 455742 | 455743 | 455751 |

Petri dishes, PS



| Lid Ø | 55 mm | 55 mm | 94 mm | 94 mm |
|------------------|--------------|-------------|--------------|------------|
| Description | without vent | with vent | without vent | with vent |
| Base height [mm] | 14 | 14 | 16 | 16 |
| Pack of | 1620 pieces | 1620 pieces | 480 pieces | 480 pieces |
| Cat. No. | 452015 | 452010 | 452000 | 452005 |



Inoculation loops, PS

| Capacity of loop | 1 μl | 10 μl | 1 + 10 μl |
|------------------|-------------|-------------|-------------|
| Color | natural | blue | yellow |
| Length [cm] | 20 | 20 | 20 |
| Pack of | 1000 pieces | 1000 pieces | 1000 pieces |
| Cat. No. | 452201 | 452210 | 452215 |

Cultivating microorganisms at an analytic scale:



96- and 384-well deep well plates are a great choice to save space and media while cultivating micro-organisms. BRAND lists products to meet your needs in chapter III on page 137.





Accessories

Threaded bottles

Soda-lime glass (amber). Screw cap PP, pouring ring PE-LD. Space-saving square

Protects light-sensitive buffers or media and stock solutions. The bottles are available ethylene-acrylate coated or uncoated. Pack of 1.



| Capacity [ml] | Width [mm] | Height [mm] | Thread | coated Cat. No. | uncoated Cat. No. |
|---------------|---------------|----------------|--------|--------------------|----------------------|
| 100 | F0 | 125 | CL 22 | 704003 | 704013 |
| 100 | 50 | 125 | GL 32 | 704002 | 704012 |
| 250 | 65 | 160 | GL 32 | 704004 | 704014 |
| 500 | 80 | 195 | GL 32 | 704006 | 704016 |
| 1000 | 95 | 230 | GL 45 | 704008 | 704018 |
| 2500* | 140 | 300 | GL 45 | 704010 | 704020 |

^{*} cylindrical shape

Magnetic stirring bar retrievers

PTFE. Magnetic core fully sealed. Pack of 1.

| Length mm | Ø mm | Cat. No. |
|--------------|---------|----------|
| 150 | 8 | 137700 |
| 250 | 8 | 137710 |
| 350 | 8 | 137720 |



Magnetic stirring bars

High magnetic strength and long life due to Alnico V magnetic cores, fully encapsulated with high-grade PTFE. Strict quality control ensures the magnetic strength, position of the magnetic core, surface quality, crack resistance, and uniform thickness of the PTFE coating. Maximum operating temperature 270 °C. Pack of 10.





| Length [mm] | Bar Ø [mm] | cylindrical Cat. No. | ring Ø [mm] | with pivot ring Cat. No. |
|-------------|---------------|-------------------------|----------------|-----------------------------|
| 2.5 | 2.5 | 137100 | - | _ |
| 3.5 | 3.5 | 137101 | - | _ |
| 5 | 2 | 137102 | - | _ |
| 6 | 3 | 137103 | - | _ |
| 8 | 3 | 137104 | 4 | 137404 |
| 12 | 4.5 | 137105 | 6 | 137405 |
| 7 | 2 | 137106 | - | - |
| 8 | 1.7 | 137107 | - | - |
| 10 | 3 | 137108 | - | - |
| 13 | 3 | 137109 | - | - |
| 15 | 4.5 | 137110 | 6 | 137410 |
| 15 | 1.7 | 137111 | - | - |
| 10 | 6 | 137113 | - | - |
| 15 | 6 | 137114 | - | - |
| 20 | 6 | 137115 | 8 | 137415 |
| 25 | 6 | 137120 | 7 | 137420 |
| 30 | 6 | 137125 | 7.5 | 137425 |
| 35 | 6 | 137127 | 8 | 137527 |
| 40 | 8 | 137130 | 8.5 | 137430 |
| 45 | 8 | 137132 | 10 | 137432 |
| 50 | 8 | 137135 | 11 | 731435 |
| 60 | 9 | 137140 | - | - |
| 70 | 9 | 137145 | 10 | 137445 |
| 80 | 9 | 137150 | - | - |
| 108** | 27 | 137155 | - | - |
| 159** | 27 | 137160 | - | - |

^{**} flattened sides, pack of 1.

To prevent demagnetization stirring bars should not be stored in a random mass but should be kept "paired".





3. Sample analysis

Routine analysis of liquids and dissolved materials is typically carried out using photometric or spectroscopic methods. Cuvettes are frequently used in both kinds of analysis. BRAND offers a variety of disposable cuvettes for the UV/VIS range, which stand out for their excellent optical transmission ranges and defined layer thicknesses. They are an inexpensive alternative to glass or quartz cuvettes in many analytic disciplines.

Staining methods used to assess biological preparations highlight whole cells or sub-cellular structures, allowing them to be identified visually. Glass slides and matching cover glasses that have the same refractive index as the lens system are an optimal choice for microscopic analysis. High-quality slides from BRAND ensure uncomplicated analysis. Staining troughs and glass slide holders facilitate easy handling and secure, space-saving archiving of preparations.

3.1 Cuvettes



- ✓ Grouped by mold cavity number
- ✓ For photometric and spectroscopic analyses
- ✓ For measurements in the UV/VIS range

In many fields, plastic disposable cuvettes for the UV/VIS range can replace expensive, sensitive glass or quartz cuvettes. Time-consuming expensive cleaning processes are eliminated, and the dangers of sample mixing and contamination are reduced to a minimum.

Information on current compatibility with different commonly available photometers is available at www.brand.de



Applications

- + Extinction measurements
- + Fluorescence spectroscopy
- + Determining nucleic acid and protein concentrations

Features

- + Made of PS, PMMA and UV polymer
- + Optical pathlength 10 mm
- + Compatible with a wide variety of photometers
- + With 2 or 4 optical windows
- + For volumes between 70 μl and 4.5 ml



User information


Overview of chemical resistance and transmission properties of different cuvettes

Chemical resistance* of plastic cuvettes

| Substance | PS | PMMA | UV-Cuvette |
|------------------------|----|------|------------|
| | | | |
| Acetic acid, 100% | - | - | + |
| Acetone | - | - | + |
| Ammonia | + | + | + |
| Benzaldehyde | - | - | + |
| Butanone | - | - | + |
| Chloroform | - | - | - |
| Dioxane | - | - | + |
| DMF | - | - | + |
| Ethyl acetate | - | - | + |
| Hexane | - | + | - |
| Hydrochloric acid, 36% | + | - | + |
| Hydrofluoric acid, 10% | + | + | + |
| Isopropanol | + | + | + |
| Nitric acid, 65% | - | - | + |
| Sodium hydroxide | + | + | + |

^{*} Short time resistance, 30 min. Longer-term storage of these chemicals should be confirmed by the user. Request a free sample.

Transmission curves of different cuvettes



To achieve reproducible results: Before the actual measurement, always determine the blank value for the cuvette, and determine the linear range of measurement by means of a calibration curve.

Overview table

| Cuvette type | Filling volumin. | ıme max. | Dimensions window (w x h) | Range of application | Standard deviation in extinction units |
|---|------------------------------------|--------------------------------------|---|----------------------|--|
| UV-Cuvette micro, z = 8.5 UV-Cuvette micro, z = 15 UV-Cuvette macro UV-Cuvette semi-micro | 70 μl 70 μl 2.5 ml 1.5 ml | 850 μl 550 μl 4.5 ml 3.0 ml | 2 x 3.5 mm (min.) 2 x 3.5 mm (min.) 10 x 35 mm 4.5 x 23 mm | from 230 to 900 nm | 240 nm ≤± 0.007 300 nm ≤± 0.005 |
| macro cuvette (PMMA) semi-micro cuvette (PMMA) | 2.5 ml 1.5 ml | 4.5 ml 3.0 ml | 10 x 35 mm 4.5 x 23 mm | from 300 to 900 nm | 320 nm ≤± 0.004 |
| macro cuvette (PS) semi-micro cuvette (PS) | 2.5 ml 1.5 ml | 4.5 ml 3.0 ml | 10 x 35 mm 4.5 x 23 mm | from 340 to 900 nm | 360 nm ≤± 0.005 |
| macro cuvette (PS) 4 clear sided | 2.5 ml | 4.5 ml | 10 x 35 mm | from 340 to 900 nm | 360 nm ≤± 0.005 |
| UV-Cuvette macro 4 clear sided | 2.5 ml | 4.5 ml | 10 x 35 mm | from 230 to 900 nm | 240 nm ≤± 0.007 300 nm ≤± 0.005 |

Accessories

Cuvette rack

PP, gray. Numbered positions. Autoclavable (121 °C). Suitable for standard 10 mm path-length cuvettes. Pack of 1.



| Description | Length [mm] | Width [mm] | Height [mm] | Cat. No. |
|-----------------|----------------|---------------|----------------|----------|
| for 16 cuvettes | 210 | 70 | 38 | 759500 |

Disposable stirring spatula

PS. Pack quantity 10000 = 20 bags of 500 per pack.



| Description | Stem Ø [mm] | Length [mm] | Cat. No. |
|-------------|----------------|----------------|----------|
| PS | 3 | 120 | 759800 |



UV-Cuvette micro

- Usable starting from 230 nm
- Specially designed for photometric determination of proteins, ssDNA, dsDNA, RNA and oligonucleotides

Caps for UV-Cuvette micro

- · Create a secure closure
- For sample storage down to -20 °C
- Multiple colors for efficient sample management

Various photometric methods are currently available for determining the concentration and purity of nucleic acids and proteins.

Protein determination using UV cuvettes:

$$C_{Protein (mg/ml)} = 1.55 \cdot A_{280 \text{ nm}} - 0.76 \cdot A_{260 \text{ nm}}$$

Nucleic determination using UV cuvettes:

$$C_{DNA (\mu g/ml)} = 50 \cdot A_{260 \text{ nm}} \cdot \text{dilution factor}$$

$$C_{RNA (\mu g/ml)} = 40 \cdot A_{260 \text{ nm}} \cdot \text{dilution factor}$$

Technical information & Ordering data



UV-Cuvette micro

| Center heigth | 8.5 mm | 8.5 mm | 8.5 mm |
|--------------------|------------|------------|---------------------------------|
| Light path [mm] | 10 | 10 | 10 |
| Sample volume [μl] | 70 - 850 | 70 - 850 | 70 - 850 |
| Quality | standard | standard | free of DNase, RNase and DNA |
| Pack of | 100 pieces | 500 pieces | 100 pieces (single wrapped) |
| Cat. No. | 759200 | 759210 | 759215 |



| Center heigth | 15 mm | 15 mm | 15 mm |
|--------------------|------------|------------|---------------------------------|
| Light path [mm] | 10 | 10 | 10 |
| Sample volume [µl] | 70 - 550 | 70 - 550 | 70 - 550 |
| Quality | standard | standard | free of DNase, RNase and DNA |
| Pack of | 100 pieces | 500 pieces | 100 pieces (single wrapped) |
| Cat. No. | 759220 | 759230 | 759235 |

Cap for UV-Cuvettes micro



| Color | blue | yellow | green | red |
|----------|------------|------------|------------|------------|
| Material | PE | PE | PE | PE |
| Pack of | 100 pieces | 500 pieces | 100 pieces | 100 pieces |
| Cat. No. | 759240 | 759241 | 759242 | 759243 |



Standard cuvettes and UV-Cuvettes macro and semi-micro

• Ideally suited for determinations in water analysis, chemistry, and in life science applications

759005

- Grouped by mold cavity number
- Significant lower costs compared to quartz glass cuvettes

Technical information & Ordering data

Macro and semi-micro cuvettes



| Description |
|--------------------|
| Material |
| Light path [mm] |
| Sample volume [ml] |
| Pack of |
| Cat- No. |

| macro | | |
|--|-----------|------------|
| PS | PMMA | UV-Polymer |
| 10 | 10 | 10 |
| 2.5 - 4.5 | 2.5 - 4.5 | 2.5 - 4.5 |
| 1000 pieces (10 boxes of 100 cuvettes per box) | | 100 pieces |

759105

759170




| Description |
|--------------------|
| Material |
| Light path [mm] |
| Sample volume [ml] |
| Pack of |
| Cat. No. |

| semi-micro | | |
|--|-----------|------------|
| PS | PMMA | UV-Polymer |
| 10 | 10 | 10 |
| 1.5 - 3.0 | 1.5 - 3.0 | 1.5 - 3.0 |
| 1000 pieces (10 boxes of 100 cuvettes per box) | | 100 pieces |
| 759015 | 759115 | 759150 |

Macro cuvette 4 clear sided

- · For efficient and safe work, without cleaning steps
- Suitable for fluorescence spectroscopy
- Significantly lower costs for use compared to quartz glass cuvettes
- UV-Cuvettes show minimal autofluorescence

Minimal autofluorescence of UV-cuvettes



3-D scan from 200 to 400 nm wavelength with Hitachi F -7000 FL-Spectrometer

Technical information & Ordering data



Macro cuvette 4 clear sided

| Material | PS | PS | UV-Polymer | UV-Polymer |
|--------------------|------------|------------|------------|------------|
| Light path [mm] | 10 | 10 | 10 | 10 |
| Sample volume [ml] | 2.5 - 4.5 | 2.5 - 4.5 | 2.5 - 4.5 | 2.5 - 4.5 |
| Pack of | 100 pieces | 500 pieces | 100 pieces | 500 pieces |
| Cat. No. | 759030 | 759035 | 759125 | 759128 |



3.2 Microscope slides | Cover glasses disposables



Microscope slides

Microscopic slide blanks from BRAND are manufactured from highly pure soda-lime glass using a float glass process. A multi-stage cleaning process ensures a perfectly clean surface.

Applications

- + Analysis of tissue sections and cellular suspensions
- + Producing permanent and fresh preparations

The "ground edge" version reduces the risk of injury

Features

- + Very good wettability
- + Fits in machinery
- + No inclusions
- + Good chemical and temperature resistance
- + Available with frosted end
- + In accordance with DIN ISO 803-1

Cover glasses

Cover glasses from BRAND are manufactured of pure white borosilicate glass in hydrolytic class 1. Fully-automated processing ensures absolutely clean, dust, and grease-free quality.

Applications

+ For covering preparations on microscopic slides

Features

- + Thickness No. 1 (0.13 to 0.17 mm)
- + Refractive index 1.52 ± 0.01; Abbe number v_e= 56.5 ± 0.5
- + Distortion-free flatness within ± 3 μm

Store dry and at a consistent temperature

of injury.

Technical information & Ordering data

Microscope slides



| Description | ground edges | | cut edges | |
|-------------|------------------------------|--------|------------------------------|--------|
| Frosted end | - both ends | | - both ends | |
| Pack of | 2500 pieces (50 boxes of 50) | | 2500 pieces (50 boxes of 50) | |
| Cat. No. | 474743 | 474744 | 474701 | 474702 |


Cover glasses



| Cover glasses | | | | | | | |
|---------------|------------|-------------------------------|---------|---------|------------|-------------------|---------|
| Description | square sha | аре | | | rectangula | ar shape | |
| Size [mm] | 18 x 18 | 20 x 20 | 22 x 22 | 24 x 24 | 24 x 40 | 24 x 50 | 24 x 60 |
| Pack of | 2000 piece | 2000 pieces (10 boxes of 200) | | | 1000 piece | S (10 boxes of 10 | 00) |
| Cat. No. | 470045 | 470050 | 470055 | 470060 | 470816 | 470819 | 470820 |



3.3 Slide boxes



When creating a sample bank, both safe storage and ease of finding individual preparations are important. Because of this, BRAND offers sturdy slide boxes that provide outstanding protection for fixed samples during storage and transportation.


Applications

- + Storage of fixed cell cultures
- + Storage of fixed tissue sections
- + Transportation of fixed samples

Features

- + Less hygroscopic than cardboard slide folders
- + Optimal for refrigerated storage
- + Light-resistant closure
- + Numbered slots
- + For slides size 76 x 26 mm (DIN ISO 8037-1)

Technical information & Ordering data





round shape

45 (Ø) x 90 (H) 10 pieces 476900

no PP 10

Slide boxes

| Description |
|------------------------|
| Sample identification |
| Material |
| Slide capacity |
| Size [L x W x H in mm] |
| Pack of |
| Cat. No. |

| rectangular shape | | |
|-------------------|-----------------|-----------------|
| with index card | with index card | with index card |
| PS | PS | PS |
| 25 | 50 | 100 |
| 120 x 96 x 35 | 270 x 97 x 35 | 230 x 187 x 35 |
| 1 piece | 1 piece | 1 piece |
| 475800 | 475900 | 476000 |
| | | |



3.4 Staining troughs



Staining troughs and inserts allow for less waste of reagents and staining solutions. Thanks to their secure fit in the inserts, multiple slides can be processed at once.

Staining troughs with inserts from BRAND offer space for multiple slides. Two practical variants allow for easy transitions between separate drainage, washing and staining solutions. The opaque container and cover of the plastic staining trough can also be filled with a desiccant to accelerate the drying process.

Applications

- + For histology and cytology stains
- + For preparation radiography

Features

- + Good chemical resistance
- + No danger of breakage, POM
- + Inserts and staining troughs available separately
- + Easy to clean

Technical information & Ordering data




Staining troughs

Description
Size [L x W x H in mm]
Slide capacity
Lid
Pack of
Cat. No.

| glass |
|---------------|
| 105 x 85 x 70 |
| 10 |
| Glass cover |
| 10 pieces |
| 472200 |

| РОМ | |
|--------------|--|
| 98 x 88 x 52 | |
| 25 | |
| Opaque cover | |
| 5 pieces | |
| 471800 | |
| | |



Accessories

Pack of Cat. No.

| wire handle for tray |
|----------------------|
| 473100 |

separate insert

10 pieces 472000

| separate insert | |
|-----------------|--|
| 5 pieces | |
| 471400 | |

Cat. No. 473100

individual container 471500





4 Assay plates

Many automated high throughput processes in the Life Sciences, such as compound, high-throughput screening and high-content analyses, are reliant on the use of assay plates. Based on their compliance with ANSI/SLAS standards, almost all assay plates are suitable for commonly available plate readers and washers.

BRANDplates® microplates and multiwell plates are manufactured under advanced, ISO class 7 cleanroom conditions and packaged using a fully automated process. This ensures the highest possible purity, even for non-sterilized assay plates.

With available 24-, 96-, 384- and 1536-well formats and nine different surfaces created through specialized plasma treatments and coatings, they are the perfect choice for applications in microbiology, immunology, or cell culture. Depending on their pigmentation, they can be used for colorimetric, luminescence or fluorescence assays. Clear, multicolored alphanumeric codes ensure unique sample identification, and offer the option of delivering assay plates with customer-specified bar codes.

4.1 Non-treated microplates

- pureGrade™
- pureGrade™ S

4.2 Microplates for **Immunoassays**

- immunoGrade™
- hydroGrade™
- lipoGrade™

4.3 Microplates for cell culture

- cellGrade™
- cellGrade[™] plus
- cellGrade[™] premium
- inertGrade™

Page 60

4.4 Cell culture inserts

- Multiwell plates
- Individual inserts
- Insert strips
- Insert 2in1

Page 72

Page 54



4.1 Non-treated plates



- ✓ Optimal surfaces for optimal results
- ✓ Reliable quality from the cleanroom
- ✓ Versatile use for assays and storage

BRAND*plates*® microplates pureGrade™ | pureGrade™ S

BRANDplates® pureGrade™ and pureGrade™ S microplates are manufactured from pure, newly synthesized polystyrene (PS). The raw materials used in the plates fulfill the relevant requirements of the USP and ISO 10993. Automated, ISO class 7 cleanroom production ensures the best possible cleanliness.

Grey alphanumeric codes on white and black 96-well microplates facilitate sample identification and reduce the risk of errors.

Chimney shape of the wells reduces cross-contamination with robots Gray or embossed alphanumeric coding for reliable, fast sample identification

Applications


- + Dilution series
- + Homogenous assays
- + Screenings
- + Sample storage
- + DNA, RNA and protein quantification
- + Fluorescence and luminescence assays
- + Bacteriological assays

Features

- + High purity, crystal-clear polystyrene
- + Hydrophobic surface
- + For all ANSI/SLAS conforming analytic equipment
- + Medium binding surface (ELISA)
- + Available sterile and non-sterile
- + Available with barcode

User information


Transmission properties BRANDplates® with UV-transparent film bases



- Slightly hydrophylized for homogeneous meniscus formation
- Ideal alternative to cuvette measurement with a large number of samples
- For microplate-based nephelometry in the UV-VIS range



Technical data sheets for BRANDplates® microplates are available at www.brand.de



BRAND plates UV-transparent

UV-cuvette micro (z = 8.5 mm) UV-cuvette micro (z = 15 mm)

| Volume (approx.) | Light path | |
|----------------------|---------------|--|
| 165.0 μl 322.5 μl | 5 mm 10 mm | |
| 70 - 850 μl | 10 mm | |
| 70 - 550 μl | 10 mm | |

Types

pureGrade™



- Non-treated, non-sterile surface
- The standard plate for most applications
- Particularly applicable for homogenous assays, screening, and for storage.

pureGrade™ S



49

- Non-treated, sterile surface
- Sterilized via β-radiation
- Especially suited for bacteriological assays

Accessories

Reagent reservoirs

PP, high clarity. Capacity 60 ml. Autoclavable (121 °C).





Information on our single

and multi-channel microliter pipette Transferpette® S is available at shop.brand.de



Technical information & Ordering data

96-well


Standard microplates











F-bottom transparent

350





| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |

| Color |
|-----------------------|
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |
| |

| 96-well | |
|----------------------------|-----------|
| U-bottom | |
| transparent | t |
| 330 | |
| 40-300 | |
| 850 | |
| n/a | |
| | sterile |
| 20 pieces (1 lid/stack) | 50 pieces |

| 30 11011 | |
|------------|-----------|
| V-bottom | |
| transparen | t |
| 360 | |
| 40-330 | |
| 850 | |
| 33 | |
| | sterile |
| 20 pieces | 50 nieces |

| 50-320 | |
|----------------------------|----------------------------|
| 850 | |
| 32 | |
| | sterile |
| 20 pieces (1 lid/stack) | 50 pieces |
| 100 pieces (20 stacks | 50 pieces (individually |

|] | 96-well |
|---|-------------|
| | C-bottom |
| | transparent |
| | 350 |
| | 50-33 |
| | 850 |
| | 25 |
| | |

| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |


| | sterile |
|--|--|
| 20 pieces (1 lid/stack) | 50 pieces |
| 100 pieces (20 stacks of 5 plates) | 50 pieces (individually wrapped) |
| 781600 | 781660 |

| 20 pieces (1 lid/stack) 50 pieces | 20 pieces | |
|---|--|--|
| (I liu/stack) | (1 lid/stack) | 50 pieces |
| 100 pieces (20 stacks of 5 plates) 50 pieces (individually wrapped) | 100 pieces (20 stacks of 5 plates) | 50 pieces (individually wrapped) |
| 781601 781661 | 781602 | 781662 |

| 20 pieces (1 lid/stack) | 50 pieces |
|--|----------------------------------|
| 100 pieces (20 stacks of 5 plates) | 50 pieces (individually wrapped) |
| 781603 | 781663 |
| | |







F-bottom white 350 50-320







| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |
| |

| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |

| 96-well | |
|-----------|--|
| U-bottom | |
| white | |
| 330 μ | |
| 40-300 | |
| 850 | |
| n/a | |
| | |
| 20 pieces | |

100 pieces (20 stacks of 5 plates)

781604

| 850 | |
|--|--|
| 32 | |
| | sterile |
| 20 pieces (1 lid/stack) | 50 pieces |
| 100 pieces (20 stacks of 5 plates) | 50 pieces (individually wrapped) |
| 781605 | 781665 |
| | |

| JO-WEII | |
|-----------|--|
| U-bottom | |
| black | |
| 330 | |
| 40-300 | |
| 850 | |
| n/a | |
| | |
| 20 nieces | |

| n/a |
|---------------------------------------|
| |
| 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) |
| 781607 |
| |


| 32 | |
|--|----------------------------------|
| | sterile |
| 20 pieces (1 lid/stack) | 50 pieces |
| 100 pieces (20 stacks of 5 plates) | 50 pieces (individually wrapped) |
| 781608 | 781668 |
| | |

Lid for 96-well standard plate, see page 84: without condensation rings Cat. No. 782151 with condensation rings Cat. No. 782150

50

96-well


with transparent bottom




Lid for 96-well plates with transparent bottom, see page 84: Cat. No. 782155

96-well strip plates









| 96-we | ш |
|--------|---|
| 9h-M/P | ш |

| | 96-well | 96-well |
|-----------------------|---|--|
| Bottom | F-bottom | F-bottom |
| Color | transparent, without grid, strips of 8 wells, not divisible | transparent, with grid, strips of 8 wells, divisible |
| Well volume [μl] | 360 | 350 |
| Working volume [μl] | 50-320 | 50-320 |
| Bottom thickness [mm] | 1.1 | 1.1 |
| Well surface [mm²] | 37 | 37 |
| | | |
| Lid | _ | - |
| Pack of | 100 pieces (4 bags of 25 plates) | 100 pieces (4 bags of 25 plates) |
| Cat. No. | 782300 | 782301 |



continued pureGrade™, pureGrade™ S (sterile)

Assay plates

384-well

Standard microplates











Bottom Color Well volume [µl] Working volume [μl] Bottom thickness [µm]

| Doctorn tinetaless [pm] | |
|-------------------------|--|
| Well surface [mm²] | |
| | |
| Lid | |
| | |
| Pack of | |
| Cat Na | |
| Cat. No. | |

| 384-well | |
|------------|---|
| F-bottom | |
| transparen | t |
| 100 | |
| 25-80 | |

| 384-well | |
|----------|--|
| F-bottom | |
| white | |
| 100 | |
| 25-80 | |
| 650 | |
| 12 | |
| | |

| F-bottom | |
|----------|--|
| black | |
| 100 | |
| 25-80 | |
| 650 | |
| 12 | |

| | sterile |
|---------------------------------------|--|
| - | 50 pieces |
| 50 pieces (5 bags of 10 plates) | 50 pieces (individually wrapped) |
| 781620 | 781680 |
| | (5 bags of 10 plates) |

650 12

| sterile |
|--|
| 50 pieces |
| 50 pieces (individually wrapped) |
| 781681 |
| |

| | sterile | |
|---------------------------------------|--|--|
| - | 50 pieces | |
| 50 pieces (5 bags of 10 plates) | 50 pieces (individually wrapped) | |
| 781622 | 781682 | |

384-well

with transparent bottom





| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |

| wett surface [mm] |
|-------------------|
| Lid |
| Pack of |
| Cat. No. |
| |

| 384-well | | 384-well | |
|---------------------------------------|--|---------------------------------------|--|
| F-bottom | | F-bottom | |
| white | | black | |
| 120 | | 120 | |
| 25-100 | | 25-100 | |
| 400 | | 400 | |
| 13 | | 13 | |
| | sterile | | sterile |
| - | 50 pieces | - | 50 pieces |
| 50 pieces (2 bags of 25 pieces) | 50 pieces (individually wrapped) | 50 pieces (2 bags of 25 pieces) | 50 pieces (individually wrapped) |

781627

781687


781686

781626

Lid for 384-well plates, see page 82: Cat. No. 782152

1536-well


Standard microplates





1536-well

F-bottom







| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Wall surface [mm2] |

| Color | |
|-----------------------|--|
| Well volume [μl] | |
| Norking volume [μl] | |
| Bottom thickness [μm] | |
| Well surface [mm²] | |
| | |
| _id | |

| 1536-well |
|-------------|
| F-bottom |
| transparent |
| 10 |
| above 2 |
| 650 |
| 2 |
| |
| - |
| |

| white |
|---------|
| 10 |
| above 2 |
| 650 |
| 2 |
| |
| - |
| |

| F-bottom |
|------------------------------------|
| black |
| 10 |
| above 2 |
| 650 |
| 2 |
| |
| - |
| 50 pieces (5 bags of 10 plates) |
| 781642 |

Cat. No.

Pack of

50 pieces (5 bags of 10 plates) 781640

781641

50 pieces (5 bags of 10 plates)

Lid for 1536-well plates, see page 82: Cat. No. 782153






4.2 Microplates for Immunoassays



- ✓ Three different surfaces for adsorption of different biomolecules
- ✓ Low well-to-well variance
- Suitable for direct, indirect and Sandwich ELISA

BRAND*plates*® microplates immunoGrade™ | hydroGrade™ | lipoGrade™

BRAND*plates*® for immunoassays are manufactured from pure, newly synthesized polystyrene (PS). Storing large quantities of a raw material batch helps ensure that material-dependent variations in immunological assays can be reduced to a minimum between different assay plate productions.



Applications

- + Solid phase assays
- + Homogeneous assays
- + Fluorescence assays
- + Luminescence assays
- + Radioimmuno-assays (RIA)

Features

- + Three different surfaces
- + Different well bottom shapes
- + Strip plates (F8)
- + Compatible with all ANSI/SLAS conforming analytic equipment



User information

Comparison of surface properties

High binding (immunoGrade™)

Highly adsorbent surface for peptides and proteins with a molecular weight > 10 kDa. These plates stand out for their hydrophilic and hydrophobic surface properties, and are highly optimized for binding of IgG and IgA.

Non-specific binding of analytes can result in increased background signals. Because of this, saturating free binding sites can be helpful with this type of plate, to increase the sensitivity of the assay.

Hydrophilized (hydroGrade™)

The percentage of hydrophilic groups in the solid phase is higher when compared to standard high binding surfaces. Microplates with highly hydrophilized surfaces preferably immobilize hydrophilic molecules such as glycoproteins, glycopeptides, and nucleic acids

The interaction between molecules and the surface can be easily influenced by pH level. The accessibility and detection of epitopes by specific antibodies can be impacted by surface-induced conformation changes to the bound molecules.

Strongly hydrophobic (lipoGrade™)

Microplates with a highly hydrophobic surface have an increased affinity to lipophilic biomolecules, such as lipoproteins and lipids. The plates are especially well-suited for liquid phase assays in which reaction components need to remain in a solution since the majority of hydrophilic biomolecules minimally bind to this surface.

Medium binding (pureGrade™)

Microplates with a medium binding surface are very well suited for immobilizing proteins with a molecular weight > 200 kDa. Typically, at this molecule size there are a large number of hydrophobic amino acids present that determine the strength of the interaction with hydrophobic styrol rings on the microplates.

Types

immunoGrade™

- · High-binding
- Optimized for the immobilization of IgG and molecules with hydrophilic and hydrophobic regions
- Standard ELISA plate

hydroGrade™

- · Strongly hydrophilic
- Increased affinity to biomolecules with primarily hydrophilic regions
- Solid phase with hydrophilic molecules, liquid phase with hydrophobic molecules

lipoGrade™

- Strongly hydrophobic
- Increased affinity to hydrophobic biomolecules
- Solid phase with hydrophobic molecules, liquid phase with hydrophilic molecules



Technical information & Ordering data

immunoGrade™ microplates

Optimized for the immobilization of IgG

- Optimized for the immobilization of IgG, offering highest binding capacity for molecules with mixed hydrophilic and hydrophobic regions.
- The surface of choice for the majority of standard ELISAs.
- Suitable for solid phase immunoassays.
- Comparable to 'high-binding' plates from other manufacturers.

96-well

Standard microplates











| В | o | tt | O! | m |
|---|---|----|----|---|
| | | | | |

Color Well volume [µl] Working volume [μl] Bottom thickness [µm] Well surface [mm²]

Lid

Pack of

Cat. No.

| 96-well |
|---------|


| U-bottom |
|---------------------------------------|
| transparent |
| 330 |
| 40-300 |
| 850 |
| n.a. |
| 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) |
| 701720 |

| V-bottom |
|---------------------------------------|
| transparent |
| 360 |
| 40-330 |
| 850 |
| 33 |
| 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) |
| 701731 |

| 96-well | |
|----------------------------------|--------|
| F-bottom | |
| transparent | |
| 350 | |
| 50-320 | |
| 850 | |
| 32 | |
| 20 pieces (1 lid/stack) | |
| 100 pieces (20 stacks of 5 pl | lates) |

781722

| | 10.85 mm | |
|-------|----------|--|
| | | |
| 00 11 | | |







| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |
| Lid |
| Pack of |

| 96-well |
|---------------------------------------|
| U-bottom |
| white |
| 330 |
| 40-300 |
| 850 |
| n.a. |
| 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) |
| 781724 |
| |

| 96-well |
|---------------------------------------|
| U-bottom |
| black |
| 330 |
| 40-300 |
| 850 |
| n.a. |
| 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) |
| 781727 |



Cat. No.



96-well

with transparent bottom





| 9 | 6- | W | e |
|---|----|----|---|
| J | v | vv | · |

| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |
| Lid |
| Pack of |

| 00 11011 | |
|--|--------------------------------------|
| F-bottom | |
| black | |
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| 20 pieces (1 lid/stack) | 20 pieces (1 lid/stack) |
| 100 pieces (20 stacks of 5 plates) | 5 pieces (1 stack of 5 plates) |
| 791731 | 781732 |



96-well

Cat. No.




Bottom









96-well

| Color |
|-----------------------|
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [mm] |
| Well surface [mm²] |

Lid Pack of Cat. No.

| F-bottom | |
|----------|--|
| | |


| transparent, without gric strips of 8 wells, not divisible |
|---|
| 360 |
| 50-320 |
| 1.1 |
| 37 |
| - |
| 100 pieces (4 bags of 25 plates) |
| 782305 |

| F-bottom |
|---|
| transparent, with grid, strips of 8 divisible |
| 350 |
| 50-320 |
| 1.1 |
| 37 |
| - |
| 100 pieces (4 bags of 25 plates) |
| 792206 |

384-well

Standard microplates













Pack of

Cat. No.

| Bottom |
|-----------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Well surface [mm²] |
| Lid |

| F-bo | ottom |
|------|-------|
| | |
| | |

781740

| 304-WEII | |
|--------------------------------|---------|
| F-bottom | |
| transparent | |
| 100 | |
| 25-80 | |
| 650 | |
| 12 | |
| 10 pieces (1 lid/stack) | |
| 50 pieces (10 stacks of 5 p | olates) |

384-well

781741

| F-bottom |
|--------------------------------------|
| white |
| 100 |
| 25-80 |
| 650 |
| 12 |
| 10 pieces (1 lid/stack) |
| 50 pieces (10 stacks of 5 plates) |

| 384-well | |
|---------------------------------|-------|
| F-bottom | |
| black | |
| 100 | |
| 25-80 | |
| 650 | |
| 12 | |
| 10 pieces (1 lid/stack) | |
| 50 pieces (10 stacks of 5 pl | ates) |
| 781742 | |




Application Note

Comparison of antibody adsorption of BRAND*plates*® immunoGrade™ with a high binding variant of the competition

Author: BRAND GMBH + CO KG

In ELISAs, reproducibility and precision are dependent on the consistent immobilized quantity of coating antibody (ab). If the quantity of coating ab bound in the well varies, this can result in sample-independent differences that may cause results to be misinterpreted. Therefore, the only variable in an ELISA should be the analyte to be measured.

Because of this, we recommend saturating all free binding sites in a well with coating ab, in order to prevent a false positive signal through non-specific immobilized analytes. However, antibodies must be added in excess to saturate the binding sites, making this process very expensive.




Materials and methods

Transparent 96-well microplates with F-bottom (BRAND*plates*® immunoGrade™ #781722, BRAND*plates*® pureGrade™ #781602 and competitor) are incubated with a horseradish peroxidase, HRP-coupled, polyclonal rabbit antibody (IgG, P0214, Dako, Denmark) in increasing dilutions (1:16,000 to 1:1,024,000 in PBS) or decreasing concentrations (81.3 ng/l to 1.3 ng/l) for 2 h at 21 °C and washed. The quantity of HRP-marked antibodies adsorbed by the plastic surface was determined indirectly through absorption (at 450 nm) of the converted TMB substrate (# 34028, ThermoScientific, USA), after adding a stop solution (Photometer EL 808, Biotek, Germany).

Conclusion

In comparison to the competitor plate, the immunoGrade $^{\text{TM}}$ surface of the solid BRAND*plates* $^{\text{®}}$ has a significantly higher affinity to the antibodies (immunoglobulin class G; IgG). Higher affinity for the coating antibody means less must be used to saturate the free binding sites, resulting in a cost savings.




For the immobilization of hydrophilic molecules

- Strongly hydrophilic, with high affinity to hydrophilic molecules, such as glycoproteins and peptides, antibodies with predominantly hydrophilic regions, and nucleic acids.
- An alternative to the immunoGrade™ surface when performing solid phase assays.
- Alternative for homogeneous assays with hydrophobic molecules, that remain in solution.

96-well

Standard microplates




lipoGrade™ microplates

For the immobilization of hydrophobic molecules

- · Strongly hydrophobic (lipophilic), for immobilization of biomolecules with predominantly hydrophobic regions.
- For the immobilization of molecules, such as lipoproteins or peptides.
- Specially suited for liquid phase assays when the reaction component should stay in solution. (The majority of hydrophilic biomolecules are not immobilized on this surface.)

96-well

Standard microplates




Lids and films can be found on page 84.






4.3 Microplates for cell culture



- ✓ Low well-to-well variance for good reproducibility
- ✓ cellGrade[™] plus and cellGrade[™] premium surfaces support serum reduction
- ✓ inertGrade surface for successful cultivation of spheroids and stem cells

BRAND*plates*® microplates cellGrade™ | cellGrade™ plus cellGrade™ premium | inertGrade™

BRAND*plates*® microplates with cellGrade[™], cellGrade[™] plus, cell-Grade[™] premium and inertGrade[™] cell culture surfaces are manufactured from pure, newly synthesized polystyrene (PS). The raw materials used in the plates fulfill the relevant requirements of the USP and ISO 10993. Automated, ISO class 7 cleanroom production ensures the best possible cleanliness.



Applications

- + Cultivation of adherent cells without additional coatings
- + Cultivation of suspension cells
- + High content screenings
- + Fluorescence assays
- + Luminescence assays

Features

- + High purity, crystal-clear polystyrene
- + Different surfaces for different culture conditions and cell types
- + Sterile plate individually packaged with lid
- + For all ANSI/SLAS conforming analytic equipment
- + Available with bar code




User information

Effects of cell culture surface on morphology and proliferation


inertGrade™

Supports the formation of spheroid cultures preventing early contact-induced differentiation of stem cells, due to cell repellent surface.




Untreated polystyrene

Supports only restricted adhesion and proliferation of cells. An excellent choice for custom coating with peptides (Poly-D-Lysine or -Ornithin) or extra-cellular matrix proteins.



Cell culture-treated polystyrene

Supports the adhesion and proliferation of cells with different origins. For many cell lines, further surface treatment is not required. This reduces preparation time for an assay and avoids the danger of increased well-to-well variance.



Types

cellGrade™

For the cultivation of adherent cells

- Standard surface for the cultivation of adherent cell lines.
- PS-surface with different chemical groups, such as carboxyl and hydroxyl groups, that are freely accessible.
- Surface is hydrophilic compared with non-treated PS.
- Serum components are easily bound onto the freely accessible chemical groups, allowing an indirect adhesion of cells.

cellGrade™ plus

For reduced-serum media cultivation of cells

- For cultivation of fastidious cell lines.
- In addition to carboxyl and hydroxyl chemical groups, free amino groups are present on the surface.
- The surface has a protein-like composition, so cells can directly attach and spread out.
- Cells adhere faster, better rate of yield.
- Sensitive cell lines can be cultivated.

cellGrade™ premium

Poly-D-Lysine equivalent surface

- Poly-D-Lysine equivalent surface, with analogous results regarding growth performance and cell morphology.
- Optimal adhesion of cells to the surface reduces cell damage when washing frequently.
- Cultivation of cell lines with the highest demands on their environment.
- Surface suited for serum-free and serum-reduced cultivation of cells.
- Good shelf life at room temperature.
- The alternative option to biologically coated surfaces.

inertGrade™

For cultivation of suspension cells

- Especially suited for cell cultures when adhesion is not desired.
- Optimized surface characteristics reduce cell adhesion, protein adsorption and keeps enzyme activation and cellular activation to a minimum.
- Inhibits early differentiation of stem cells.



Technical information & Ordering data

cellGrade™ microplates Comparison of proliferation and adhesion after washing (CHO cells) 900 1 800 -700 -600 -500 -400 -300 -200 -100 --100 --200 cellGrade™ competitor A competitor B cell 200 competitor C 100 П reference 1 DIV 2 DIV 3 DIV washed

96-well

Standard microplates




Cultivation area [mm²]

Lid Pack of Cat. No.

| 96-well | |
|-------------|--|
| U-bottom | |
| transparent | |
| 330 | |
| 40-300 | |
| 850 | |
| n/a | |
| sterile | |
| 50 pieces | |
| | |

50 pieces (individually wrapped) 781960






transparent 360 40-330 850 33 sterile

50 pieces 50 pieces (individually wrapped)) 781961



F-bottom



| 1 Bottom |
|-------------|
| transparent |
| 350 |
| 50-320 |
| 850 |
| 32 |
| sterile |


50 pieces 50 pieces (individually wrapped) 781962



781965







| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |

| | 10.65 mm |
|--------|----------|
| 6-well | |

| F-bottom |
|----------------------------------|
| white |
| 350 |
| 50-320 |
| 850 |
| 32 |
| sterile |
| 50 pieces |
| 50 pieces (individually wrapped) |


| 96-well |
|----------------------------------|
| F-bottom |
| black |
| 350 |
| 50-320 |
| 850 |
| 32 |
| sterile |
| 50 pieces |
| 50 pieces (individually wrapped) |
| 781968 |
| |



96-well

with transparent bottom





| Bottom |
|------------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Cultivation area [mm²] |

| JO WCII | |
|----------|--|
| F-bottom | |
| white | |
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| sterile | |

| | 7774 |
|----------|------|
| 96-well | |
| F-bottom | |
| black | |
| 330 | |
| 50-310 | |
| 750 | |
| 21 | |

| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |


| sterile | |
|--|------------------------------------|
| 50 pieces | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| 781970 | 781974 |

| piece |
|-----------------------------|
| oieces bag of pieces) |
| 1975 |
| |


384-well

Standard microplates









| Bottom |
|------------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Cultivation area [mm²] |

| F-bottom | |
|-------------|--|
| transparent | |
| 100 | |
| 25-28 | |
| 650 | |
| 12 | |
| sterile | |
| 50 nieces | |

| F-bottom | |
|----------|--|
| white | |
| 100 | |
| 25-28 | |
| 650 | |
| 12 | |
| sterile | |

| F-bottom | |
|----------|--|
| black | |
| 100 | |
| 25-28 | |
| 650 | |
| 12 | |
| sterile | |

| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |

| 12 | |
|----------------------------------|--|
| sterile | |
| 50 pieces | |
| 50 pieces (individually wrapped) | |
| 781980 | |
| | |

| sterile |
|-------------------------------------|
| 50 pieces |
| 50 pieces (individually wrapped) |
| 781981 |


50 pieces 50 pieces (individually wrapped) 781982


384-well


with transparent bottom



384-well F-bottom white 120







| Bottom |
|------------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Cultivation area [mm²] |
| |

Lid

Pack of

Cat. No.

| 25-100 | |
|--|------------------------------------|
| 400 | |
| 13 | |
| sterile | |
| 50 pieces | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| 781986 | 781988 |

| 1 | | |
|---|--|------------------------------------|
| 1 | 384-well | |
| | F-bottom | |
| | black | |
| | 120 | |
| | 25-100 | |
| | 400 | |
| | 13 | |
| | sterile | |
| | 50 pieces | 1 piece |
| | 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| | 781987 | 781989 |
| | | |




Technical Note


Proliferation of CHO cells on BRAND*plates*® cellGrade™ surface

Author: BRAND GMBH + CO KG

Culture conditions

For each experiment CHO cells were seeded at a density of 6000 cells/cm² in wells of transparent 96-well F-bottom BRAND*plates*® (#781962) and cultivated in DMEM medium containing 7% FCS at 37 °C, 95% relative humidity and 5% CO₂.





a), c) Phalloidin-TRITC marked F-Aktin (red), nucleus (blue)

CHO cells cultivated on BRAND*plates*® cellGrade™ show higher fluorescence signals indicating higher cell numbers when compared to non-treated microplates (PS).


b), d) The whole-well scans show significantly improved cell adhesion on the cellGrade™ surface after completing crystal violet staining.

Conclusion

BRAND*plates*® with cellGrade™ surface perfectly support attachment and proliferation of CHO cells.




Technical information & Ordering data





Standard microplates



Bottom

Color Well volume [µl] Working volume [µl] Bottom thickness [µm]

Cultivation area [mm²]

Lid

Pack of Cat. No.

| | 10.65 mm |
|----------|----------|
| 96-well | |
| F-bottom | |

transparent 350 50-320 850

sterile 50 pieces

32

50 pieces (individually wrapped)

782022

wrapped) 782030


96-well

with transparent bottom





ottom



| Bottom |
|------------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Cultivation area [mm²] |
| |

| Lid | |
|----------|--|
| Pack of | |
| Cat. No. | |
| | |



| 30-Well | | 30- |
|--|------------------------------------|-----------------------|
| F-bottom | | F-b |
| white | | bla |
| 330 | | 330 |
| 50-310 | | 50- |
| 750 | | 750 |
| 31 | | 31 |
| sterile | | ste |
| 50 pieces | 1 piece | ا 50 |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) | 50 (indi wrap |

782034

| black | |
|--|------------------------------------|
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| sterile | |
| 50 pieces | 1 piece |
| | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |




Technical Note


Proliferation of HEK293 cells on BRAND*plates*® cellGrade™ plus surface

Author: BRAND GMBH + CO KG

Culture conditions

For each experiment HEK293 cells were seeded at a density of 6000 cells/cm² in wells of transparent 96-well F-bottom BRAND plates® (#782022) and cultivated in DMEM medium containing 7% FCS at 37 °C, 95% relative humidity and 5% $\rm CO_2$.






Comparative phase contrast images of HEK293 cells cultivated in untreated (PS) and cellGrade™ plus treated microplates. DIV days in vitro, (200x zoom)

Conclusion


BRAND*plates*® with cellGrade™ plus surface perfectly support attachment and proliferation of HEK293 cells.

Technical information & Ordering data



96-well

Standard microplates



Bottom

Color Well volume [µl] Working volume [µl] Bottom thickness [µm]

Cultivation area [mm²]

Lid

Pack of

Cat. No.

| transparent |
|-------------|
| 350 |
| 50-320 |
| 850 |
| 32 |
| sterile |

F-bottom

50 pieces

50 pieces

(individually wrapped)

782082


96-well

with transparent bottom









| Bottom |
|------------------------|
| Color |
| Well volume [μl] |
| Working volume [μl] |
| Bottom thickness [μm] |
| Cultivation area [mm²] |
| |

| A. | | |
|------|------|--|
| 96-w | /ell | |

| 96-Well | |
|----------|--|
| F-bottom | |
| white | |
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| | |

| 31 | |
|--|------------------------------------|
| sterile | |
| 50 pieces | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| 782090 | 782094 |
| | |

| 96-well | |
|----------|--|
| F-bottom | |
| black | |
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| ctorilo | |

| 31 | |
|--|------------------------------------|
| sterile | |
| 50 pieces | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| 782091 | 782095 |
| | |



Application Note

High yields of transfected cells with BRANDplates® cellGrade™ premium surface

Author: Martin Liss, Sabine Kraft Neuromuscular & Cardiovascular Cell Biology, Max-Delbrück-Centrum Berlin, Germany

Introduction

Transfection is defined as non-viral DNA/gene delivery into eukaryotic cells performed by several chemical, physical or biological methods. The subsequent exogenous expression of a tagged protein in cell culture is a well established approach to investigate function and localization of the protein of interest. In normal culture medium, nucleases present in serum could degrade DNA while other serum components tend to form complexes with nucleic acids, thereby reducing the availability of DNA for transfection [Ref.1]. To avoid such interference, serum free culture medium is required for successful transfections. However, serum deprivation

can reduce cell viability, proliferation and attachment. To partially compensate for these negative effects arising from serum deprived culture conditions, special modifications of cell culture surfaces have been developed to support cell attachment and increase cellular yields after transfection. Here we compare 3 different microplate surfaces regarding their ability to support proliferation and attachment of transfected cells during washing steps. It is shown, that on the cellGrade™ premium surface transfected cells were retained in same quantity when compared to 96-well microplates of other manufacturers.

Material and Methods

HEK293.EBNA cells were cultured in DMEM 4.5 g/L Glucose with L-glutamine supplemented with 10% fetal bovine serum and 100 units/mL penicillin/streptomycin. Cells were seeded in comparable tissue culture treated black 96-well microplates with transparent bottoms and grown at 37° C with 5% $\rm CO_2$. A total of 200 ng/well GFP-encoding plasmid-DNA pEGFP-C1 was used to transfect cells using 40 kDa linear polyethylenimine at a ratio of 1:3 DNA:PEI40 24 hrs later [Ref.2]. After an incubation of 72 hrs, culture medium

was changed to PBS and one set of cultures from each microplate was washed additional 2 times with 200 μL PBS at 37 °C using an electronic multichannel pipette at lowest dispensing speed in order to not disturb the cell monolayer. For read-out a TECAN Infinite® M200 PRO was used to detect the remaining relative fluorescent units (RFUs) at ex485/em535 nm. The detector of the plate reader was adjusted according to the highest signal intensity to be measured.

Results

A transfection mastermix was used to transfect cultured cells on different plates in order to achieve comparable transfection efficiency (Fig.1).




Figure 1: Example of transfected HEK293.EBNA cells expressing GFP 72 hrs post-transfection. Scale bar 500 µm.




Figure 2: Measurement of GFP relative fluorescence units (RFU) shows the good performance of BRANDplates® cellGrade™ premium surface in promoting proliferation and attachment of transfected HEK293.EBNA cells.

To ensure an equal pipetting strength during washing an electronic multichannel pipette was used. In this case the only variable is the TC culture surface of different manufacturers. The quantification of relative GFP fluorescence units shows that cellGrade™ premium surface promote proliferation of transfected cells and retain GFP expressing cells after washing to the same extent as TC-treated microplates from competitors.

Conclusion

BRAND*plates*® cellGrade™ premium surface can improve experimental performance when cell proliferation or cell binding to culture surface is critical.

References:


- 1: D. Llères, J.M. Weibel, D. Heissler, G. Zuber, G. Duportail, Y. Mély, Dependence of the cellular internalization and transfection efficiency on the structure and physicochemical properties of cationic detergent/DNA/liposomes, J. Gene. Med. 6 (2004) 415–428.
- 2: SP. Huh et al., Optimization of 25 kDa linear polyethylenimine for efficient gene delivery, Biologicals. (2007), 35(3):165-71.




Technical information & Ordering data

inertGrade™ microplates

- Surface effectively suppresses cell adhesion
- For cultivating stem cells
- Ideal for generating tumor spheroids



Wellscan of U-bottom plate (781900) with single spheroid formed by L292 cells.



Close-up ot the spheroid

96-well

Standard microplates








F-bottom

350

850

50-320

transparent



Bottom

Color

Well volume [µl] Working volume [µl] Bottom thickness [µm] Cultivation area [mm²]

Lid

Pack of

Cat. No.

| The same of the sa | 3 |
|--|-----|
| 96-we | ell |

| U-bottom | |
|-------------|--|
| transparent | |
| 330 | |
| 40-300 | |
| 850 | |
| | |

sterile

50 pieces

50 pieces

781900

(individually wrapped)

32

sterile 50 pieces

> 50 pieces (individually wrapped)

781902


96-well

with transparent bottom









| 5 | 44 | | |
|---|----|--|--|

Color

Well volume [µl] Working volume [µl] Bottom thickness [µm]

Cultivation area [mm²]

Lid

Pack of

Cat. No.

| | 11.15 mm | |
|---|----------|--|
| Ė | | |

| 20 | |
|------|-------|
| | A. C. |
| | |
| 96-١ | well |

F-bottom

black 330

| L5 mm |
|-------|
|-------|

96-well

50 pieces 50 pieces

(individually

wrapped)

781910

| F-bottom | |
|----------|--|
| white | |
| 330 | |
| 50-310 | |
| 750 | |
| 31 | |
| sterile | |

1 piece

5 pieces

(1 bag of

5 pieces)

781912

| 330 | |
|--|------------------------------------|
| 50-310 | |
| 750 | |
| 31 | |
| sterile | |
| 50 pieces | 1 piece |
| 50 pieces (individually wrapped) | 5 pieces (1 bag of 5 pieces) |
| 781911 | 781913 |




Application Note

BRAND*plates*® inertGrade™


Author: Dr. Benedikt Busse, zell-kontakt GmbH, Nörten-Hardenberg, Germany

In many cell culture techniques, such as producing tumor spheroids or embryoid bodies, the suppression of integrinmediated adhesion to surfaces plays a crucial role.

The illustration shows that adherent growing cell lines can be made to form spheroids with a comparably high cell division rate by cultivating them on the inertGrade™ cell culture surface.



The cell-repellent surface of the BRAND plates® inertGrade™ also demonstrates effective suppression of cell adherence when cultivating stem cells. This prevents contact-induced and uncontrolled differentiation and maintains the stem cell character.



Application note "Formation of spheroids and suppression of adhesion by adherent growing cells in inertGrade™ microplates", see www.brand.de



At a glance

96-well microplates Type Non-treated Immunological surfaces Cell culture surfaces Standard hydroGrade™ immunoGrade™ lipoGrade™ cellGrade™ cellGrade™ Color Bottom / pure cellGrade™ inertGrade¹ . Grade™ . Grade™ S plus Well volume premium U / 330 μl 781600 781660 781720 781780 781840 transparent 781960 781900 781661 transparent V / 360 µl 781601 781721 781961 transparent F / 350 µl 781602 781662 781722 781782 781842 781962 782022 782082 781902 $C\,/\,350\,\mu l$ 781603 781663 transparent 781724 U / 330 μl 781604 white $F/350\,\mu l$ white 781605 781665 781965 . C / 350 μl white U / 330 μl 781607 781727 black F / 350 μl 781608 781668 781968 black $C/350 \mu l$ black With transp ent bottom Color Bottom / pureGrade™ immunoGrade™ hydroGrade™ lipoGrade™ cellGrade™ cellGrade™ cellGrade™ inertGrade™ Well volume plus premium white $F\,/\,330~\mu l$ 781610 781670 781970 782030 782090 781910 781974 782034 782094 781912 white' $F/330~\mu l$ 781611 781671 781731 781971 782031 782091 781911 black $F\,/\,330\,\mu l$ black* $F/330 \mu l$ 781732 781975 782035 782095 781913 With UV file ottom Bottom / pureGrade™ pureGrade™ S immunoGrade™ hydroGrade™ lipoGrade™ cellGrade™ cellGrade™ cellGrade™ inertGrade™ Color Well volume plus premium transparent $F/350 \mu l$ 781614 black F / 350 µl 781615 Strip plates pureGrade™ pureGrade™ S immunoGrade™ hydroGrade™ lipoGrade™ cellGrade™ cellGrade™ cellGrade™ inertGrade™ Bottom / Color Well volume premium plus transparent, 782305 782300 F / 360 µl without grid transparent, $F/350 \mu l$ 782301 782306 with grid

¹ not available in USA * Pack of 5

| | | 384-well F | ITS microp | lates | | | | | NO CENT | | |
|------------------|-------------------------|------------------------|----------------------|-----------------------|-------------|------------|------------|--------------------|-----------------------|-------------|--|
| Type Non-treated | | Immunological surfaces | | Cell culture surfaces | | | STERILE | | | | |
| Standard | | MO-CERT. | WO CERT! | | | | | | | | |
| Color | Bottom / Well volume | pure Grade™ | pure STERNS Grade™ S | immunoGrade™ | hydroGrade™ | lipoGrade™ | cellGrade™ | cellGrade™ plus | cellGrade™ premium | inertGrade™ | |
| transparent | F / 100 µl | 781620 | 781680 | 781740 | _ | _ | 781980 | _ | _ | _ | |
| white | F / 100 µl | 781621 | 781681 | 781741 | _ | _ | 781981 | - | - | _ | |
| black | F / 100 µl | 781622 | 781682 | 781742 | - | - | 781982 | - | - | - | |
| With transpa | rent bottom | | | | | | | | | | |
| Color | Bottom / Well volume | pureGrade™ | pureGrade™ S | immunoGrade™ | hydroGrade™ | lipoGrade™ | cellGrade™ | cellGrade™ plus | cellGrade™ premium | inertGrade™ | |
| white | F / 120 µl | 781626 | 781686 | - | _ | - | 781986 | - | - | _ | |
| white * | F / 120 µl | - | - | - | - | - | 781988 | - | - | _ | |
| black | F / 120 µl | 781627 | 781687 | - | - | - | 781987 | - | - | _ | |
| black* | F / 120 µl | - | - | - | - | - | 781989 | - | - | _ | |


* Pack of 5

| 1536-Well UHIS microplates | | | | | | | | | NO CERTS | |
|----------------------------|-------------------------|-------------|--------------|-----------------------|-------------|------------|------------|--------------------|-----------------------|-------------|
| Type Non-treated | | Immunologi | cal surfaces | Cell culture surfaces | | | STERILE | | | |
| Standard | | de tra | Silve CERT | | | | | | | |
| Color | Bottom / Well volume | pure Grade™ | pure STEEN'S | immunoGrade™ | hydroGrade™ | lipoGrade™ | cellGrade™ | cellGrade™ plus | cellGrade™ premium | inertGrade™ |
| transparent | F / 10 µl | 781640 | - | - | - | - | _ | - | - | - |
| white | F / 10 μl | 781641 | - | - | - | - | _ | - | - | - |
| black | F / 10 µl | 781642 | - | - | - | - | - | - | - | - |




4.4 Cell culture inserts

4.4.1 Multiwell plates



- ✓ Optimal cell growth thanks to cellGrade™ plus surface
- ✓ Side well access for easier pipetting and removing cover slips
- ✔ Perfect positioning of the BRANDplates® insert

BRAND*plates*® multiwell plates offer better functionality than commonly available multiwell plates. Each well of the 24-well and 6-well plates has an additional extension on the edge of the well to serve as a pipette and forceps access point. This "feeding port" allows the well to be accessed even with a mounted BRAND*plates*® Insert. The additional space in the "feeding port" creates an ideal lever point for forceps to grip cover glasses without scratching them and damaging cultivated cells on the glasses.



Applications

- + Cultivation of adherent cells
- + Cultivating cells on cover glasses
- + Mounting BRANDplates® inserts and insert strips
- + Automated cell culture applications

Features

- + High purity, crystal-clear polystyrene
- + Conforms to ANSI/SLAS Standards 1 and 4
- + Manufactured in an ISO Class 7 cleanroom
- + Individually wrapped with lid, sterile (SAL 10⁻⁶)
- + Untreated or cell culture treated



24-well standard plate

The plate includes 24 individually fillable wells that can be fitted with strips of 4 inserts and/or individual inserts

| Format | 24-well | 6-well |
|--|---------|--------|
| Well surface [mm²] (incl. feeding port) | 210 | 855 |
| Working volume [ml] | 3.1 | 10 |





6-well special plate

The 4 wells are all connected as one large, elongated well. This well can be fitted with a strip of 4 inserts so that all 4 of the inserts in the strip can be supplied with medium at the same time. Particularly well suited to the use of insert strips with inlet channels. Also suitable for single inserts and 2 or 3 connected inserts.

The well and insert are perfectly coordinated

The guide grooves in the support collars of the wells in the 24-well standard plate hold the guide ridges of the insert in position. This prevents the individual inserts from rotating – the feed ports on the wells remain open. At the same time, the guide ridges center the insert in the well.

Accessories





Information on accu-jet® pro pipetting aid and Transferpette® S microliter pipette is available at shop.brand.de, while information on centrifuge tubes and counting chambers is available on pages 17 and 11.

Technical information & Ordering data





24-well and 6-well

Multiwell plates

| pureGrade™ S | cellGrade™ plus | pureGrade™ S | cellGrade™ plus |
|--|--|--|--|
| 24 | 24 | 6 | 6 |
| 3.1 | 3.1 | 8 - 10 | 8 - 10 |
| 210 | 210 | 855 | 855 |
| with lid | with lid | with lid | with lid |
| 10 pieces (individually wrapped) | 10 pieces (individually wrapped) | 10 pieces (individually wrapped) | 10 pieces (individually wrapped) |
| 782880 | 782890 | 782881 | 782891 |
| | | | |

4.4.2 Inserts



- ✓ Optimal cell growth thanks to cell culture treatment
- ✓ Add up to four inserts at once
- ✔ Fast, safe handling

Cell culture inserts with microporous membranes greatly expand the range of methods that can be used in classic cell cultures.

The innovative BRAND*plates*® insert system offers a product perfectly adapted to reconstructing 3D epithelial models. The strip format ensures that the inserts sit in the well without rotation, and the 6-well plate allows for medium exchange in up to four inserts at once.



Applications

- + Epithelial cell cultures
- + Barrier analysis
- + Polarization studies
- + Epidermis models
- + Full skin models
- + Co-cultures
- + Impedance measurements

Features

- + Cell culture treated PC or PET membranes
- + Culture surface 0.6 cm²
- + As 4x strips or individual
- + Strips divisible
- + Manufactured in an ISO Class 8 cleanroom
- + Sterile (SAL 10⁻⁶)



Advantages of specialized insert-plate combinations

A 3D culture of 0.6 cm² should be supplied with at least 1 ml of medium per day, in particular during cultivation at the air-liquid interphase. Medium must also be exchanged with the same frequency.

The BRAND insert system offers a variety of solutions to increase the provided basal volume (below the membrane) and reduce the number of medium changes.

24-well plate with 13 mm insert strip

Standard conditions for 3D cell cultures with high nutrient requirements.

Smooth-walled inserts, suitable for differentiation, transportation, co-cultivation, transmigration and cell polarity assays.

24-well plate with 9 mm insert strip

Ideal for cultures at the air-liquid interphase (ALI)

ALI cultures are supplied with 1.7 ml of medium per 24-well. This combination greatly optimizes the medium supply to ALI cultures.

Not suitable for transportation, transmigration and cell polarity assays.

6-well plate with 13 mm insert strip

Ideal for more complex 3D cultures, such as full skin models.


When using just 2 inserts per well, each ALI culture is supplied with 1.75 ml. This means that up to 12 epithelial models can be cultivated in one plate, saving space.


The smart 6-well design facilitates simultaneous medium exchange for all of the inserts in a series.


6-well plate with 9 mm insert strip


Excellent supply for cells during an air-liquid interphase culture.

When using a full strip, each culture is supplied with 2 ml of medium. Using half strips increases the basal volume to 4 ml per culture.










Co-culture:

Membranes with pore sizes of 0.4 and 1.0 μ m. Use PET membranes for good cell visibility under an optical microscope. PC membranes with comparable pore sizes have a higher pore density, improving interaction between the cells than PET membranes. PC membranes, however, are not recommended for transmitted light microscopes.

Chemotaxis and transmigration:

Depending on the cell type, transmigration assays can be accomplished with pore sizes above 3.0 μ m. Use PET membranes for microscopic applications.






Importance and function of the inlet opening system (IOS)


When removing apical medium in cultures of reconstructed epithelial models, there is a danger of injuring tissue cultures with pipette tips, making the tissue culture unusable in further examinations.

The Inlet Opening System of the BRAND plates Insert makes it possible to adjust the medium levels in inserts by controlling the medium level in the corresponding wells.


In addition to improved reliability, combining 6-well plates and inserts with IOS can reduce pipetting work for 4 inserts in fused well row from eight aspiration and filling steps to just one aspiration and one filling step. This drastically reduces the time that the cultures spend outside of the incubator, making it possible to greatly reduce the effects of temperature and pH fluctuations.




During cell seeding or applying coatings, the unique geometry of the Inlet Opening System (IOS) prevents the insert from leaking



The submersion culture is also established by adding medium to the well. The arrow indicate that the medium flows evenly into the interior of the insert.



The IOS accelerates and simplifies the medium exchange. The arrows show the direction of flow for the medium from the insert into the well where the aspiration pipette is placed.



This allows the air-liquid interface to be adjusted without the risk of tissue damage.

Possible causes for poor adhesion of cells in assay plates:

- The passage used in the cell line is too high and the cells are senescent
- The seeding density is too low
- The medium used is inadequate
- · Cells are contaminated
- Cells require a specific substrate (laminin, collagen, vitronectin, fibronectin)

Recommended volumes for different culture phases of the 3D culture

| | 24-well | 6-well | 24-well | 6-well |
|--|-----------|-----------|-----------|-----------|
| Insert height [mm] | 13 | 13 | 9 | 9 |
| Insert [μl] (such as coating, cell seeding) | 150 - 400 | 150 - 400 | 150 - 250 | 150 - 250 |
| Well: Submersion culture [ml] with added insert | 1.6 - 2 | 8 - 10 | 2.2 - 2.5 | 9 - 10 |
| Well: air-liquid-interphase [ml] (of basal coated membrane) | 0.8 | 3.5 | 1.8 | 8 |

Membrane pore size / application examples

| Pore size | Areas of application |
|-----------|---|
| 0.4 μm | Co-culture, transport studies, secretion studies, cell polarity studies, etc. |
| 1.0 μm | Co-culture, transport studies, secretion studies, etc. |
| 3.0 μm | Migration studies, chemotaxis studies, metastasis experiments, etc. |
| 8.0 µm | Migration studies, chemotaxis studies, metastasis experiments, etc. See also the construction of full-thickness skin models (www.tissue-factory.com) |



Technical information & Ordering data

Insert Strips

PC membrane

| Pore size | 0.4 μm | | 1.0 μm | 3.0 μm | 8.0 μm |
|----------------------------------|-----------------------------|----------|--------------------------------------|--------------------------------------|--------------------------------------|
| Pore density per cm ² | 1 x 10 ⁸ | | 2 x 10 ⁷ | 2×10^6 | 1 x 10 ⁵ |
| Growth area [cm²] | 0.6 | | 0.6 | 0.6 | 0.6 |
| Insert height [mm] | 13 | 9 | 13 | 13 | 13 |
| Pack of | 12 pieces (12 strips x 4 | inserts) | 12 pieces (12 strips x 4 inserts) | 12 pieces (12 strips x 4 inserts) | 12 pieces (12 strips x 4 inserts) |
| Туре | smooth-w | alled | smooth-walled | smooth-walled | smooth-walled |
| Cat. No. | 782800 | 782900 | 782820 | 782840 | 782860 |
| Туре | IOS | | IOS | IOS | IOS |
| Cat. No. | 782801 | 782901 | 782821 | 782841 | 782861 |

PET membrane

| Pore size | 0.4 μm | | 8.0 μm |
|----------------------------------|--------------------------------------|---|--------------------------------------|
| Pore density per cm ² | 1 x 10 ⁸ | | 1 x 10 ⁵ |
| Growth area [cm²] | 0.6 | | 0.6 |
| Insert height [mm] | 13 9 | | 13 |
| Pack of | 12 pieces (12 strips x 4 inserts) | | 12 pieces (12 strips x 4 inserts) |
| Туре | smooth-walled | | smooth-walled |
| Cat. No. | 782810 782910 | | 782870 |
| Туре | IOS | | IOS |
| Cat. No. | 782811 | - | 782871 |



You need bulk packages? Five 6-well plates filled with 6 insert strips each (120 inserts) can be ordered at www.info@brand.de

Individual inserts

PC membrane

| Pore size | 0.4 μm | 1.0 μm | 3.0 μm | 8.0 μm |
|----------------------------------|---------------------|---------------------|---------------------|---------------------|
| Pore density per cm ² | 1 x 10 ⁸ | 2 x 10 ⁷ | 2 x 10 ⁶ | 1 x 10 ⁵ |
| Growth area [cm²] | 0.6 | 0.6 | 0.6 | 0.6 |
| Insert height [mm] | 13 | 13 | 13 | 13 |
| Pack of | 48 pieces | 48 pieces | 48 pieces | 48 pieces |
| Туре | smooth-walled | smooth-walled | smooth-walled | smooth-walled |
| Cat. No. | 782806 | 782826 | 782846 | 782866 |

PET membrane

| Pore size | 0.4 μm | 8.0 μm |
|----------------------------------|---------------------|---------------------|
| Pore density per cm ² | 1 x 10 ⁸ | 1 x 10 ⁵ |
| Growth area [cm²] | 0.6 | 0.6 |
| Insert height [mm] | 13 | 13 |
| Pack of | 48 pieces | 48 pieces |
| Туре | smooth-walled | smooth-walled |
| Cat. No. | 782816 | 782876 |
| Cat. No. | 782816 | 782876 |




4.4.3 Insert 2in1



- ✓ Can be used standing or suspended
- ✓ Flexible and easy to use
- ✓ Cell culture treated membrane for optimal cell growth

The smart design of the new BRAND Insert 2in1 allows for almost unrestricted compatibility with all ANSI/SLAS standard multiwell plates. In addition, it is the only cell culture insert of its kind that can be suspended in the well plates without additional support plates. This allows the 2in1 insert from BRAND to provide the flexibility you need in establishing new experimental approaches.



Applications


- + Transmigration and invasion assays
- + Toxicity assessments
- + Tissue engineering
- + Barrier and transportation studies
- + Co-cultivation
- + Polarity testing
- + Cell polarization studies

Features

- + Use in a hanging or standing position
- + Works with all common 6-, 12-, or 24-well plates
- + Surface: cellGrade™ plus
- + PC or PET membrane
- + Pore size: 0.4 μm and 8.0 μm
- + Manufactured in cleanroom ISO class 8

Hanging

If you use the Insert 2in1 as a hanging insert, add the medium to the multiwell plates before hanging the insert inside the wells (make sure the medium comes into contact with the membrane). Then fill the insert with medium.




Standing

If you would like to use the Insert 2in1 as a standing insert, place the insert into the provided multiwell plate or culture dish. Add the medium to the insert and then into the well or the culture dish.




Common applications


Co-culture



Transmigration, chemotaxis



Air-lift culture in multiwell plate



Transport/barrier analysis (TEER measurement), cytotoxity



Air-lift culture in culture dish



BRAND Insert 2in1 working volume and culture area

| Well | Working volume | Culture area |
|---------|----------------|----------------------|
| 24-well | 150 - 400 μl | 0.6 cm ² |
| 12-well | 300 - 1000 μl | 1.38 cm ² |
| 6-well | 800 - 3000 μl | 4.83 cm ² |

Increased sample volume with air-liquid interphase cultures? Switch to the BRANDplates® Insert System (see p. 72): same membrane, same culture surface as 24-well inserts, less time-wasting culture optimizations than when switching from other manufacturer systems.



Technical information & Ordering data

BRAND Insert 2in1

- TC treated (cellGrade™ plus) PC- and PET membranes
- Can be used with all common 24-, 12- and 6-well plates
- Use in hanging or standing position
- Individually packed or in multi-packs



24-well Insert 2in1

PC membrane

| Pore size | 0.4 μm | | 8.0 μm | |
|----------------------------------|---------------------|---------------|---------------------|---------------|
| Pore density per cm ² | 1 x 10 ⁸ | | 1 x 10 ⁵ | |
| Growth area [cm²] | 0.6 | | 0.6 | |
| Insert height [mm] | 10 | | 10 | |
| | | | | |
| Туре | single blister | multi-pack | single blister | multi-pack |
| Pack of | 40 ! | 4 v 12 minana | 48 pieces | 4 x 12 pieces |
| Pack OI | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces |



12-well Insert 2in1

PC membrane

| Pore size | 0.4 μm | | 8.0 μm | |
|----------------------------------|---------------------|---------------|---------------------|---------------|
| Pore density per cm ² | 1 x 10 ⁸ | | 1 x 10 ⁵ | |
| Growth area [cm²] | 1.4 | | 1.4 | |
| Insert height [mm] | 11 | | 11 | |
| _ | | 100 | | 100 |
| Туре | single blister | multi-pack | single blister | multi-pack |
| Pack of | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces |
| Cat. No. | 782720 | 782721 | 782726 | 782727 |



6-well Insert 2in1

PC membrane

| Pore size | 0.4 μm | | 8.0 μm | |
|----------------------------------|---------------------|---------------|---------------------|---------------|
| Pore density per cm ² | 1 x 10 ⁸ | | 1 x 10 ⁵ | |
| Growth area [cm²] | 4.8 | | 4.8 | |
| Insert height [mm] | 11 | | 11 | |
| Time | ain ala bliatau | manifet monde | ainala bliatau | maniki manik |
| Туре | single blister | multi-pack | single blister | multi-pack |
| Pack of | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces |
| Cat. No. | 782740 | 782741 | 782746 | 782747 |





Technical information & Ordering data

BRAND Insert 2in1 Multi-pack

- Quickly, conveniently open an entire pack
- Remove 3 inserts at one time
- Reduces packaging waste



24-well Insert 2in1

PET membrane

| Pore size | 0.4 μm | | 8.0 μm | |
|----------------------------------|---------------------|---------------------------------|----------------|---------------|
| Pore density per cm ² | 2 x 10 ⁶ | 2×10^6 2×10^5 | | |
| Growth area [cm²] | 0.6 | | 0.6 | |
| Insert height [mm] | 10 | | 10 | |
| | | | | |
| Туре | single blister | multi-pack | single blister | multi-pack |
| Pack of | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces |
| Cat. No. | 782710 | 782711 | 782716 | 782717 |

To open the entire blister simply tear off the sealing paper diagonally (purple arrow).

A perforation in the sealing paper also allows opening individual rows, while the other inserts remain securely sealed (blue arrow).

12-well Insert 2in1

PET membrane

| Pore size | 0.4 μm | | 8.0 μm | |
|----------------------------------|---------------------|---------------|---------------------|---------------|
| Pore density per cm ² | 2 x 10 ⁶ | | 2 x 10 ⁵ | |
| Growth area [cm²] | 1.4 | | 1.4 | |
| Insert height [mm] | 11 | | 11 | |
| Туре | single blister | multi-pack | single blister | multi-pack |
| Pack of | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces |
| Cat. No. | 782730 | 782731 | 782736 | 782737 |

6-well Insert 2in1

PET membrane

| Pore size | 0.4 μm | | 8.0 μm | | |
|----------------------------------|---------------------|---------------|---------------------|---------------|--|
| Pore density per cm ² | 2 x 10 ⁶ | | 2 x 10 ⁵ | | |
| Growth area [cm²] | 4.8 | | 4.8 | | |
| Insert height [mm] | 11 | | 11 | | |
| _ | 1. 1. 1.12.4 | 102 | 1.1.124 | 100 | |
| Туре | single blister | multi-pack | single blister | multi-pack | |
| Pack of | 48 pieces | 4 x 12 pieces | 48 pieces | 4 x 12 pieces | |
| Cat. No. | 782750 | 782751 | 782756 | 782757 | |



Application Note

BRAND® Insert 2in1 supports the cultivation of Reconstructed Human Epidermis (RhE) used for skin corrosion tests (OECD TG 431)

Author: BRAND GMBH + CO KG



Reconstructed Human Epidermis (RhE) is used as an alternative in vitro test system partially able to replace tests on laboratory animals and provide data that may be more predictive for humans when compared to animal testing. For these reasons 3D tissue models become more and more attractive not only for research but also in the context of regulatory hazard identification of irritant and corrosive chemicals (OECD TG 431*). However, to be used for regulatory decision making, a validated RhE must meet certain quality criteria to reliably distinguish the different hazard potentials of chemicals. Here we show that human derived keratinocytes cultivated in the BRAND Insert 2in1 differentiate into RhE models using the standard cultivation procedure including a submerged and air-liquid interphase condition. The RhE reproducibly determines the corrosive potential of the categorized chemicals.

* OECD Test Guideline for testing chemicals 431: In vitro skin corrosion: reconstructed human epidermis (RHE) test method; 2015

Methods

Cell culture

Reconstructed human Epidermis was generated using normal human keratinocytes seeded in BRAND Insert 2in1 or cell culture inserts from another manufacturer in a density of 2^*10^5 cells/cm² (125.000 cells in 200 μ l per insert). For submerged and air-liquid interphase (ALI) cultures both insert types were placed standing on the bottom of culture plates. BRAND Inserts featured a plasma-treated (cellGradeTM plus) polycarbonate membrane with a pore size of 0.4 μ m and a culture area of approximately 0.6 cm². After submerged cultivation ALI-culture was initiated to induce keratinocyte differentiation into the multilayered epidermal model and finally exposed to chemicals.

MTT assay and test substance application was performed according to the SOP for epiCS® In Vitro Skin Corrosion (CellSystems®).

Test substances

For each exposure time and chemical 3 RhE models were used for in vitro skin corrosion testing. The test chemicals applied were phosphate buffered saline (PBS) (negative control), 8N KOH (positive control), 4-(Methylthio)-benzaldehyde, lactic acid and formic acid. RhE mean viability was determined for each test chemical after 3 and 60 min of exposure and normalized to the mean viability of negative controls at the corresponding time point.

Results

Morphology

The RhE models were fixed with Bouin's Solution and subsequently cryo-embedded. Following cross sections of the RhE samples were stained with hematoxylin and eosin and subjected to histological imaging. The RhE models show the typical layers of native skin with a multilayered corneal layer (stratum corneum).




Figure 1: Hematoxylin/eosin staining of RhE models cultivated in the cell culture Insert 2in1 (1) and in an insert from another manufacturer (2). Human derived keratinocytes develop a stratified epidermis with a multilayered stratum corneum.

Barrier function test (EC50)

To determine whether the stratum corneum of RhE models cultured in different inserts developed a proper barrier function cultures were exposed to PBS and the benchmark chemical Triton X-100 for 60 min. After the exposure, RhE models were incubated in presence of MTT vital dye. Quantification of the metabolic activity was determined by measuring the optical density of the reduced MTT-dye at 570 nm wave length. Data indicates a distinct barrier function of the stratum corneum as the mean viability of the cultures was not reduced by more than 50 % at the given exposure time.




Figure 2: Viability of RhE exposed to PBS or Triton X-100 (TX-100). Data shows the optical density at 570 nm (OD) of isopropanol extracted formazan from tissue cultures.

In vitro corrosion test

First, MTT assay derived viability of RhE models was determined for 3 and 60 minutes using PBS. Measurements show that the viability of RhE models within the two insert types is comparable. However, tissue cultures from the BRAND insert 2in1 generated data with reduced standard deviations at 3 and 60 min of PBS exposure when compared to tissue culture

grown in the competitor insert (table 1).

To test whether the RhE models cultivated in BRAND insert 2in1 can also be used to distinguish the corrosive potential of chemicals, RhE models were exposed to a set of classified substances. In parallel, the same chemicals were applied to RhE models cultivated in the insert from another manufacturer used in chemical hazard identification context before. The mean viability of treated RhE models was normalized to viability data of the negative control (NC).

| OD negat | ive control | | |
|-----------------------|-------------|----------|------------|
| BRAND Ir | nsert 2in1 | Other ma | nufacturer |
| 3 min | 60 min | 3 min | 60 min |
| 2.92 | 2.21 | 2.76 | 2.38 |
| 2.95 | 2.22 | 2.82 | 2.45 |
| 2.96 | 2.44 | 2.48 | 1.79 |
| 2.94 | 2.45 | 2.47 | 1.75 |
| 2.96 | 2.52 | 2.08 | 2.23 |
| 2.99 | 2.51 | 2.06 | 2.13 |
| Standard deviation OD | | | |
| 0.02 | 0.16 | 0.36 | 0.32 |

Table 1: OD measurement of formazan-isopropanol extracted from RhE models exposed to PBS (NC). For each condition 6 tissues were tested. Measurements were performed in transparent flat bottom microplates using a microplate spectrophotometer at 540 -570 nm




Figure 3: Comparison of corrosive potential of different chemicals. NC, negative control; PC, positive control. Data show mean viability of 3 RhE per condition with standard deviation. Viability was determined by MTT assay. Optical density of isopropanol extracted formazan was measured in microplate spectrophotometer at 540 -570 nm.

BRAND Inserts 2in1 are equally suitable Figure 3: Comparison of corrosive potential of a positive control. Pata show many visibility of 3.5

to produce RhE as inserts from other manufacturers. This was shown by the comparison of H&E stained histological slides with the mulilayered stratified epidermis (fig.1) and the integrative growth of the keratinocytes with a functional barrier function was demonstrated by EC₅₀ data (fig. 2).

Conclusion

Using proven chemicals for the OECD corrosion test with RhE, we could measure data comparable with inserts of another manufacturer. The BRAND Insert 2in1 is a promising tool for use in corrosion tests and a step forward to avoid animal testing and gather data much more transferable to humans than animal testing ever will be.

The presented data show that the BRAND Insert 2in1 with PC membrane and a pore size of 0.4 µm supports the differentation of normal human keratinocytes to a stratified epidermis model. Tissue models from the two inserts predicted 4-(Methylthio)-benzaldehyde as non corrosive chemical because viability is not reduced by 50 % after 3 min and 60 min of exposure when compared to NC. Formic acid is predicted to be corrosive because viability of tissue models from both inserts is reduced by more than 50% and more than 85% after exposure for 3 min and 60 min, respectively. Lactic acid is a corrosive substance of subcategory 1B/1C, which is shown by a viability higher than 50 % after 3 min and lower than 15 % after 60 min exposure, respectively. The not significant difference to the 50 % threshold within the 3 min exposure with the BRAND insert may be due to the small number of measurements.



Lids

Cover mats

Sealing films



Lids for 96-well standard plates

For BRAND plates $^{\circ}$ microplates Cat. No.: 7816 00-08, 7816 60-68, 7817 20-29, 7817 80-82, 7818 40-42, 7819 00-02, 7819 60-68, 7820 22-28, 7820 82

| Condensation rings | Height | Sterile | Pack of | Cat. No. |
|--------------------|--------|---------|--------------------------------|----------|
| yes | 8 mm | - | 100 pieces (20 bags of 5 lids) | 7821 50 |
| no | 8 mm | _ | 100 pieces (20 bags of 5 lids) | 7821 51 |



Lids for black and white 96-well plates with transparent bottom

For BRAND plates microplates Cat. No.:

7816 10-11, 7816 70-71, 7817 31, 7819 10-11, 7819 70-75, 7820 30-35, 7820 90-95

| Condensation rings | Height | Sterile | Pack of | Cat. No. |
|--------------------|--------|---------|--------------------------------|----------|
| yes | 9 mm | _ | 100 pieces (20 bags of 5 lids) | 7821 55 |



Lids for all 384-well plates

For BRAND*plates*® microplates Cat. No.: 7816 20-27, 7816 80-87, 7817 40-42, 7819 80-89

| Condensation rings | Height | Sterile | Pack of | Cat. No. |
|--------------------|--------|---------|-------------------------------|----------|
| no | 4.5 mm | _ | 50 pieces (5 bags of 10 lids) | 7821 52 |



Lids for all 1536-well plates

For BRAND*plates*® microplates Cat. No.: 7816 40-42, 7817 00-02, 7820 00-02

| Condensation rings | Height | Sterile | Pack of | Cat. No. |
|--------------------|--------|---------|-------------------------------|----------|
| no | 5.5 mm | _ | 50 pieces (5 bags of 10 lids) | 7821 53 |



Cover mats

Cover mats reduce the maximum volume of wells. Adhesive sealing films and polystyrene lids can also be used.

| Description | Material | Pack of | Cat. No. |
|----------------------------|----------|-----------|----------|
| for 0.3 ml 384-well plates | Silicone | 50 pieces | 701357 |

Sealing films, self-adhesive

Automation


Easy to pierce with pipette tips. Temperature range -40 °C to +90 °C. Single films.



PE top, underside PP with adhesive. Inert, chemically resistant.

Packs of 50 sheets.

Cat. No. 701370



Vinyl, acrylic adhesive. Repeatably pierceable with pipette tips. Packs of 100 sheets.

Cat. No. 701374


Fluorescence and luminescence measurement

Temperature range -40 °C +80 °C. Single films.



For fluorescence measurement Vinyl, black. Light-absorbent. Packs of 50 sheets.

701371




For luminescence measurement Vinyl, white. Reflective. Packs of 50 sheets.

Cat. No. 701372

Cell and tissue culture

Rayon. Gas-permeable. Temperature range -20 °C to +80 °C. Single films.



Non-sterile pack of 100 sheets

Cat. No. 701364 Sterile pack of 50 sheets 701365

More sealing films, see chapter II, page 116.

Comparison of sealing options for BRANDplates® microplates

| | Evaporation protection | Transparency | Handling | Price |
|---|------------------------|--------------|----------|-------|
| BRAND <i>plates</i> ® lid | + | ++ | +++ | +++ |
| Self-adhesive sealing film | ++ | ++ | ++ | ++ |
| Pressure sensitive sealing film | +++ | +++ | +++ | + |
| Gas-permeable sealing film | + | - | ++ | ++ |
| Sealing film for automation | + | - | ++ | ++ |
| Vinyl sealing film (black and white) | ++ | - | ++ | ++ |



PCR & qPCR

The Polymerase Chain Reaction (PCR) is an enzyme-based process for duplicating DNA in vitro. PCR is considered a standard method in almost all life science laboratories. The process is used in a wide variety of applications, such as DNA cloning, diagnosing genetic disorders or infectious diseases, functional gene analysis, paternity tests, and forensic analysis.

PCR is becoming increasingly important as our society ages, chronic illness increases, personalized medicine develops and as our understanding of disease diagnoses grows.

Because of this, new and even more sensitive versions are being developed all the time. Quantitative PCR (qPCR) which provides insight into the amount of amplified DNA is quickly gaining favor. BRAND offers cleanroom quality PCR consumables for sophisticated PCR and qPCR applications where quality and purity are key. Live monitoring of our validated, ISO class 8 cleanroom and a high degree of automation ensure the purity of PCR products from BRAND. Independent test laboratories accredited in accordance with ISO 17025 inspect our PCR products for the absence of DNA, DNase, RNase and endotoxins/pyrogens.



Chapter II

PCR & qPCR work areas

Sample preparation

PCR testing

Assaying and sample storage



5.1 Microtubes page 89



6.1 Single PCR tubes



page 94



6.2 PCR strips page 97



8.1 PCR cap strips page 113



8.2 Sealing films page 116







7.3 384-well plates page 109



5. Sample preparation

PCR offers outstanding flexibility and variability. In addition to different PCR versions, users can individually select their primers and polymerase. DNA or RNA serves as the starting material for the PCR. There are many different options for the isolation of DNA/RNA from the available samples. Precise test planning, clean DNA/RNA isolation, and correct preparation and creation of the master mix, are essential for a successful PCR.

In addition to the purity and high quality of the consumable materials used, how materials are handled also plays an important role. The PCR reagents used are expensive and must always be properly stored and protected while work is being carried out.

BRAND offers a wide variety of PCR-suitable microtubes with cleanliness suitable for reliable and fast sample preparation. Cleanroom production and strict quality controls ensure appropriate security and reliability.




5.1 PCR-suitable microtubes



- ✓ Lid membrane highly transparent and easy to pierce
- ✓ Tight-sealing, easy to open cap
- ✔ High-purity polypropylene free from RNase, DNA and pyrogens (acc. to LAL-test)

DNA isolation and preparation of the master mix are essential for a successful PCR, require the highest possible product cleanliness, good impermeability, and the option for use in high throughput analysis.

BRAND offers microtubes that fulfill all of the requirements for use in PCR, with certified free of RNase, DNA and endotoxins.



Applications

- + DNA and RNA isolation
- + DNA and RNA purification
- + Preparing a master mix
- + Sample dilution

Features

- + Made of pure polypropylene
- + Tight-sealing cap
- + In sizes 0.5 ml, 1.5 ml and 2.0 ml
- + Highly transparent and consistent wall thickness



- When incubating at high temperatures, we recommend using microtubes with lid closure in order to prevent the vessels from bursting open.
- Microtubes with lid closure can be centrifuged up to 30,000 x g.

Caution: The relative centrifugal force (RCF) is dependent on the radius of the rotor and the speed (RPM) of the centrifuge!

General conversion formula:

 $g = RCF = ((U/min)/1000)^2 \cdot r \cdot 1.118$

g-force Gravitational accelerationRCF: Relative centrifugal force (corresponds to the g-force)

r: Rotation radius

U/min: Rotor revolutions per minute (speed)

We advise against autoclaving microtubes. Autoclaving can be a source of contamination for disposable products.

Advantages of PP

- **High resistance to chemicals:** microtubes can be used with DMSO and other aggressive chemicals.
- Good temperature resistance: Containers remain stable even at high temperatures; these products are generally autoclavable at 121 °C (2 bar), acc. DIN EN 285.
- Minimal retention: PCR tubes, microtubes and tips have no residual wetting and the material is biologically inert

 no adhesion of biomolecules to the surfaces.



The microtubes are not recommended for long-term storage. We recommend using microtubes with screw cap (chapter III) or cryogenic tubes (chapter I).

Accessories

Microtube rack, PP

Numbered positions for 20 microtubes, 1.5 ml. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Pack of 1.

Cat. No.

7806 05



Ordering information for BRAND liquid handling equipment is provided at shop.brand.de



Mini cooler, PC

Durable polycarbonate filled with non-toxic gel. Mini coolers hold twelve 0.5 ml to 2.0 ml tubes. Pack of 1.



| Bench temp. maintained | Time held | Color | Cat. No. |
|------------------------|-----------|--------|----------|
| 0 °C | 60 min. | red | 114930 |
| -20 °C | 60 min. | yellow | 114935 |
| -70 °C | 45 min. | white | 114940 |

Microtube rack, PP

Stackable racks with alphanumeric positions. Operating temperature -20 °C to +90 °C. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Density 1.2 g/cm³. Will not float in waterbath. Pack of 5.



| For Ø up to mm | Positions | white Cat. No. | blue Cat. No. | red Cat. No. |
|-------------------|-----------|-------------------|------------------|-----------------|
| 11 | 8 x 16 | 4341050 | 4341051 | 4341052 |
| 13 | 6 x 14 | 4341000 | 4341001 | 4341002 |

--=

Technical information & Ordering data

Microtubes with lid, BIO-CERT®

- Sterile and free from DNA, RNase, pyrogens and ATP
- Graduation for approximate volume determination
- Tight-sealing, easy to open lid





Microtubes with lid

| Volume |
|----------------------------------|
| Lid membrane Ø [mm] |
| Lid membr. thickness [mm |
| Outer-Ø [mm] |
| Height with closed lid [mm] |
| RCF max. (at 20 °C, t 20 min) |
| Pack of |
| Cat. No. |


| 1.5 ml | |
|----------------------------|--------------------------|
| 8.5 | |
| 0.3 | |
| 10.75 | |
| 40.8 | |
| 20,000 | |
| 450 piece (30 blister p | es packs of 15 tubes) |
| 780400 | |

Information on the different quality levels is provided on page 5.



Microtubes with lid

- Free from PCR inhibitors
- Perfect lid seal to protect against evaporation
- High transparency, with easy to pierce lid membrane



Lid membr. thickness [mm Outer-Ø [mm] Height with closed lid [mm] RCF max. (at 20 °C, t 20 min) Pack of Cat. No.

| 0.3 |
|------------|
| 7.9 |
| 31.4 |
| 10,000 |
| 500 pieces |
| 780507 |
| |

| 2.0 ml | |
|------------|--|
| 0.3 | |
| 10.7 | |
| 41.15 | |
| 20,000 | |
| 500 pieces | |
| 780550 | |



Microtubes with lid closure, PCR-BIO-CERT®

- Enhanced lid closure protects against accidental opening while heating samples
- Free from PCR inhibitors
- Can be centrifuged up to 30,000 x g



Ø 9.8 mm



Microtubes with lid closure

| volumen |
|----------------------------------|
| Lid membrane thickness [mm] |
| Outer-Ø [mm] |
| Height with closed lid [mm] |
| RCF max. (at 20 °C, t 20 min) |
| Pack of |
| Cat. No. |
| |

| 0.5 ml | |
|------------|--|
| 0.3 | |
| 10.0 | |
| 30.0 | |
| 30,000 | |
| 500 pieces | |
| 780536 | |
| | |

| 0.5 ml | |
|------------|--|
| 0.3 | |
| 10.0 | |
| 30.0 | |
| 30,000 | |
| 500 pieces | |
| 780536 | |

| 1.5 ml | 2.0 ml |
|--------|--------|
| 0.4 | 0.45 |
| 12.8 | 12.8 |
| 38.8 | 40.0 |
| 30,000 | 30,000 |

500 pieces

780546



1000 pieces

780540

Ø 9.9 mm





6. PCR tubes for small and medium sample throughput

When establishing a PCR, users must select the right primer, reagents, optimal annealing temperatures, and the ideal duration for each PCR step.

The optimal method is important to ensure the PCR reaction is stable and that no complications occur later in the routine process. A large number of preliminary tests are required to check the influence of different parameters on the individual PCR.

BRAND offers a broad spectrum of single PCR tubes and PCR strips. Our product range allows users to optimize their methods and work economically, even with a small number of samples. Users can also process samples in parallel without accidental mix-ups thanks to the different color options.



6.1 Single PCR tubes




- ✓ Thin walls for rapid heat transfer
- ✓ Tightly closing covers protect samples against evaporation
- ✓ Colors available for easy identification of samples

Single PCR tubes from BRAND with volumes of 0.2 and 0.5 ml are the efficient solution for small and medium sample throughput. The extra thin-walled tubes ensure optimum heat transfer during PCR for shorter cycle times over a wide range of temperatures.

To prevent sample losses from heating, the caps reliably seal the vessels with their tight fit. This ensures quality and repeatable results even with small sample volumes. At the same time, the caps can be opened and closed with ease.

Tubes are available in several colors, allowing easy visual sample tracking.



Applications

- + Tests with small sample sizes
- + Testing different primer variants
- + Establishing a method
- + Inspecting reagents

Features

- + Made of pure polypropylene
- + Tight-sealing cap
- + In sizes 0.2 and 0.5 ml and colors transparent, rose, yellow, green and blue
- + Suitable for all standard thermal cyclers

If the PCR tubes become deformed, check whether the closing pressure for the thermocycler lid is too great or whether it is distributed unevenly over the PCR tube: Most cycler manufacturers recommend placing empty tubes with the same type of cap (domed or flat) into the corners of the thermoblocks as "buffers," in order to distribute the force over multiple tubes when there is only a small numbers of samples.


We advise against autoclaving PCR products. Autoclaving can be a source of contamination for disposable products.

In addition to setting up PCR reactions, tubes are suitable for:

- setting up a restriction digest or ligation
- aliquoting and short-term storage between 4 °C and 25 °C

PCR tubes should not be used:

- · to store samples for an indefinite period of time
- to store samples and aliquots down to -20 °C





PCR tubes:

Tubes with highly transparent caps for sensitive detection of fluorescence signals

PCR plates:

Plates that fit in quantitative Real-Time Seals, highly transparent for sensitive thermal cyclers, also available in white

PCR seals:

detection of fluorescence signals

Accessories

Ordering information for BRAND liquid handling equipment is available at shop.brand.de



Mini cooler, PC

Mini coolers are designed to protect a wide range of solutions (enzymes, DNA, RNA, cell suspensions) by helping to maintain freezer temperatures on the lab bench. Durable polycarbonate filled with non-toxic gel. Mini coolers hold twelve 0.5 ml to 2.0 ml tubes. Pack of 1.



| Bench temp. maintained | Time held | Color | Cat. No. |
|------------------------|-----------|--------|----------|
| 0 °C | 60 min. | red | 114930 |
| -20 °C | 60 min. | yellow | 114935 |
| -70 °C | 45 min. | white | 114940 |

PCR box/rack, PP

Assorted colors (red, yellow, green, purple, blue). Suitable for sample preparation, for keeping and storing 0.2 ml single tubes, 8-strips, and 12-strips, and 96well PCR plates. These racks can also be stacked without lids. Withstand temperatures from -80 to +121 °C. Pack of 5.







Mini cooler PCR, PP

With transparent lid. For protecting samples from warming. The mini PCR cooler keeps samples at 4 °C for approximately 3 hours.

The insulating gel changes from violet to pink at 7 °C. Suitable for 0.2 ml single tubes, 8-strips, and 12-strips, as well as 96-well PCR plates. Pack of 2.







Technical information & Ordering data


Single PCR tubes with flat or domed cap

- · Perfect cap seal to protect against evaporation
- Easy to open and close
- Various colors allow fast sample identification

Pack of

Cat. No.

Fits all commonly used thermocyclers with a heated lid



96 www.brand.de

(2 bags of 500)

781311

(2 bags of 500)

781312

(2 bags of 500)

781310


(2 bags of 500)

781314

(2 bags of 500)

781313


6.2 PCR strips



- ✓ High flexibility with a wide range of cap types and film strips
- ✓ Reduced evaporation losses thanks to tightly closing cap strips
- ✓ Rapid heat transfer through thin vessel walls

PCR 8- and 12-tube strips offer a flexible solution for your PCR or qPCR with medium sample volumes. The choice is yours: domed caps for extra sealing pressure via the lid of the thermal cycler, or flat caps required for qPCR. Attached cap strips can be easily opened and closed with one hand, while separate cap and film strips are especially suitable for automation, as they will not obstruct robotics.

All variants seal the vessels reliably, effectively protecting your samples from evaporation and contamination. BRAND's cleanroom quality ensures that the strips are free of DNase, DNA, RNase, and pyrogens by producing them under controlled cleanroom conditions. This ensures reliable and reproducible results.



Applications

- + Tests using small sample sizes
- + Routine applications with triple repetition and appropriate negative controls
- + Single real-time tests

Features

- + Made of pure polypropylene with flat or domed caps
- + Available in low or standard profiles
- + Available in various colors for sample identification or white for optimized qPCR
- + Strips with three connectors for increased rigidity



- PCR strips with a connector offer good flexibility.
 The strips can be cut easily using scissors or by twisting them for individual adjustment.
- For applications using strips with increased rigidity, we recommend using tubes with three braces. These cannot be easily divided, but offer maximum security thanks to improved stability.
- Side grip tabs and attachments on the individual caps allow for easy opening and contamination-free handling.
- Strips with attached individual lids offer improved protection against contamination and reduce the danger of mix-ups.

We advise against autoclaving PCR products.
Autoclaving can be a source of contamination for disposable products.

White PCR products by BRAND yield significantly better results in qPCR than transparent vessels. In combination with the smooth surfaces, the white color ensures optimal reflexion of the fluorescence signals.

Accessories





Cap Tool

For reliable sealing and opening of cover caps. Handy and light-weight material for fatigue-free operation. Pack of 1.



781419





PCR box/rack, PP

Assorted colors (red, yellow, green, purple, blue). Suitable for sample preparation, for keeping and storing 0.2 ml single tubes, 8-strips, and 12-strips, and 96-well PCR plates. These racks can also be stacked without lids. Withstand temperatures from -80 to +121 °C. Pack of 5.



781362





Mini cooler PCR, PP

With transparent lid. For protecting samples from warming. The mini PCR cooler keeps samples at 4 $^{\circ}$ C for approximately 3 hours.

The insulating gel changes from violet to pink at 7 °C. Suitable for 0.2 ml single tubes, 8-strips, and 12-strips, as well as 96-well PCR plates. Pack of 2.

Cat. No.

781260






Technical information & Ordering data

PCR strips with detached cap strips

- Domed or flat cap strips for a perfect seal
- Contamination-free opening with grip tabs on the end and side of each cap
- Numbered wells for clear identification









6666666

PCR 8-tube strips

| Color |
|-------------|
| Volume [ml] |
| Pack of |
| Cat. No. |

| transparent | | |
|-------------|-------|--|
| 0.2 | q PCR | |
| 125 pieces | | |
| 781320 | | |
| | | |

| rose |
|------------|
| 0.2 |
| 125 pieces |
| 781321 |
| |

| green | |
|------------|--|
| 0.2 | |
| 125 pieces | |
| 781323 | |

| blue | |
|------------|--|
| 0.2 | |
| 125 pieces | |
| 781324 | |



PCR 8-cap strips



| transparent |
|-------------|
| domed |
| 125 pieces |
| 781340 |

| rose | |
|------------|--|
| domed | |
| 125 pieces | |
| 781341 | |

Charles har part part part

| yellow | |
|------------|---|
| domed | - |
| 125 pieces | |
| 781342 | 1 |

| green | blue |
|------------|------------|
| domed | domed |
| 125 pieces | 125 pieces |
| 781343 | 781344 |

| transp | arent |
|--------|-------|
| flat | q PCR |
| 125 pi | eces |
| 78133 | 4 |

Large pack: PCR 8-tube strips and 8-cap strips

| Color | transparent | transparent |
|-------------|--|--|
| Volume [ml] | 0.2 | 0.2 Q PCR |
| Cap | domed | flat |
| Pack of | 250 pieces each (8-tube strips and 8-cap strips) | 250 pieces each (8-tube strips and 8-cap strips) |
| Cat. No. | 781327 | 781326 |



PCR 12-tube string


| Color | transparent |
|-------------|-------------|
| Volume [ml] | 0.2 |
| Pack of | 80 pieces |
| Cat. No. | 781280 |

| PCR 12-cap strips | |
|-------------------|-------------|
| Color | transparent |
| Сар | domed |
| Pack of | 80 pieces |
| Cat. No. | 781290 |



PCR strips with attached cap strips

- Attached cap strips with domed caps for one-handed operation
- · Contamination-free opening thanks to grip tab on the end
- Thin-walled wells for good temperature transmission






PCR 8-tube strips with attached cap strips

| Color | transparent |
|-------------|-------------|
| Volume [ml] | 0.2 |
| Cap | domed |
| Pack of | 125 pieces |
| Cat. No. | 781330 |

Information on the different quality levels is provided on page 5.

PCR strips with attached individual caps


- Highly transparent, flat caps for qPCR applications
- · Easy to separate 8-piece strips with 1 connector for maximum flexibility
- Highly stable 8-piece strips with 3 connectors for extremely secure handling
- Standard profile and low profile for reduced volumes





PCR 8-tube strips with single connector

| Profile | standard | low profile |
|-------------|---|---|
| Volume [ml] | 0.2 Q PCR | 0.15 Q PCR |
| Color | transparent | transparent |
| Pack of | 120 pieces (10 bags of 12 strips) | 120 pieces (10 bags of 12 strips) |
| Cat. No. | 781332 | 781333 |












7. PCR plates for medium and high sample throughput

As new PCR methods become established all the time, the number of different tests completed is also growing. PCR is considered a standard process in many fields. In addition to processes with medium sample throughput, high throughput applications are becoming more and more common in order to save time and costs. Easy and secure handling is essential for managing growing sample quantities. Users are working to optimize processes and reduce the consumption of materials and reagents.

BRAND offers ideal consumable materials for high throughput analysis, thanks to its wide-ranging product portfolio of PCR plates. Extra thin walls, smooth surfaces to avoid sample loss due to interaction with the material, and different colors and shapes are ideal for use in a broad spectrum of applications and equipment. Their standardized ANSI/SLAS format allows them to be used in all commonly available cyclers.



7.1 24-well | 48-well PCR plates




- ✓ Compact format fits all common thermal cyclers
- ✓ Raised well edges protect against cross-contamination
- Rapid heat transfer through thin vessel walls

With 24- and 48-well PCR plates, you can handle medium sample volumes with ease. The compact format works with all common thermal cyclers and provides easy handling compared to strips or single tubes.

To avoid cross-contamination from well to well, the edges of the wells are slightly raised so that you always obtain reliable results. Thin vessel walls ensure rapid temperature transfer for short cycle times.

The cleanroom quality of PCR consumables from BRAND guarantees reliable results.



Applications

- + Tests using medium sample sizes
- + Testing different primer variants
- + Small sample throughput with a large number of repetitions

Features

- + Made of pure polypropylene
- + Extra-thin walls for fast temperature transmission
- + Tight sealing with cap strips and film strips
- + Compatible with all commonly available cyclers
- + For use with multichannel pipettes



- The plates allow for work even with small sample throughput thanks to their compact design. This provides the perfect balance between efficiency and ease of handling.
- Unique alphanumeric codes prevent mix-ups.
- The plates can be sealed using cap strips or sealing film strips. Closing individual rows reduces the risk of mixups and contamination.

 To ensure an optimal plate format with a small number of samples, non-skirted PCR plates can be cut using regular scissors.





We advise against autoclaving PCR products. Autoclaving can be a source of contamination for disposable products.

Technical information & Ordering data

24-well and 48-well plates, non-skirted

- Compact standard format fits all commonly used thermocyclers with a heated lid
- Free from DNA, RNAse, pyrogens and PCR inhibitors
- Easy to seal with 8-cap strips or sealing film strips





24-well, non-skirted, standard profile





| Туре |
|-------------|
| Well rim |
| Color |
| Volume [ml] |
| Pack of |
| Cat. No. |

| standard | standard |
|---------------------------------|---------------------------------|
| not elevated | not elevated |
| transparent | white |
| 0.2 | 0.2 |
| 40 pieces (5 plates per bag) | 40 pieces (5 plates per bag) |
| 781411 | 781412 |

48-well, non-skirted, standard profile





| Туре | standard | standard |
|-------------|---------------------------------|---------------------------------|
| Well rim | not elevated | not elevated |
| Color | transparent | white |
| Volume [ml] | 0.2 | 0.2 |
| Pack of | 40 pieces (5 plates per bag) | 40 pieces (5 plates per bag) |
| Cat. No. | 781415 | 781416 |



7.2 96-well PCR plates




- ✓ Rapid heat transfer through thin vessel walls
- ✓ Suitable for all standard thermal cyclers
- ✓ Tightly sealable to protect against evaporation and contamination

For medium and high sample throughput, 96-well plates from BRAND are the efficient solution for PCR and qPCR, and can be conveniently filled using multichannel pipettes or pipetting robots. The uniform and thin wall thicknesses of the wells ensure rapid

The uniform and thin wall thicknesses of the wells ensure rapid transfer of the temperature from the cycler to the sample, thus reducing cycle times.

A number of skirt choices ensures a good fit in common thermal cyclers for efficient heat transfer. For qPCR, white plates are available that optimally reflect the fluorescence signals.



Applications

- + Use for high throughput analyses
- + Use in automated process sequences
- + Method testing with 2D gradient PCR
- + PCR arrays

Features

- + Made of PP in low profile or standard profile
- + Available with different skirt options and in white or transparent
- + Elevated well rim available to prevent well to well contamination
- + Smooth interior surfaces for minimal interactions



- · To achieve accurate and consistent results throughout the entire plate, the plates must fit the cycler exactly. The plates must be tightly sealed to prevent evaporation.
- · The right profile and skirt version must be selected depending on the cycler used.

Which plate is right for my application?

With the large number of plates and cyclers available on the market, it can be difficult to choose. However, you should

primarily choose your plate based on the cycler you are using. The compatibility table provides an overview of tested combinations, which can help you quickly find the right plate for your cycler:





We advise against autoclaving PCR products. Autoclaving can be a source of contamination

Standard or low profile?

- · Standard profile: These tubes fit into most classic thermocyclers, real-time PCR detection systems and sequencers.
- Low profile: The reduced air space above the PCR solution reduces evaporation. This ensures reaction conditions remain more constant during thermocycling than in standard profile tubes, particularly for low volumes of solution (≥ 20 μl). At the same time, these tubes also offer advantages in terms of light transmission during fluorescence assays, low volume, and fast PCR applications.

Semi-skirted and skirted PCR plates can be tagged with a barcode:



Application Note


for disposable products.

Improved sealing surface of PCR plates from BRAND to support reliable evaporation protection

Author: BRAND GMBH + CO KG

The selection of proper material and surface finishing have an important influence on the sealing properties of PCR plates. It's not only important to select quality sealing films, but considering PCR plate design also can improve results for sample

recovery during PCR. Design features such as a planar surface, and uniform plate and well thickness are essential for proper sealing and to the minimization of evaporative losses. In addition, the improved adhesion of sealing films support sample preservation. This technical note compares the attachment qualities of the Real-Time PCR sealing film (#781391) with corresponding PCR plates from several manufacturers and having different physical characteristics.






Technical information & Ordering data

96-well plate, non-skirted

- Maximum variability in cycler selection
- Good plate stability thanks to a reinforced base plate
- Quick sample identification with alphanumeric codes in contrasting colors



96-well, non-skirted, low profile



Type
Well rim
Color
Volume [ml]
Cut corner
Pack of
Cat. No.



low profile low profile not elevated not elevated transparent white 0.15 0.15 H12 H12 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781366 781367

96-well, non-skirted, standard profile



Type
Well rim
Color
Volume [ml]
Cut corner
Pack of
Cat. No.



standard standard not elevated not elevated transparent white 0.2 0.2 A12 A12 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781369 781368

96-well, non-skirted, standard profile, elevated rim



Type
Well rim
Color
Volume [ml]
Cut corner
Pack of
Cat. No.




standard standard elevated elevated transparent white 0.2 0.2 H12 H12 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781350 781354



96-well plates, semi-skirted

- Reliable sample identification with colored alphanumeric codes
- Semi-skirted plates are suitable for labeling or applying a bar code
- Optimized surface texture for reliable closure with self-adhesive sealing film



96-well, semi-skirted, low profile



Type Well rim Skirt Color Volume [ml] Cut corner Pack of Cat. No.



| ow profile | low profile |
|--------------------------------|---------------------------------|
| not elevated | not elevated |
| standard | standard |
| ransparent | white |
| 0.15 | 0.15 |
| A12 | A12 |
| 50 pieces 5 plates per bag) | 50 pieces (5 plates per bag) |
| 781371 | 781372 |



low profile low profile not elevated not elevated raised raised white transparent 0.15 0.15 Α1 Α1 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781373 781374

96-well, semi-skirted, standard profile



Type Well rim Skirt Color Volume [ml] Cut corner Pack of Cat. No.




standard standard not elevated not elevated standard standard transparent white 0.2 0.2 A12 A12 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781375 781376



standard standard elevated elevated standard standard transparent white 0.2 0.2 H12 H12 50 pieces 50 pieces (5 plates per bag) (5 plates per bag) 781400 781357

96-well plates, semi-skirted, for Roche LightCycler 480

- White PCR plate optimized for qPCR use in the Roche LightCycler 480
- Semi-skirted plates are suitable for labeling or applying a bar code



96-well, semi-skirted, low profile



Type Color Volume [ml] Cut corner

Pack of Cat. No.



781364

low profile low profile q PCR white white 0.15 0.15 H12 H12 50 pieces + 50 pieces 50 films for qPCR (5 plates per bag) (781391)



107 www.brand.de


781365

q PCR



96-well plates, skirted

- Especially rigid for secure handling with robots and automated pipetting systems
- · Available with bar code
- Optimized surface texture for reliable closure with self-adhesive sealing film



96-well, skirted, low profile



| Туре |
|-------------|
| Color |
| Volume [ml] |
| Cut corner |
| Pack of |

Cat. No.



0.15

| low profile | low profile |
|-------------|-------------|
| transparent | white |

0.15

H1 H1
50 pieces (10 plates per bag) (10 plates per bag)

781377 781378



Cap strips can also be used for sealing purposes: 781413 (flat) 781414 (domed)


Application Note

Characterisation of antibodies with BRAND PCR plates

Author: AG Arndt/ Krauss National Center for Tumor Diseases (NCT) Heidelberg Im Neuenheimer Feld 460 69120 Heidelberg


As long as the laboratory has the correct primers available, colony PCR is a fast and established method to verify the gene of interest (GOI) within a colony-forming clone. Generally, it is sufficient to transfer a minimum number of cells from the colony into the PCR premix. However, these sensitive verification methods can be disrupted by low-quality PCR tubes and contamination by nucleic acids.

The application note "Characterization of antibodies with BRAND PCR plates" describes the use of this technique to identify clones that carry a desired GOI as an insert in the vector. Reactions occurred evenly throughout all of the wells of the BRAND 96-well PCR plate (#781375), allowing for unique identification of positive clones.



 $Image: Verification of the approx. \ 1kb insert in the vector of 8 transformed clones (E.coli).$

7.3 384-well PCR plates




- For applications in automation and high-throughput analyses
- ✓ Rapid heat transfer through thin vessel walls
- ✓ Can be sealed reliably with self-adhesive sealing films

BRAND 384-well PCR plates are an economical solution for automated high-throughput analyses. The thin walls allow fast transmission of the temperature specified by the cycler, thus reducing cycle times.

The stable design of the plates makes them ideal for automation, as they can be gripped by robot systems without twisting.

To minimize evaporation with small sample volumes and to prevent contamination, seal the plates with the appropriate sealing film.



Applications

- + High throughput analyses
- + Automated process sequences
- + PCR arrays

Features

- + Made of PP in low profile
- + Compatible with most cyclers
- + 40 μ l wells for use with sample volumes between 2 μ l and 30 μ l
- + Rigid edges for ideal hold in automated applications
- + Available with a bar code



User information

To achieve good results throughout the entire plate, the plates must fit the cycler exactly. The plates must be tightly sealed to prevent evaporation. This is the only way to obtain reliable results.

The right plate for your automated system:


- · Skirted plates allows the plate to be gripped with different gripper systems
- · Rigid plates with reinforced covers provide increased stability
- · All plates are low profile.

We advise against autoclaving PCR products. Autoclaving can be a source of contamination for disposable products.

Technical information & Ordering data

384-well plates, skirted

- Transparent wells for optimal control
- Especially rigid for secure handling with robots and automated pipetting systems
- Labels and coding for easy identification



384-well, skirted





Volume [ml]
Cut corner
Pack of

Cat. No.




781345



781347

384-well plates, skirted, for Roche Light Cycler

- · White wells for better fluorescence measurement
- Optimal for Roche LightCycler 480 and comparable devices
- · Labels and coding for easy identification



384-well, skirted, for Roche Light Cycler



Type
Color
Volume [ml]
Cut corner
Pack of
Cat. No.

white PCR
0.03
A24, P24
50 pieces
(10 plates per bag)
781358



Application Note

Higher sensitivity of qPCR reactions with BRAND 384-well PCR plates

Author: BRAND GMBH + CO KG

Introduction

In many laboratories transcriptase quantitative PCR has become a standard technique to correlate phenotypic observations not only with altered protein expression data but also with quantitative changes. The quality of results obtained by RT-qPCR depends on several factors, including, but not limited to, adequate primers for reverse transcriptase and qPCR response, proper RNA sample preparation and well-defined reference genes. However, the best experimental design will give poor results if external factors like malfunction of thermocyclers and inadequate PCR-vessels disturb the reaction.

Here we show, for example, that signal amplification is improved with white 384-well PCR plates from BRAND when compared with the white plates of another well-known manufacturer.

Material and Methods

Murine hippocampi were homogenized in peqGOLD RNAPureTM buffer (PeqLab) with TissueLyser (Qiagen). Total RNA was extracted using RNeasy Kit (Qiagen). cDNA was synthesized from 1 μ g total RNA using iScriptTM cDNA Synthesis Kit (Bio-Rad).

```
For RT-qPCR the following reaction was set up:

0.5 µl Primer 5 µM

5 µl SYBR®select (2X)

1 µl cDNA

3 µl H<sub>2</sub>O

10 µl total
```

SYBR® Green based gene expression reactions were loaded in triplicates in white 384-well PCR plates from BRAND (#781358) and a competitor. Plates were sealed with qPCR sealing films from BRAND (#781391). PCR was performed in the CFX384TM real-time PCR machine (Bio-Rad).

Results

In the two different white 384-well PCR-plates none of the PCR-reactions failed. However, signal intensity was much stronger in the BRAND plates when compared to the competitor.






Figure:
Data show mean and
standard deviation of
384 RT-qPCR results per
plate.

Conclusion

RT-qPCR runs more efficiently in the white 384-well PCR-plates from BRAND in comparison with the plates from another well-known manufacturer as indicated by the slope and the plateau of the two different curves. This might be the result of optimized thin walled wells leading to a fast and homogenous thermal transfer, and by the use of raw materials from which less PCR-inhibiting substances could be released.






8. Sealing options

A reliable seal on samples is essential to protect them from contamination and evaporation during the PCR assay and during subsequent measurements. The proper seal must be selected to match the type of PCR assay conducted, as well as the PCR vessel used. Highly transparent films, for instance, are required to calculate reliable values during a real-time PCR, since the measurement is completed directly in the cycler.

In addition to choosing the right sealing option, how the film or cap is handled plays a key role in effectively protecting your samples.

Whether you choose film or cap strips: BRAND offers the right seal for any application. We provide reliable, convenient sealing options even for very small sample quantities.


8.1 PCR cap strips



- ✔ Effective protection against evaporation and contamination
- ✓ The right cap shape for your application
- Easy to open and close without risk of contamination

With PCR cap strips you can seal PCR strips and plates with 24, 48, and 96 wells reliably, and protect your samples effectively against evaporation and contamination. To prevent contamination, the cap strips are equipped with two side tabs for exact positioning before closing and a small opening attachment on each cap. This prevents contact with the inside of the cap.

The highly transparent flat cap strips are ideal for qPCR because the cap shape allows accurate fluorescence measurement. With domed cap strips, thermal cyclers without pressure sensors exert a stronger force, thus further increasing the sealing effect.



Applications

- + Sealing of PCR strips
- + Sealing of PCR plates

Features

- + Easy to attach and remove
- + Tight sealing on both strips and plates
- + Highly transparent, flat cap strips for optical measurements
- + Side grip tabs for easy, contamination-free handling





User information

Flat or domed?

- Flat cap strips are especially well-suited for optical measurements.

 The measurements can be completed directly through the cap.
- Domed caps increase the closing pressure from the lid of the thermocycler, and prevent small leaks.
- It is important to select caps depending on the cycler chosen.

Contamination-free handling:

- Sealing samples early on avoids cross-contamination and protects samples.
- The side grip tabs and attachments on every cap allow for contamination-free handling.

We advise against autoclaving PCR products. Autoclaving can be a source of contamination for disposable products.

Accessories

Cap Tool

For reliable sealing and opening of cover caps. Handy and lightweight material for fatigue-free operation.

Pack of 1.



781419










Ordering information for BRAND liquid handling equipment is available at shop.brand.de



Technical information & Ordering data

Strips of 8 PCR caps

- Domed or flat
- Easy to open and close
- Grip tabs and cap attachments for careful, contamination-free opening
- For sealing of strips and plates



Strips of 8 caps, flat





Strips of 8 caps, domed

| Cap design | domed | domed | domed | domed | domed |
|------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| Color | transparent | rose | yellow | green | blue |
| Pack of | 1000 pieces (8 bags of 125 strips) |
| Cat. No. | 781340 | 781341 | 781342 | 781343 | 781344 |


Strips of 12 PCR caps

- Easy to open and close without tools
- Grip tabs and cap attachments for contamination-free opening



Strips of 12 caps, domed

| Cap design | domed |
|------------|--|
| Color | transparent |
| Pack of | 1500 pieces (12 bags of 125 strips) |
| Cat. No. | 781290 |






8.2 Sealing films



- ✓ Temperature stability up to 120 °C
- ✓ Tight seal minimizes evaporation
- ✓ Highly transparent for use in qPCR methods

Whether standard PCR, qPCR or digital droplet PCR, the source material is always valuable and the volume always low. To protect samples and maintain their sensitivity at the same time, PCR samples must be perfectly sealed.



Applications

- + PCR and qPCR
- + For short-time storage of PCR samples
- + For contamination prevention at high-throughput analyses

Features

- + Easy to apply and remove without expensive equipment
- + Reliable adhesion for optimum protection and minimized evaporation loss
- + Highly-transparent films for optimal measurement results

116

User information

- The pressure-sensitive sealing film 781391 can be easily repositioned for a
 perfect seal thanks to pressure-sensitive adhesive beads which are only
 activated when pressure is applied.
- The film must be pressed on evenly with a sealing paddle to ensure proper seal. Please check the edges for an optimal result.
- Highly adhesive films will be difficult to remove. The plate must be fixed properly during removal to prevent spills.

For long-term storage, ensure films have good temperature stability.



Accessories

Sealing paddle

The sealing paddle helps to apply self-adhesive films. Thanks to its streamlined sides and rounded shape, it rests comfortably in your hand and ensures optimal force transfer. Pack of 2.



701381



PCR box/rack, PP

Assorted colors (red, yellow, green, purple, blue). Suitable for sample preparation, for keeping and storing 0.2 ml single tubes, 8-strips and 12-strips, and 96-well PCR plates. These racks can also be stacked without lids. Withstand temperatures from -80 to +121 °C. Pack of 5.



781362





Mini cooler PCR, PP

With transparent lid. For protecting samples from warming. The mini PCR cooler keeps samples at 4 °C for approximately 3 hours. The insulating gel changes from violet to pink at 7 °C. Suitable for 0.2 ml single tubes, 8-strips, and 12-strips, as well as 96-well PCR plates. Pack of 2.



781260





Technical information & Ordering data

qPCR film

- For real-time PCR, ELISA and other colorimetric applications
- · Highly transparent with minimal autofluorescence
- Pressure-dependent adhesive capsules allow for easy attachment (#781391)
- Minimal evaporation thanks to an innovative adhesive



qPCR film





PCR film

- · For PCR, ELISA, EIA and other optical applications
- · Transparent for visual inspection of samples
- · Simple handling and secure attachment with two grip tabs
- Minimal evaporation thanks to strong adhesive



PCR film

| Description | film |
|-------------|------------|
| Material | polyester |
| Pack of | 100 pieces |
| Cat. No. | 781390 |

Film for PCR and storage

- For PCR, ELISA and sample storage
- DMSO resistant with strong adhesive that is highly resistant to solvents
- Temperature stability down to -80 °C
- Can be removed and re-adhered without leaving a residue



Film for PCR and storage

| Description | film |
|-------------|---------------|
| Material | polypropylene |
| Pack of | 100 pieces |
| Cat. No. | 701367 |



Application Note

BRAND PCR plates and PCR sealing films - a perfectly adjusted system

Author: BRAND GMBH + CO KG

Introduction

The PCR plates from BRAND are designed to support polymerase chain reactions in several ways. The source materials selected are free of PCR inhibitors and the smooth vessel interior minimizes the binding of enzymes and nucleic acid to the walls. In addition, the ultra thin-walled PCR plate design facilitates constant, rapid and precise heat transfer leading to convincing yields and short PCR cycle times.

Generating the desired PCR product and shielding it from evaporation are decisive elements of a successful PCR. The innovative self-adhesive press-to-seal sealing film wins over with easy handling; it is not tacky to the touch and provides superior evaporation protection. The film is highly transparent and can be used for measuring the smallest signals during optical measurements like Real-Time PCR.

The BRAND PCR plates and the BRAND PCR sealing films form a masterfully tuned system. The surfaces of the PCR plates and the adhesive side of the sealing films are tailored to each other and reach striking results.

Material & Methods

Reagent reservoir

Devices:

Thermal cycler Biometra T1
Precision scale Sartorius CP 225 D
Transferpette® S (#7047 78)
Pipette tips 200 µl (#7320 08)
TipBox (#7322 08)
Roller (#7013 80)

PCR systems:

BRAND PCR system:
PCR plate (#781368)
with sealing film (#781391)
Competitor 1 PCR system:
PCR plate with matching sealing film

Competitor 2 PCR system:

PCR plate with matching sealing film

Chemicals reagents:

Water (10 ml [50 µl each well]) Cationic dye methylene blue

Measurement of evaporation losses of different PCR systems

(#7034 59)


A mixture of water with the cationic dye methylene blue was prepared. In each PCR plate every well was filled with 50 μ l of the water dye mixture and sealed with adhesive sealing film. The weighed portion of the plates and the sealing films was determined before and after the filling of the wells. The roller was used to ensure a firm seal. The PCR plates were then put into the thermal cycler Biometra T1 and a PCR run was performed (table 1).

Temperatures and times during the thermal cycler process (table 1)

| Temperature | Time |
|-------------|--------|
| 94 °C | 3 min |
| 94 °C | 30 sec |
| 50 °C | 30 sec |
| 72 °C | 30 sec |
| 72 °C | 10 min |

Finally, the weighting portion of the PCR plates was examined again.

Analysis and Results



The percentaged evaporation losses of the different PCR systems were determined and represented in a graph (figure 1).



Conclusion

To obtain successful PCR results it is important to use a harmonizing PCR system. The PCR plates have to be securely sealed to preserve the generated PCR products. The adhesive surface of the highly transparent self-adhesive sealing film of BRAND goes hand in hand with the surface of the BRAND PCR plates. The encapsulated, pressure sensitive adhesive keeps the film easy to handle and non-tacky to the touch. After sealing, areas above the sample wells remain adhesive free and do not distort PCR samples. On top the ultra-thin liner and high transparency allow detection of smallest signals during the Real-Time PCR.



PCR products at a glance

Low throughput

Single PCR tubes


page 94



- Volume: 0.2 and 0.5 ml
- Various colors available
- Sealing options:
 - flat cap (attached)
 - domed cap (attached)

PCR strips

page 97



- Volume: 0.15 and 0.2 ml
- 8- and 12-tube strips
- Various colors available
- Sealing options:
 - cap strips, attached or detached, domed or flat caps
 - single flat caps
 - sealing film strips

24-well PCR plates

page 102



- Volume: 0.2 ml
- White or transparent
- Sealing options:
 - cap strips
 - sealing film strips

Plate designs

Standard / low profile

Depending on the sample volumes





Non-skirted, semi-skirted, skirted

Non-skirted PCR plates are suitable for most commercially available thermal cyclers.



Semi-skirted PCR plates can easily be labeled or tagged with a barcode.




Skirted PCR plates are especially rigid, and are optimally suited for use with automatic pipetting systems.



High throughput

48-well PCR plates

page 102



- Volume: 0.2 ml
- · White or transparent
- Sealing options:
 - cap strips
 - sealing film strips

96-well PCR plates

page 104



- Volume: 0.15 and 0.2 ml
- White or transparent
- Sealing options:
 - cap strips
 - sealing film or sealing film strips

384-well PCR plates

page 109



- Volume: 2 30 μl
- White or transparent
- Sealing options:
 - sealing film
- Suitable for Roche LightCycler 480

Sealing options

Cap strips

page 113

- Optimal seal for 8-tube strips or individual plate rows.
- Reliable seal thanks to optimized fit, even for plates.
- Available domed and flat

Sealing film strips

page 116

Sealing film strips for quickly and reliably sealing strips and plate areas.



page 116

- Fast, reliable seal for whole plates to prevent evaporation
- Highly transparent film for use in real-time PCR









SAMPLE STORAGE

Safe and reliable storage is essential to working efficiently in the laboratory. In addition to selecting and complying with specific storage conditions, having the right storage containers plays a key role. Samples must be protected against aging and contamination over long periods of time. In addition to appropriate temperature stability, volume, and format, containers also need to provide space-saving storage and easy identification to handle large numbers of samples.

To manage such samples, BRAND offers a range of microtubes with screw caps, deep-well plates and 96-well tube racks providing simple and efficient solutions for sample storage at temperatures down to -196 °C. Alphanumeric codes, individually coded tubes, bar codes, colored screw caps or cap inserts facilitate fast sample identification and ensure efficient sample management. Different styles of cryogenic tubes are available for long-term storage.



Chapter III

Sample storage work areas

Storage down to -20 °C

Storage down to -80 °C

Storage down to -196 °C



9.1 Microtubes with snap lid



9.2 96-well microplates, PP, and deep-well plates, PS, p. 128



10.1 Microtubes with lid closure p. 132



10.2 Microtubes with screw cap p. 134



11.1 Microtubes with silicone seal p. 144



11.2 Cryogenic tubes p. 150



10.3 Deep-well plates, PP p. 137



10.4 Tube racks p. 141

- Short-term storage
- Intermediate storage

- Long-term storage of non-critical samples
- Intermediate storage of sensitive samples
- Sample databases
- Storage of cells
- Long-term storage



9. Sample storage down to -20 °C

Often, samples need to be stored for a short time during a test procedure so that they can be processed again later on. These samples are often frozen for short periods of time at -20 °C to prevent undesirable degradation or intermediate reactions. It is important to ensure these samples remain clearly identifiable and are stored in such a way that they are reliably protected from contamination. Tight sealing caps, high purity and inert materials are essential.

BRAND offers a large range of microtubes with snap lids or screw caps offering users excellent flexibility and security. Carefully selected materials and precise finishing ensure samples are well protected.

Different colors also ensure they can be clearly classified and identified.




9.1 Microtubes with snap lids



- ✓ Tight sealing snap lid
- ✓ Can be opened and closed with one hand
- ✓ Available in different colors for clear sample identification

It is important to store samples securely so that they are protected against contamination during long procedures. Convenient handling is also important for ensuring processes can be completed quickly.

Microtubes with snap lids from BRAND offer tight-sealing lids with convenient lid opening mechanisms. They are also available in different colors to facilitate easy identification guaranteeing smooth work processes.



Applications

- + Aliquoting
- + DNA and RNA isolation and purification
- + Use in analysers
- + Sample dilution
- + Short-term sample storage

Features

- + Made of pure polypropylene
- + Tight-sealing lid
- + Available in sizes 0.5 ml, 1.5 ml and 2.0 ml
- + Highly transparent
- + Autoclavable at 121 °C (2 bar), acc. DIN EN 285



User information

• The microtubes with snap lids can be centrifuged up to 20,000 x g. The rotor fit and tared weight distribution must be taken into consideration. Even minimal weight differences can cause an imbalance and damage both the centrifuge and the vessel.

Caution: The relative centrifugal force (RCF) is dependent on the radius of the rotor and the speed (RPM) of the centrifuge.

General conversion formula:

 $g = RCF = ((U/min)/1000)^2 \cdot r \cdot 1.118$

g-force: Gravitational acceleration RCF: Relative centrifugal force (corresponds to the g-force)

Rotation radius r:


U/min: Rotor revolutions per minute (speed)

Microtubes should not be filled to the top during freezing, due to volumetric expansion. The recommended fill levels correspond to the top graduated lines.

The microtubes with snap lids are not recommended for long-term storage. We recommend using microtubes with a screw cap (chapter III) or cryogenic tubes (chapter I). These allow for safe long-term storage, preventing the lid from breaking.

Refrigerated or frozen samples generally used in testing should be exposed to the smallest temperature fluctuations possible. Try to maintain the temperature using

during aliquoting.



Accessories

Microtube rack, PP

Stackable racks with alphanumerical positions. Operating temperature -20 °C to +90 °C. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Density 1.2 g/ cm³. Will not float in waterbath. Pack of 5.



| For Ø up to mm | Positions | white Cat. No. | blue Cat. No. | red Cat. No. |
|-------------------|-----------|-------------------|------------------|-----------------|
| 11 | 8 x 16 | 4341050 | 4341051 | 4341052 |
| 13 | 6 x 14 | 4341000 | 4341001 | 4341002 |

Microtube rack, PP

Numbered positions for 20 microtubes, 1.5 ml. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Pack of 1.

| Cat. No. | 7806 05 |
|-----------|---------|
| Cut. Ito. | 100000 |



Mini cooler, PC

Durable polycarbonate filled with non-toxic gel. Mini coolers hold twelve 0.5 ml to 2.0 ml tubes. Pack of 1.



| Bench temp. maintained | Time held | Color | Cat. No. |
|------------------------|-----------|--------|----------|
| 0 °C | 60 min. | red | 114930 |
| -20 °C | 60 min. | yellow | 114935 |
| -70 °C | 45 min. | white | 114940 |



Technical information & Ordering data

1.5 ml microtubes with snap lid

- Easy handling with perfectly sealing and easy-to-open lids to protect against contamination
- Frosted marking area
- Autoclavable at 121 °C (2 bar), acc. DIN EN 285



Large pack: 1.5 ml microtubes with lid, transparent

| Color | transparent |
|----------------------------------|--------------------------------|
| Lid membrane Ø [mm] | 8.5 |
| Lid membrane thick- ness [mm] | 0.3 |
| Outer-Ø [mm] | 10.75 |
| Height with closed lid [mm] | 40.8 |
| RCF max. (at 20°C, t 20 min) | 20,000 |
| Pack of | 3000 pieces (6 bags of 500) |
| Cat. No. | 780502 |

Additional microtubes in higher purity classes are listed in chapter II "PCR" (p. 105)






9.2 96-well microplates, PP and deep-well plates, PS



- ✓ ANSI/SLAS conforming
- ✓ Alphanumeric coding and cut corner for easy sample identification
- ✓ Optimal sample recovery

PP microplates and PS deep-well plates are a good choice for space-saving, short-term storage of large numbers of samples down to -20 °C. Thanks to their compact design and the option for using multi-channel pipettes or robots, they can be used to safely and reliably process even large quantities of samples.



Applications

- + Sample storage down to -20°C
- + Cultivating microorganisms
- + Extracting nucleic acids and proteins
- + Screening tests or fluorescence measurements

Features

- + Highly transparent polystyrene plate for optical measurements
- + Optimal sample collection and mixture thanks to U-shaped base
- Usable with multi-channel systems and in automation processes
- + Alphanumeric coding for reliable sample identification



- The highly transparent PS plate allows for easy visual inspection.
- The raised edges of the well protect against contamination, allowing for a secure closure using self-adhesive
- Barcodes can be applied to the sides for clear identification. These ensure clear classification and prevent mix-ups, even with large numbers of stored samples. An ordering form for adding bar codes to your products is

available on our website:



Sealing films for automation applications



Film with adhesive-free areas, easy to puncture and highly resistant against chemicals (Cat. No. 701370).



Pre-punched film, for multiple punctures by pipette tips (Cat. No. 701374)



Additional sealing films are available in our online shop at shop.brand.de

Sealing mats

The mats are ideal for short-term storage, and reliably protect samples against contamination and evaporation. Working volumes are reduced as follows when using sealing mats:

| Deep-well plate [Cat. No.] | Material | | Max. filling volume with sealing mat* [ml] | Sealing mat [Cat. No.] |
|-------------------------------|----------|-----|--|---------------------------|
| 701352 | PS | 1.1 | 1.00 | 701360 |

^{*} approx. 2 mm space to the mat

Accessories

Sealing paddle

The sealing paddle helps to apply self-adhesive films. Thanks to its streamlined sides and rounded shape, it rests comfortably in your hand and ensures optimal force transfer. Pack of 2.



701381





Ordering information for BRAND liquid handling equipment is provided at


shop.brand.de



Technical information & Ordering data

96-well microplates made of PP

- Raised well edges provide protection from contamination
- Usable with multi-channel systems and automation
- Secure closure using self-adhesive sealing film





96-well microplates

Packaging unit

Order no.

Volume

0.3 ml Round Well-Format U-shaped base Base shape 14.35 Height [mm]

14.35 mm


100 pieces (10 pieces per bag)

701330

| Order no. | 782152 |
|----------------|----------------------------------|
| Packaging unit | 50 pieces (10 pieces per bag) |
| Material | PS |
| Cover | Lid |
| | |

96-well deep-well plates made of PS

- Highly transparent
- · Stackable for space-saving storage
- Usable with multi-channel systems and automation





96-well deep-well plates

Cat. No.

| Capacity | 1.1 ml |
|--------------|-----------|
| Well shape | round |
| Bottom | round |
| Height [mm] | 41 |
| Pack of | 32 pieces |
| Cat. No. | 701352 |
| | |
| Cover | mat |
| Material | mod. PE |
| Autoclavable | no |
| | |
| Pack of | 24 pieces |

781360

Tips for using sealing mats are provided on page 129.



10. Sample storage down to -80 °C

If the number of samples in use increases and processes are automated, laboratories need to store large quantities of samples for longer time periods. We recommend storage at -80 °C for long-term protection of samples.

Key characteristics of storage plates and tubes are compact formats for space saving storage, secure closure, easy handling and versatile materials for flexible applications. BRAND offers a large number of different storage options that reliably protect samples down to -80 °C and are easily integrated into different applications. Deep-well plates allow for space-saving storage of large numbers of samples. The ANSI/SLAS format of deep-well plates allows for the utilization with automated processes and for creating large sample libraries. Tight-sealing microtubes with screw caps or lid closure and tube racks allow for space saving storage of many samples and the taking of individual samples at the same time.



10.1 Microtubes with lid closure



- ✓ Highly transparent
- ✓ Lid closure for secure storage
- ✓ Suitable for centrifugation up to 30,000 x g

Microtubes with lid closure allow for sample storage down to -80 $^{\circ}$ C with easy, consistent handling. Practical lids are convenient for opening and closing quickly and easily with one hand. Their high-purity polypropylene and high transparency make them ideal storage vessels especially for valuable samples.



Applications

- + Sample storage
- + Aliquoting and sample preparation
- + Extracting nucleic acids and proteins
- + Screening tests
- + For use in analysers

Features

- + High-purity polypropylene with very good chemical resistance
- + Tight-sealing caps with lid closure
- + Withstand centrifugation up to 30,000 x g
- + Autoclavable at 121 °C (2 bar), acc. DIN EN 285



User information

Microtubes are exposed to high loads in general, and in particular under thermal stress, such as during thermal denaturation. The biggest danger is that the lid may break open as pressure increases. Microtubes with lid closures provide optimal protection due to the significantly higher force required to open them. This graphic shows lid opening forces in Newtons (N).






The lid closure protects against accidental opening of the lid.

The wide lid rim facilitates one-handed operation.

Correct thawing

Significant temperature fluctuations put a strain not only on the materials used in vessels, but on the samples as well. Because of this, avoid frequent thawing and freezing, and thaw samples stored at -80 °C slowly and carefully. Clean the exterior of the sample vessel thoroughly after thawing to remove any contamination.

Lid opening force



Thawing tips:

- Thaw slowly (overnight in a 4 degree refrigerator)
- Thaw in a water bath with constant circulation
- Do not actively apply heat

Technical information & Ordering data

Microtubes with lid closure

- · Lid closure to ensure good lid security
- · High transparency
- Frosted marking area





Microtubes with lid closure

| Volume | 0.5 ml | 1.5 ml | 2.0 ml |
|-------------------------------|------------|-------------|------------|
| Lid membrane thickness [mm] | 0.3 | 0.4 | 0.5 |
| Outer-Ø [mm] | 10.0 | 12.8 | 12.8 |
| Height with closed lid [mm] | 30.0 | 38.8 | 40.0 |
| RCF max. (at -5 °C, t 20 min) | 30,000 | 30,000 | 30,000 |
| Pack of | 500 pieces | 1000 pieces | 500 pieces |
| Cat. No. | 780536 | 780540 | 780546 |




10.2 Microtubes with screw cap and plug seal



- ✓ Screw cap with plug seal ensures secure closure
- ✓ Silicone-free
- ✓ Microtubes with round bottom withstand RCF to 17,000 x g (at 20 °C, 20 min)

Expensive reagents and formulations are best protected in microtubes with screw caps. A screw cap offers reliable protection, preventing accidental opening. The plug seal in the cap ensures a secure closure, to provide a tight seal for excellent protection against freeze drying and without the danger of silicone contamination. This means they are an especially good choice for sensitive samples.



Applications

- + Aliquoting reagents
- + Storage of sensitive samples
- + Storage of biological materials, such as serums or blood samples
- + Preparing formulations

Features

- + Tubes made of highly transparent polypropylene
- + Non-graduated
- + Silicone-free
- + Colored cap inserts available for sample identification



User information

- Ideal for storing sensitive samples and for heating and centrifuging samples. The plug seal minimizes the risk of samples freeze drying, reliably protecting even your most valuable samples.
- Tubes with screw cap should not be filled to the top during freezing due to volumetric expansion.
- Microtubes with a plug seal are a good choice to prevent silicone seal contamination of sensitive samples during storage.



Self-standing tubes with a foot-rim can easily be opened in the rack with one hand



Accessories

Cryogenic tube rack

For self-standing cryogenic tubes and tubes with screw cap. Pack of 4.





Mini cooler, PC

Durable polycarbonate filled with non-toxic gel. Mini coolers hold twelve 0.5 ml to 2.0 ml tubes. Pack of 1.

| 5 | | |
|---|-------|----------|
| d | Color | Cat. No. |
| | red | 114020 |

| bench temp. maintained | Time netu | Color | Cat. No. |
|------------------------|-----------|--------|----------|
| 0 °C | 60 min. | red | 114930 |
| -20 °C | 60 min. | yellow | 114935 |
| -70 °C | 45 min. | white | 114940 |

Microtube rack, PP

Stackable racks with alphanumerical positions. Operating temperature -20 °C to +90 °C. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Density 1.2 g/cm³. Will not float in waterbath. Pack of 5.



| For Ø up to mm | Positions | white Cat. No. | blue Cat. No. | red Cat. No. |
|-------------------|-----------|-------------------|------------------|-----------------|
| 11 | 8 x 16 | 43410 50 | 43410 51 | 43410 52 |
| 13 | 6 x 14 | 43410 00 | 43410 01 | 43410 02 |

Microtube rack, PP

Numbered positions for 20 microtubes, 1.5 ml. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Pack of 1.

| Cat. No |). | 7806 05 |
|---------|----|---------|
| | | |







Technical information & Ordering data

Microtubes with attached screw cap with plug seal, non-sterile

- · High-purity polypropylene tube and PE screw cap
- Perfect cap seal to protect against evaporation and freeze drying
- Operating range -90 °C to +100 °C
- Not autoclavable






10.3 Deep-well plates, polypropylene



- ✓ Stackable
- ✓ ANSI/SLAS format
- ✓ Alphanumeric coding and cut corners for easy well identification

The compact ANSI/SLAS format allows a large number of samples to be processed at the same time, and allows for automated processing. The format is space-saving and has optimal closure options to ensure secure storage.

With a wide range of plate formats available, there is a BRAND plate to match any application. The low-profile plate is optimized to use storage space efficiently, while the 384-well plate allows handling of a large number of samples in an automated work sequence.



Applications

- + Sample storage
- + Cultivating microorganisms
- + Extracting nucleic acids and proteins
- + Screening tests

Features

- + High-purity polypropylene with very good chemical resistance
- + Optimal sample collection and mixture
- + Usable with multi-channel systems and in automation processes



User information

- Deep-well plates have a standardised ANSI/SLAS format which can be used in automated processes.
- The U-shaped base ensures optimal sample mixture and collection.
- The raised edges of the well allow for secure closure, protecting against contamination.
- The low-profile plate uses space efficiently with same well volume compared to standard plates. Use this plate for storage when you need to save as much space as possible.
- Barcodes can be applied to the sides for identification. These ensure clear classification and prevent mix-ups. An ordering form for adding barcodes is available:



- Sealing mats are ideal for short-term storage, and reliably protect samples against contamination and evaporation.
- The mats are reusable. Mats that can not be autoclaved can be cleaned with ethanol. Some mats can be autoclaved for reuse. Please note that the mats will shrink slightly if autoclaved.

Adhesive sealing films can also be used. Matching films are available on page 140 and in our online shop at shop.brand.de

Using sealing mats

Working volumes are reduced as follows when using sealing mats:

| Deep-well plate [Cat. No.] | Material | Nominal volume [ml] | Max. filling volume with cover mat* [ml] | Sealing mat [Cat. No.] |
|-------------------------------|------------------|------------------------|--|---------------------------|
| 701346 | PP | 0.5 | 0.44 | 701358 |
| 701350 | PP | 1.1 | 0.99 | 701360 |
| 701342 | PP | 1.2 | 0.97 | 701360 |
| 701340 | PP (low profile) | 1.1 | 0.85 | 701368 |
| 701354 | PP | 2.2 | 2.09 | 701362 |
| 701355 | PP | 0.3 | 0.25 | 701357 |

 $^{^{\}star}$ approx. 2 mm space to the mat

Accessories

Sealing paddle

The sealing paddle helps to apply self-adhesive films. Thanks to its streamlined sides and rounded shape, it rests comfortably in your hand and ensures optimal force transfer. Pack of 2.

Cat. No.

701381



Ordering information for BRAND liquid handling equipment is provided at shop.brand.de






Technical information & Ordering data

96-well deep-well plates made of PP

- Good chemical resistance, for example, to DMSO
- Use at -80 °C to 121 °C
- Autoclavable at 121 °C (2 bar), acc. DIN EN 285
- Free from RNase, DNase, endotoxins and human DNA (except 701340)



| 96-well deep-well plates | 28.5 mm | 40.6 mm | 41.4 mm | 26.5 mm | 44.0 mm | 44.0 mm |
|-----------------------------|-----------|-----------|--------------|-------------|-----------|-----------|
| Capacity | 0.5 ml | 1.1 ml | 1.2 ml | 1.2 ml | 2.2 ml | 2.2 ml |
| Plate | standard | standard | elevated rim | low profile | standard | standard |
| Well shape | round | round | round | round | square | square |
| Bottom | round | round | round | round | round | V-shape |
| Height [mm] | 28.5 | 40.6 | 41.4 | 26.5 | 44.0 | 44.0 |
| Pack of | 48 pieces | 24 pieces | 32 pieces | 50 pieces | 24 pieces | 30 pieces |
| Cat No | 701246 | 701250 | 701242 | 701240 | 701254 | 701252 |

| Cover mats for 96-well deep-well plates | | | | | | |
|---|-----------|-----------|-----------|-----------|-----------|-----------|
| For plate no. | 701346 | 701350 | 701342 | 701340 | 701354 | 701353 |
| Material | PP | mod. PE | mod. PE | TPE | EVA | EVA |
| Autoclavable | yes | no | no | yes | no | no |
| Pack of | 50 pieces | 24 pieces | 24 pieces | 50 pieces | 24 pieces | 24 pieces |
| Cat. No. | 701358 | 701360 | 701360 | 701368 | 701362 | 701362 |
| | | | | | | |

| Lids, PS for 96-well deep-well plates | |
|---|-----------|
| For plate no. | 701346 |
| Material | PS |
| Pack of | 50 pieces |
| Cat. No. | 782152 |



Matching sealing films are available in our online shop at shop.brand.de



384-well deep-well plates

- Usable with multi-channel systems and in automatic processes
- Usable down to -80 °C
- Free from RNase, DNase, endotoxins and human DNA



384-well deep-well plates



Cover mats for 384-well deep-well plates

| For plate no. | 701355 |
|---------------|-----------|
| Material | silicone |
| Autoclavable | yes |
| Pack of | 50 pieces |
| Cat. No. | 701357 |

Sealing films for 96-well and 384-well plates made of PP

- Temperature stable down to -80 °C
- Tight seal to minimize evaporation
- Remove without residue to easily access samples




| inum |
|--|
| num film can be punc- for easy collection |
| to 120°C |
| ieces |
| 31 |
| |



| Aluminum | Polypropylene |
|---------------------------------------|--------------------------|
| film strips for 96-well plates | film for PCR and storage |
| -80 °C to 120 °C | -80 °C to 120 °C |
| 300 strips (50 sheets of 6 strips) | 100 pieces |
| 781382 | 701367 |




10.4 Tube racks



- ✓ Temperature resistant down to -80 °C
- ✓ Individually removable tubes
- ✓ Tubes and racks can be autoclaved in accordance with DIN EN 285 at 121 °C (2 bar)

Tube racks and racked-packed tubes offer a tight seal and compact storage format, as well as the option to remove individual vessels, helping to prevent unnecessary temperature fluctuations. In addition, they can also be used when working with multi-channel or automated systems.



Applications

- + Storage of microorganisms
- + Creating databases
- + Cell growth studies
- + Storing and transporting reagents
- + PCR, RIA or EIA

Features


- + Tight sealing closure options
- + Vessel labelling for easy identification
- + Transparency for simple sample checks
- + Autoclavable at 121 °C (2 bar), acc. DIN 285



Technical information & Ordering data

96 tube racks, non-sterile, for use with robots

- Tubes in the rack can be labelled individually, with caps
- Bar codes can be added
- Autoclavable at 121 °C (2 bar), acc. DIN EN 285






96 tube racks, non-sterile, for use with robots

| Capacity | 0.65 ml | 1.2 ml |
|----------|-----------|-----------|
| Material | PP | PP |
| Pack of | 50 pieces | 50 pieces |
| Cat. No. | 781565 | 781566 |

Tubes 1.2 ml rack-packed, non-sterile

- Tight sealing cap strips and caps
- Usable with multi-channel systems
- Tubes and racks are autoclavable at 121 °C (2 bar), acc. DIN EN 285





Complete racks with tubes

| Description | Rack with 96 individual tubes | Rack with 12 strips of 8 tubes |
|-------------|-------------------------------|-----------------------------------|
| Material | PP | PP |
| Pack of | 10 pieces | 10 pieces |
| Cat. No. | 781500 | 781510 |



Replacement tubes

| Description | Individual tubes | Strip of 8 tubes |
|-------------|------------------|------------------|
| Material | PP | PP |
| Pack of | 960 pieces | 120 pieces |
| Cat. No. | 781520 | 781525 |



Replacement caps

| Description | Individual caps | Strip of 8 caps | |
|-------------|-----------------|-----------------|--|
| Material | PE | PE | |
| Pack of | 960 pieces | 120 pieces | |
| Cat. No. | 781530 | 781555 | |



Rack with grid, empty

| Material | PP |
|----------|-----------|
| Pack of | 10 pieces |
| Cat. No. | 781540 |



11. Sample storage down to -196 °C

Creating gene databases or long-term storage of valuable cells and microorganisms requires reliable storage options and places high demands on storage containers.

To prevent chemical reactions and avoid sample degradation, most samples are stored in the gas phase of liquid nitrogen at -196 °C. In order to use this method, vessels must be able to handle extreme temperature fluctuations, have a long-lasting seal, and retain their properties over a long period of time.

BRAND offers microtubes with screw caps and silicone seals, and specialized cryogenic tubes that provide safe and reliable long-term storage.

In addition, a large, frosted marking area and colored caps ensure easy identification and durable, legible labeling.




11.1 Microtubes with screw cap and silicone seal



- ✓ Excellent seal reliability
- ✓ Fast opening and closing with 1¼ turn of cap
- ✓ High purity polypropylene

Microtubes with screw caps with silicone seals are available with different base shapes to offer greater flexibility. They seal tightly and reliably and are an excellent choice for securely storing expensive reagents. Microtubes with screw caps with silicone seals are also a secure choice for interim storage of prepared formulations to be used in later testing.



Application

- + Aliquoting reagents
- + Storage of expensive samples
- + Storage of medical materials, such as serums or blood samples
- + Preparing formulations

Features

- + All tubes are made of highly transparent polypropylene
- + Screw cap with silicone seal for secure closure
- + Variable base shape for convenience
- + Easy identification through color coding



User information

- Ideal for storing medical materials such as serums and blood samples, as well as for sample heating and centrifuging.
- The microtubes can be centrifuged up to 17,000 x g.

Caution: The relative centrifugal force (RCF) is dependent on the radius of the rotor and the speed (RPM) of the centrifuge.

General conversion formula:

 $g = RCF = ((U/min)/1000)^2 \cdot r \cdot 1.118$

g-force: Gravitational accelerationRCF: Relative centrifugal force (corresponds to the g-force)


r: Rotation radius

U/min: Rotor revolutions per minute (speed)

 Microtubes are sealed extremely well with silicone seals, without contact between the sample and the sealing ring. The containers are suitable for the storage of samples in the gaseous (vapor) phase of liquid nitrogen.



The tamper-evident screw cap guarantees the user an uncontaminated sample. A visible ring acts as an antitamper seal, which breaks when the cap is first opened.
 The microtubes have a silicone seal, and are suitable for the storage of samples in the gaseous (vapor) phase of liquid nitrogen.



Self-standing tubes with a foot rim can easily be opened in the rack with one hand



Accessories

Cryogenic tube rack

For self-standing cryogenic tubes and tubes with screw cap. Pack of 4.





Mini cooler, PC

Durable polycarbonate filled with non-toxic gel. Mini coolers hold twelve 0.5 ml to 2.0 ml tubes. Pack of 1.



| Bench temp. maintained | Time held | Color | Cat. No. |
|------------------------|-----------|--------|----------|
| 0 °C | 60 min. | red | 114930 |
| -20 °C | 60 min. | yellow | 114935 |
| -70 °C | 45 min. | white | 114940 |

Microtube rack, PP

Stackable racks with alphanumerical positions. Operating temperature -20 °C to +90 °C. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Density 1.2 g/cm³. Will not float in waterbath. Pack of 5.



| For Ø up to mm | Positions | white Cat. No. | blue Cat. No. | red Cat. No. |
|-------------------|-----------|-------------------|------------------|-----------------|
| 11 | 8 x 16 | 4341050 | 4341051 | 4341052 |
| 13 | 6 x 14 | 4341000 | 4341001 | 4341002 |

Microtube rack, PP

Numbered positions for 20 microtubes, 1.5 ml. Autoclavable at 121 °C (2 bar), acc. DIN EN 285. Pack of 1.

| Cat. No. | 780605 |
|----------|--------|
| | |







Technical information & Ordering data

Microtubes with attached screw cap with silicone seal, non-sterile

- · Easy handling due to attached lid
- For storage in gaseous phase of liquid nitrogen
- Operating range -196 °C to +121 °C
- Autoclavable at 121 °C (2 bar), acc. DIN EN 285










Microtubes with bulk screw cap with silicone seal, sterile



- · High purity polypropylene, DNA-, DNase-, and RNase-free, endotoxine-free, non-mutagenic, non-toxic
- Perfect cap seal to protect against evaporation
- Operating range -196 °C to +121 °C





| | rew caps for crotubes | | | | | |
|---|--------------------------|-------------|-------------|-------------|-------------|-------------|
| С | olor | white | blue | red | green | yellow |
| P | ack of | 1000 pieces |
| С | at. No. | 780740 | 780741 | 780742 | 780743 | 780744 |



Microtubes with bulk tamper-evident screw cap with silicone seal, sterile


- The tamper-evident screw cap guarantees uncontaminated samples
- · For storage in gaseous phase of liquid nitrogen
- Operating range -196 °C to +121 °C



12.7 mm 12.7 mm 12.7 mm 12.7 mm 12.7 mm 44 mm 44.75 mm 45.4 mm 45.0 mm 45.4 mm **Bulk tamper-evident** screw cap with silicone seal, steril 1.5 ml 2 ml Capacity 0.5 ml 1.5 ml 2 ml 44.75 45.4 45.4 45.0 Height [mm] 44 Description self-standing self-standing round-bottom self-standing round-bottom Pack of 500 pieces 500 pieces 500 pieces 500 pieces 500 pieces Cat. No. 780755 780756 780757 780758 780759

Microtubes without screw cap, non-sterile, ungraduated


- Easy identification through different coloured lids
- The tamper-evident screw cap guarantees uncontaminated samples
- For storage in gaseous phase of liquid nitrogen





Microtubes without screw cap, non-sterile, graduated

- High purity polypropylene
- Operating range -196 °C to +121 °C
- Autoclavable at 121 °C (2 bar), acc. DIN EN 285



| Screw caps fo microtubes | r | | | | | |
|--------------------------|---|-------------|-------------|-------------|-------------|-------------|
| Color | | white | blue | red | green | yellow |
| Pack of | | 1000 pieces |
| Cat. No. | | 780740 | 780741 | 780742 | 780743 | 780744 |



11.2 Cryogenic tubes



- ✓ Safe long-term storage down to -196 °C
- ✓ Tight sealed containers
- ✔ High purity polypropylene, RNase-, DNA- and endotoxin-free

Cryopreservation is an essential process for halting almost all chemical reactions during long-term storage and for preventing sample degradation. The most commonly used approach is to store samples in the gas phase of the liquid nitrogen tank, or in freezers. BRAND offers highly stable cryogenic tubes as an ideal choice for safe, long-term storage of biological materials. The right plastic and a precise thread design help perfectly seal these containers, reducing the danger of sample contamination.



Applications

- + Sample storage
- + Aliquoting and sample preparation
- + Extracting nucleic acids and proteins
- + Screening tests

Features

- + High-purity polypropylene with excellent chemical resistance
- + Tight-sealing and easy opening
- + Available in sizes 0.5 ml, 1.5 ml and 2.0 ml
- + Autoclavable at 121 °C (2 bar), acc. DIN EN 285



What does storage under cryogenic conditions mean?

Cryogenic conditions indicate temperatures below approx. -130 °C (approx. < 140 K). This means the temperature is below the temperature at which water turns into a gas. Ice no longer recrystallises, and therefore there is no further growth of ice crystals (BURDEN 1999). This ensures that chemical processes in the samples are minimised, and that morphological changes (ie, ice crystal growth) are

prevented. When samples are stored in the gas phase in liquid nitrogen, the evaporating nitrogen in the sample storage container also creates an inert gas atmosphere that likewise generally prevents samples from changing due to oxygen from the ambient air (oxidation processes).

Examples of products stored under cryogenic conditions are:

- · Sperm, egg cells
- · Stem cells, bone marrow
- Blood components, such as erythrocytes
- · Heart valves
- · Skin, bones, teeth
- Samples for DNA analysis in genetic engineering.

Source: Dr. Heinz Rüdel, Martin Weingärtner, Fraunhofer Institute for Molecular Biology and Applied Oncology; Title: Lagerung von Umweltproben unter Cryobedingung; December 2008, V 2.0.0



Comparison of thread types



Advantages of external thread with sealing lid and silicone seal

- Simplifies single-handed operation in comparison to cryogenic tubes with internal thread.
- Reduces the danger of contamination.



Advantages of internal thread

- Space-saving compared to cryogenic tubes with external thread.
- Colored cap inserts snap in farther. Tubes can be removed from the box using the rod.
- Uniform exterior diameter improves fit with centrifuge rotors.




A

Technical information and ordering data for cryogenic tubes is available in chapter I "Cell culture" starting on page 22, and in our online shop at shop.brand.de



Correct sample storage

When choosing correct materials for different storage conditions, storage duration and temperature are key in addition to the sample to be stored. The lower the storage temperature required for safe storage, the greater the temperature fluctuations the vessel must withstand, as well as the closure especially when freezing and thawing the vessel.



Repeated thawing and freezing may have a negative effect on the quality of your samples. We recommend creating aliquots and freezing these.

| Storage down to -20°C | Storage down to -80 °C | Storage down to -196°C |
|---|--|--|
| Short-term storageIntermediate storage | Long-term storage of non-critical samples Intermediate storage of sensitive samples | DatabasesStorage of cell culturesLong-term storage |

Overview of different closure options for plates

| | Lid | Sealing mats | Sealing films |
|------------------------|--|--|---|
| Use | Easy closure for short - term storage . Caps offer only minor protection against evaporation. | For intermediate storage and protection during use. Good evaporation reduction. | For long-term storage. Films reduce evaporation to a minimum and offer long-term sealing for plates. |
| Evaporation protection | V | V V | V V V |
| Transparency | V V | - | -/ ~ |
| Simple handling | V V V | V V | V V V |
| Costs | V V V | V V V | V V |

Trademark Index

accu-jet®, BIO-CERT®, BLAUBRAND®, BRAND®, BRAND. For lab. For life.®, BRANDplates®, cellGrade™, Dispensette®, hydroGrade™, immunoGrade™, inertGrade™, lipoGrade™, pureGrade™, seripettor®, Transferpette®, as well as the figurative marks depicted here and the BRAND figurative mark are registered trademarks or trademarks of BRAND GMBH + CO KG, Germany.

All other trademarks mentioned or depicted here are the property of the respective owners.

